





**Brunswick Harbor
OCEAN DREDGED MATERIAL DISPOSAL SITE**

**SITE MANAGEMENT
AND MONITORING PLAN**

May 2012



**US Army Corps
of Engineers®**



This page left blank intentionally.

The following Site Management and Monitoring Plan (SMMP) for the Brunswick Ocean Dredged Material Disposal Site (ODMDS) has been developed and agreed to pursuant to the Marine Protection, Research, and Sanctuaries Act of 1972 (MPRSA), as amended by the Water Resources Development Act Amendments of 1992 (WRDA 92), for the management and monitoring of ocean disposal activities, as resources allow, by the US Environmental Protection Agency (EPA) and the US Army Corps of Engineers (USACE).

Jeffrey M. Hall
Colonel, District Commander
US Army Corps of Engineers,
Savannah District
Savannah, Georgia

Date

Gwendolyn Keyes Fleming
Regional Administrator
US Environmental Protection Agency
Region 4
Atlanta, Georgia

Date

This plan is effective from the date of signature for a period not to exceed 10 years. The plan shall be reviewed and revised more frequently if site use and conditions indicate a need for revision.

BRUNSWICK ODMDS**SITE MANAGEMENT AND MONITORING PLAN**TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
1.0 INTRODUCTION	1
1.1 Site Management and Monitoring Plan Team	1
2.0 SITE MANAGEMENT	2
2.1 Disposal Site Characteristics.....	3
2.2 Management Objectives.....	5
2.3 Dredged Material Volumes.....	5
2.4 Dredged Material Suitability.....	7
2.5 Time of Disposal.....	7
2.6 Disposal Techniques	8
2.7 Disposal Location	8
2.8 Permit Process.....	8
2.9 Permit and Contract Conditions.....	9
2.10 Information Management of Dredged Material Placement Activities.....	9
3.0 SITE MONITORING	10
3.1 Baseline Monitoring.....	10
3.2 Disposal Monitoring	11
3.3 Post Discharge Monitoring	12
3.4 Material Tracking and Disposal Effects Monitoring	13
3.4.1 Summary of Results of Past Monitoring Surveys.....	13
3.4.2 Future Monitoring Surveys.....	13
3.5 Reporting and Data Formatting	15
4.0 ANTICIPATED SITE USE	16
5.0 MODIFICATION OF THE BRUNSWICK ODMDS SMMP	16
6.0 IMPLEMENTATION OF THE BRUNSWICK ODMDS SMMP.....	16
7.0 REFERENCES.....	16

LIST OF FIGURESFigure No.

Figure 1. Brunswick ODMDS Location Map and Operational Boundaries

LIST OF TABLESTable No.

Table 1. Yearly Record of Dredged Material Disposal in the Brunswick ODMDS
Table 2. Cross References to Permit and Contract Conditions for Site Monitoring
Table 3. Surveys and Studies Conducted at the Brunswick ODMDS
Table 4. Brunswick ODMDS Monitoring Strategies and Thresholds for Action

APPENDICES

Appendix A: Water Column Evaluations Numerical Model (STFATE) Input Parameters
Appendix B: Generic Special Conditions for MPRSA Section 103 Permits
Appendix C: Generic Contract Specification Language
Appendix D: Brunswick ODMDS Bathymetry

BRUNSWICK ODMDS

SITE MANAGEMENT AND MONITORING PLAN

1.0 INTRODUCTION

It is the responsibility of the US Environmental Protection Agency (EPA) and the US Army Corps of Engineers (USACE) under the Marine Protection, Research, and Sanctuaries Act (MPRSA) of 1972 to manage and monitor each of the Ocean Dredged Material Disposal Sites (ODMDS) designated by the EPA pursuant to Section 102 of MPRSA. The goal of this management is to ensure that ocean dredged material disposal activities will not unreasonably degrade the marine environment or endanger human health or economic potential.

In 1989, EPA designated the Brunswick ODMDS as an approved dumping site (40 CFR 228.15(h)(7)). This SMMP specifically addresses the disposal of dredged material into the Brunswick ODMDS. The plan includes past monitoring results and complies with provisions of the Water Resources Development Act (WRDA) of 1992 and the Memorandum of Agreement (MOA) between EPA and USACE (EPA and USACE, 2007).

The first SMMP for the Brunswick ODMDS was included in the Brunswick Harbor Deepening EIS, approved in May 1999. This Brunswick ODMDS SMMP supersedes the 1999 SMMP and has been prepared in accordance with the *Guidance Document for Development of Site Management Plans for Ocean Dredged Material Disposal Sites* (EPA and USACE 1996). That document provides a framework for the development of SMMPs required by MPRSA and WRDA 92. The SMMP may be modified if it is determined that such changes are warranted as a result of information obtained during the monitoring process. Pursuant to Section 102(c)(3) of the MPRSA, this SMMP will be reviewed and revised as needed or every ten years, whichever time period is shorter.

Upon execution of this SMMP, the provisions herein shall be requirements for all future dredged material disposal activities at the Brunswick site. All Section 103 (MPRSA) ocean disposal permits or evaluations shall be conditioned as necessary to assure consistency with the SMMP.

1.1 SMMP Team. We view the following agencies and their respective representatives as an interagency team whose comments will be considered during the final preparation of this document:

- USACE, Savannah District
- Georgia Department of Transportation
- Environmental Protection Agency, Region 4
- Georgia Department of Natural Resources

Other agencies, such as the National Marine Fisheries Service (NMFS), the US Fish and Wildlife Service (USFWS), the Bureau of Ocean Energy Management (BOEM), and the Bureau of Safety and Environmental Enforcement (BSEE) will be asked to participate where appropriate. EPA and USACE, Savannah District will evaluate existing monitoring data, the type of disposal (i.e., operations and maintenance (O&M) vs. new work), the type of material (i.e., sand vs. mud), the location of placement within the ODMDS, and the quantity of material.

Specific responsibilities of EPA and the USACE, Savannah District are:

EPA: EPA is responsible for designating/de-designating MPRSA Section 102 ODMDS, evaluating environmental effects of disposal of dredged material at these sites, and reviewing and concurring on dredged material suitability determinations.

USACE: USACE is responsible for evaluating dredged material suitability, issuing MPRSA Section 103 permits, regulating site use, and developing and implementing disposal monitoring programs.

2.0 SITE MANAGEMENT

ODMDS management involves a broad range of activities including the regulation of: the schedule of use, the quantity, and the physical/chemical characteristics of dredged materials disposed of at the site. It also involves establishing disposal controls and conditions and requirements to avoid and minimize potential impacts to the marine environment. Finally, ODMDS management involves monitoring the site environs to verify that unanticipated or significant adverse effects are not occurring from past or continued use of the site and that permit conditions are met.

Section 228.3(a) of the Ocean Dumping Regulations (40 CFR 220 - 229) states:

Management of a site consists of regulating times, rates, and methods of disposal and quantities and types of materials disposed of; developing and maintaining effective ambient monitoring programs for the site; conducting disposal site evaluation studies and designation studies; and recommending modifications in site use and/or designation.

The plan may be modified if it is determined that such changes are warranted as a result of information obtained during the monitoring process. MPRSA, as amended by WRDA 92, provides that the SMMP shall include but not be limited to:

- A baseline assessment of conditions at the site;
- A program for monitoring the site;
- Special management conditions or practices to be implemented at each site that are necessary for the protection of the environment;

- Consideration of the quantity and physical/chemical characteristics of dredged materials to be disposed of at the site;
- Consideration of the anticipated use of the site over the long-term; and
- A schedule for review and revision of the plan.

2.1 Disposal Site Characteristics. The Brunswick ODMDS (Figure 1) encompasses an area of 2.0 square nautical miles (NM) within a 1.0 by 2.0 NM rectangular site located about 6.6 NM east of the coastline and 2 NM south of the whistle buoy at mile 8 of the Brunswick Bar Channel. The corner coordinates are as follows:

ODMDS Geographic Coordinates (NA D27)

31°02'35"N	81°17'40"W
31°02'35"N	81°16'30"W
31°00'30"N	81°16'30"W
31°00'30"N	81°17'42"W

State Plane Coordinates (meters)

235658.71E	115945.69N
237514.86E	115960.43N
237545.74E	112111.07N
235635.86E	112095.93N

The Brunswick ODMDS has received an annual average of approximately 1 million cubic yards (cy) of dredge material from the Brunswick Harbor Navigation Project (1976-2012). The ODMDS was not used in 2009, 2010 and 2011. Project sediments typically range from 2 to 72 percent fine-grained material depending on their location along the length of the channel. Sediment physical, chemical, toxicological, and bioaccumulation conditions at the ODMDS and of the dredge material to be placed in the ODMDS are described in the *Final Report, Brunswick Harbor Navigation Project, Brunswick, Georgia* (Section 103 Evaluation Report, Anamar Environmental Consulting, Inc.) and *Brunswick ODMDS – Status and Trends, May 2007 (U.S. EPA)*.




Figure 1: Brunswick ODMDS location map and operational boundaries.

2.2 Management Objectives. There are three primary objectives in the management of the Brunswick ODMDS:

- Protect the marine environment, living resources, and human health and welfare;
- Document disposal activities at the ODMDS and provide information which is useful in managing the dredged material disposal activities; and
- Provide for beneficial use of dredged material whenever practical, particularly nearshore placement of suitable sediments.

The objective of the SMMP is to provide guidelines in making management decisions necessary to fulfill mandated responsibilities to protect the marine environment as discussed previously. An appropriate SMMP narrows the uncertainty of unforeseeable effects and reduces the level of risk associated with the activity to foster a sound and informed decision. The following sections provide the framework for meeting these objectives.

2.3 Dredged Material Volumes. It is intended that the Brunswick ODMDS will be used for the disposal of material dredged (both maintenance and construction or new work material) from the Brunswick entrance channel oceanward of the Sidney Lanier Bridge (U.S. Highway 17). The primary user of the Brunswick ODMDS is the USACE for Civil Works. The site is designated for disposal of dredged material from the Brunswick Harbor area.

Between 1964 and 2012, approximately 38 million cy of dredged material has been disposed in the Brunswick ODMDS. Disposal volumes since 1976 are listed in Table 1. Based on a February 2012 Savannah District bathymetric survey, the capacity of the site is estimated to be approximately 21,500,000 cy to a fill depth of -25 feet Mean Lower Low Water (MLLW).

Table 1. Yearly Record of Dredged Material Disposal in the Brunswick ODMDS

Year	Cubic Yards (cy)
1976	2,260,700
1977	800,000
1978	2,449,900
1979	57,400
1980	2,246,900
1982	817,700
1983	685,100
1984	1,674,800
1986	2,583,000
1987	309,100

Year	Cubic Yards (cy)
1988	1,993,400
1989	1,500,700
1991	1,215,000
1993	1,472,200
1995	988,100
1996	803,501
1997	1,076,261
1998	1,088,977
1999	948,158
2000	1,332,000
2001	1,459,163
2002	584,075
2004	1,567,328
2005	965,962
2008	306,033
2012	264,527

Future volumes and rates of disposal from the Brunswick Harbor area are expected to be approximately 1 million cy per year. However, future actions including deepening and/or widening the Federal navigation channel into Brunswick Harbor may affect long-term life expectancy of the site and require consideration of alternative disposal sites (e.g., designation of a new Brunswick ODMDS). Civil works maintenance projects for Brunswick Harbor are anticipated to account for approximately 100% of the total volume of material to be disposed at the ODMDS and nearshore sediment placement areas. No private applicants are expected.

The Brunswick ODMDS has been determined to be a dispersive site. However, the dispersiveness of the site, and consequently the ultimate capacity of the ODMDS, is subject to unpredictable variability. Past surveys indicate the ODMDS may lose approximately 800,000 cy per year. The 1988 Final EIS for designation of the Brunswick ODMDS placed no restrictions on disposal volumes. Due to the unknowns regarding dispersiveness and capacity, a capacity analysis will be conducted by the site user prior to disposal of significant quantities of material from any new work project. Significant quantities are considered those in excess of historical usage, i.e. 1 million cubic yards per year. The capacity analysis should utilize USACE developed models including MDFATE, MPFATE, STFATE and/or LTFATE to simulate the disposal of the new work project and to determine an appropriate disposal strategy (i.e. release zone) to prevent excessive mounding (see Section 2.7) and impacts outside of the ODMDS as defined by deposition of 5 cm or more.

2.4 Dredged Material Suitability. Two basic sources of sediment are expected to be placed at the site -- new work material and maintenance dredged sediment. These materials consist of mixtures of silts, clays, and sands in varying percentages. Sediments dredged for navigation in Brunswick Harbor are derived from mainly ocean and estuarine sources. Shoals occur where specific physical factors promote deposition or movement of sediments. These factors may vary spatially and temporally.

The placement of any significant quantities of beach-compatible sand from future projects will be determined on a project-by-project basis. Utilization of any significant quantities of beach-compatible dredged sediment for beach nourishment is strongly encouraged and supported by EPA and the USACE. The USACE manages its dredged material under its Regional Sediment Management (RSM) initiative which encourages beneficial use of excavated sediment. As a result, the USACE evaluates the whole coastal system when managing dredged material placement rather than focusing on an individual project. Placement of non-beach quality sand should be planned to allow the material to be placed so that it will be within or accessible to the sand-sharing system, to the maximum extent practical, and following the provisions of the Clean Water Act.

The suitability of dredged material for ocean disposal must be verified by the USACE and agreed to by EPA prior to disposal. Verification will be valid for three years from the date of last verification. Verification will involve (40 CFR 227): 1) a case-specific evaluation against the exclusion criteria; 2) a determination of the necessity for testing, including bioassay (toxicity and bioaccumulation) testing for non-excluded material based on the potential for contamination of the sediment since last tested; and 3) testing (when deemed necessary) and determining that the non-excluded, tested material is suitable for ocean disposal.

Documentation of verification will be completed prior to use of the site. Documentation will be in the form of a MPRSA Section 103 Evaluation. The evaluation, and any testing, will follow the procedures outlined in the 1991 *EPA/Corps Dredged Material Testing Manual* and the 2008 *Southeast Regional Implementation Manual (SERIM)*. Water Quality Compliance determinations should be made using the STFATE (ADDAMS) model and the input parameters provided in Appendix A or approved modifications. Only material determined to be suitable through the verification process by the USACE and EPA will be placed at the Brunswick ODMDS.

2.5 Time of Disposal. At present, no restrictions have been determined to be necessary for disposal related to seasonal variations in ocean current or biota activity. As monitoring results are compiled, should any such restriction appear necessary, disposal activities will be scheduled so as to avoid adverse impacts. The USACE currently restricts hopper dredging to the period of 15 December through 31 March to protect sea turtles. This window may be adjusted in the future through coordination with NMFS and the USACE South Atlantic Division (SAD). The USACE also requires monitoring for sea turtles, Shortnose and Atlantic sturgeon, and North Atlantic right whales (NARW). Additionally, if new information indicates that endangered or threatened species are being adversely impacted, restrictions may be imposed.

2.6 Disposal Techniques. No specific disposal technique is required for this site. However, to protect NARW, disposal vessel speed (either hopper dredge or tug and scow) and operation will be restricted in accordance with the most recent USACE SAD Endangered Species Act Section 7 Consultation Regional Biological Opinion for Dredging of Channels and Borrow Areas in the Southeastern United States. In addition, 50 CFR §224.103(c)(1)(i) prohibits any person, including the disposal vessel's captain, from approaching within 500 yards of a right whale by vessel, aircraft, or any other means.

2.7 Disposal Location. In accordance with 40 CFR §227.28, disposal shall occur no less than 100 meters (330 feet) inside the site boundaries. The USACE will prevent mounded dredged material from becoming a navigation hazard. Dredged material shall be placed so depths will be no less than -25 feet MLLW (i.e., a clearance will be maintained 25 feet above the bottom) where a depth of -30 feet is the warning threshold for monitoring and management purposes. If -30 feet MLLW is reached, then management decisions will be made on future sediment placement to avoid exceeding the -25 foot MLLW threshold. In order to maximize capacity and monitoring efforts, disposal shall be within a specific area within the ODMDS identified by the USACE in consultation with EPA, Region 4. To implement this provision, the USACE will coordinate with EPA after the most recent post-disposal project bathymetric surveys are available to identify whether any placement restrictions should be considered for the next sediment disposal event. Depths at the time of disposal will be monitored to detect if adjustments of disposal methods are needed to prevent unacceptable mounding (i.e. navigational hazards). The physical removal or leveling of material above -25 feet MLLW are potential management alternatives should mound heights occur that are greater than those elevations. Disposal shall be limited within the disposal release zone and shall be completed (doors closed) prior to departing the ODMDS.

The capacity of the ODMDS can be preserved whenever suitable sediments can be deposited in an approved nearshore placement area rather than in the ODMDS. Placement of sediments in the nearshore environment may occur at locations identified in Figure 1. Placement of material in nearshore feeder berms may occur in the future provided the sediments are determined suitable for nearshore placement and the placement is determined to be practicable. Submerged nearshore sediment placement mounds may allow wave action to move the sediments towards the mudflat, marsh and/or upland area along the shore, aiding in the stabilization of this estuarine environment from erosion. The mounds may also provide protection from storm events. Placement of suitable sediment at a nearshore site would provide beneficial uses of dredged sediment and support the goals of the Georgia Coastal Management Program and the Rivers and Harbor Development Act (O.C.G.A. 52-9-2).

2.8 Permit Process. All disposal of dredged material in the ocean, with the exception of Federal Civil Works projects, requires an ocean dumping permit issued by the USACE pursuant to Section 103 of the MPRSA. A summary of the permitting process can be

found at:

http://www.epa.gov/region4/water/oceans/Dredged_Material_Permit_Process.html.

2.9 Permit and Contract Conditions. The disposal monitoring and post-disposal monitoring requirements described under Section 3, Site Monitoring, will be included as permit conditions on all MPRSA Section 103 permits and will be incorporated in the contract language for all Federal projects. Cross references to the management and monitoring requirements are listed in Table 2.

Table 2. Cross references to Permit and Contract Conditions for Site Monitoring

Condition	SMMP Reference
Dredged Material Suitability and Term of Verification	Page 7, ¶ 2.4
Disposal within Appropriate Zones	Page 8, ¶ 2.7
Disposal Monitoring and Recording of Disposal Locations	Page 11, ¶ 3.2
Post Bathymetric Surveys within 60 days of Project Completion	Page 12, ¶ 3.3
Reporting Requirements: Daily & Monthly Operations Reports and Disposal Summary Reports within 90 Days of Project Completion	Page 15, ¶ 3.5

2.10 Information Management of Dredged Material Placement Activities. As discussed in the following sections, a substantial amount of diverse data regarding use of the Brunswick ODMDS and the effects of disposal is required from many sources. If this information is readily available and in a useable format, it can be used to answer many questions typically asked about a disposal site:

- What is being dredged?
- How much is being dredged?
- Where did the dredged material come from?
- Where was the dredged material placed?
- Was dredged material dredged and placed correctly?
- What will happen to the environment at the disposal sites?

In an attempt to streamline data sharing, EPA Region 4 and USACE South Atlantic Division have agreed on an eXtensible Markup Language (XML) standard for sharing of disposal monitoring data (see also Section 3.5). Additional standards will continue to be

investigated for sharing of other disposal site related information (e.g., environmental monitoring data, testing data, etc.).

The USACE has an Ocean Disposal Database maintained by the Engineering Research and Development Center (ERDC). This database provides the quantities disposed of at the ODMDS along with the chemical, physical, and biological information, and whether the project is from a civil works project or private entity.

3.0 SITE MONITORING

The implementing regulations of the MPRSA require that a monitoring program be included in the SMMP (40 CFR 228.3). Site monitoring is conducted to preserve the environmental integrity of a disposal site and the areas surrounding the site, and to verify compliance with the site designation criteria, special management conditions, and permit requirements. Monitoring programs should be flexible, cost effective, and based on scientifically sound procedures and methods to meet site-specific monitoring needs. A monitoring program should detect changes to the environment caused by disposal activities and assist in determining regulatory and permit compliance. The intent of the monitoring program is to provide the following:

- (1) Information indicating whether the disposal activities are occurring in compliance with the permit and site restrictions; and/or
- (2) Information concerning the short-term and long-term environmental impacts of the disposal; and/or
- (3) Information indicating the short-term and long-term fate of materials disposed of in the marine environment.

The main purpose of a disposal site monitoring program is to determine whether dredged material site management practices, including disposal operations at the site, need to be changed to avoid significant adverse impacts.

3.1 Baseline Monitoring. Disposal has occurred at the present site since the 1960s and predates any data gathering at the site. Therefore, no true baseline information has or can be collected. The results of investigations presented in EPA's 1988 Site Designation EIS and subsequent surveys listed in Table 3 serve as the main body of data for the monitoring of the impacts associated with the use of the Brunswick ODMDS.

Table 3. Surveys and Studies Conducted at the Brunswick ODMDS

Survey/Study Title	Conducted By	Date	Purpose	Results
Sea-bed Drifter Study	GA DNR	1982	Determine direction of sediment transport	Baseline Survey - General trend of movement was due westward away from ODMDS
Environmental Study (COE contract #DACW 21-84-C-005)	GA Institute of Technology	1985	Support permanent designation of Brunswick ODMDS	Baseline Survey-no significant adverse effects to biota, water or sediment quality from previous dumping
Sediment Mapping	UGA Center for Applied Isotopes for EPA	February 1995	Characterization of bottom sediments using gamma spectrometry	Baseline Survey
Investigation of Dredged Sediment Movement and Fate	Evans Hamilton, Inc, for ERDC	2004	Describe sediment movement at the entrance to Brunswick Harbor	The Brunswick study was designed to provide an initial data set to assess the models performance for coastal regions similar to those at Brunswick, GA
Status and Trends Report	EPA	December 2007	Assess status of benthos and water column within and adjacent to ODMDS	No significant differences found
Bathymetric Survey	USACE	Before and After Disposal Event	Monitor bathymetry changes	Database
Disposal Monitoring	USACE	During each Event	Compliance	Database

3.2 Disposal Monitoring. For all disposal activities, an electronic tracking system (ETS) must be used. The ETS will provide surveillance of the transportation and disposal of dredged material. The ETS will be maintained and operated to continuously track in real-time the horizontal location and draft condition (nearest 0.5 foot) of the disposal vessel (i.e. hopper dredge or disposal scow) from the point of dredging to the disposal site, and return to the point of dredging. Data shall be collected at least every 500 feet during travel to and from the ODMDS and every minute or every 200 feet of travel, whichever is smaller, while approaching within 1,000 feet of the boundary of the ODMDS and within

the ODMDS. The following information shall be electronically recorded for each disposal cycle:

- Contractor Name
- Load Number
- Disposal Vessel Name and Type (e.g. scow)
- Tow or Trawler Vessel Name (if applicable)
- Volume and Description of Material Disposed
- Source of Dredged Material
- Date, Time and Location at Initiation and Completion of Disposal Event (State Plane Coordinates)

It is expected that disposal monitoring will be conducted using the National Dredging Quality Management (DQM) Program for Civil Works projects [see <http://dqm.usace.army.mil/Specifications/Index.aspx>], although other systems may be deemed acceptable upon mutual agreement between the USACE and EPA. Disposal monitoring and ETS data are expected to be reported to EPA Region 4 on a weekly basis using the eXtensible Markup Language (XML) specification and protocol per Section 3.5. EPA Region 4 and the USACE Savannah District shall be notified within 24 hours if disposal occurs outside of the ODMDS or specified disposal zone or if excessive leakage occurs. EPA has defined excessive leakage as any change in draft exceeding 1.5 feet from the point of departure from the dredging site to the disposal site.

3.3 Post Discharge Monitoring. The USACE, or other site user, will conduct a bathymetric survey within 60 days after disposal project completion; however, surveys are not required for projects less than 50,000 cy. Surveys will conform to the minimum performance standards for USACE Hydrographic Surveys for “Other General Surveys & Studies” as described in the USACE Engineering Manual, EM1110-2-1003, *Hydrographic Surveying*, dated January 1, 2002 [http://publications.usace.army.mil/publications/eng-manuals/EM_1110-2-1003_pfl/toc.htm]. The number and length of transects required will be sufficient to encompass the ODMDS and a 500-foot wide area around the site. In coordination with EPA, the Savannah District may reduce the survey area on a case-by-case basis if disposal zones are specified and adhered to. The surveys will be taken along lines spaced at 500-foot intervals or less. The minimum performance standards from Table 3-1 in *Hydrographic Surveying* shall be followed. Horizontal location of the survey lines and depth sounding points will be determined by an automated positioning system utilizing either a microwave line of site system or differential global positioning system. The vertical datum will be referenced to prescribed NOAA MLLW datum, 1983-2001 epoch, as shown on the Tidal Benchmark sheet for St. Simons Island, GA (Station ID: 8677344). MLLW is 3.23 feet below NGVD 1929. The horizontal datum will be Georgia State Plane (zone 1001 GA East, NAD 1983). Bathymetric surveys will be used to monitor the disposal mound to ensure a navigation hazard is not produced, to assist in verification of material placement, to monitor bathymetric changes and trends, to aid in environmental effects monitoring, and to ensure that the site capacity is not exceeded,

i.e., the mound does not exceed the site boundaries. Copies of these surveys shall be provided to EPA, Region 4 when completed.

The interagency team will meet to review the results of these surveys and determine whether more information is needed. This need will be based on observance of any anomalies or potential adverse impacts associated with a specific event. If the results of the bathymetric surveys do not indicate any anomalies or adverse impacts, no additional monitoring will be required for the disposal event. Reassessment of the site may be undertaken, possibly every 10 years. This reassessment may include benthic macrofaunal and sediment chemistry surveys. Additional surveys for water quality, sediment mapping, or the use of remote sensing equipment may also be required.

3.4 Material Tracking and Disposal Effects Monitoring. Surveys can be used to address possible changes in bathymetric, sedimentological, chemical, and biological aspects of the ODMDS and surrounding areas as a result of the disposal of dredged material at the sites.

3.4.1 Summary of Results of Past Monitoring Surveys. The surveys/studies listed in Table 3 have indicated that the ODMDS is a dispersive site for fine-grained material and as a result dredged material may move beyond the designated site boundaries.

3.4.2 Future Monitoring Surveys. Based on the type and volume of material disposed, various monitoring surveys can be used to examine if, and the direction, the disposed dredged material is moving, and the environmental effects to the site and adjacent areas caused by the material.

At the current time, no nearby biological resources have been identified that are of concern for potential impact and, at the time of designation, no known hard-bottom areas were within close proximity to ODMDS boundaries. The site has been designated as dispersive. This means that it is expected that material will move outside the site boundaries. It is also expected that this material will not move in distinct mounds, but instead will blend with the surrounding environment causing a progressive transition to sediments containing a higher percentage of silt and clay. Changes in sediment composition may alter the benthic community structure. However, based on previous benthic studies, it is unlikely that permanent or long-term adverse impacts will result due to changes in sediment composition.

Future surveys as outlined in Table 4 will focus on determining the rate and direction of disposed dredged material dispersal and the capacity of the ODMDS. The management plan may require revision based on the outcome of any monitoring program.

Table 4. Brunswick ODMDS Monitoring Strategies and Thresholds for Action

Goal	Technique	Sponsor	Rationale	Frequency	Threshold for Action	Management Options	
						Threshold Not Exceeded	Threshold Exceeded
Monitor Bathymetric Trends	Bathymetry	Site User	Determine the extent of the disposal mound and major bathymetric changes	Post Disposal	Disposal mound occurs outside ODMDS boundaries	Continue monitoring	<ul style="list-style-type: none"> - Modify disposal method or placement - Restrict disposal volumes
Benthic Effects Monitoring	Sediment Profile Imaging	EPA	Determine aerial influence of dredged material	As Necessary	Communities under the influence of dredged material outside the site have significant differences in diversity/richness/biomass from those not under dredged material influence after one-year recovery period	Discontinue monitoring unless disposal quantities, type of material or frequency of use significantly changes	<ul style="list-style-type: none"> - Limit quantity of dredged material to prevent impacts outside boundaries - Create berms to retard dredged material movement - Cease site use
	Benthic Survey		Determine impact of dredged material on benthic community				
Short & Long-Term Fate of Disposed Dredged Material	<ul style="list-style-type: none"> - Modeling - Erosional Analysis 	USACE	Determine dispersiveness of site and aerial extent of impact	As resources allow	Aerial extent of impact reaches resources of concern and /or increases over time	Continue to use site without restrictions	<ul style="list-style-type: none"> - Restrict disposal volumes - Create berms to retard dredged material transport - Cease site use/designate new site
Site Capacity	Information from Long-Term Fate	USACE/EPA/Site Users	Determine dispersiveness of site and long and short term capacity	As resources allow	- New work and/or maintenance volumes exceed estimated capacity	Continue to use site without restrictions	<ul style="list-style-type: none"> - Enlarge site or designate new site
Ensure Safe Navigation Depth	Bathymetry	Site User	Determine height of mound and any excessive mounding	Post disposal	Mound height > -30 feet MLLW	Continue monitoring	<ul style="list-style-type: none"> - Modify disposal method or placement - Restrict disposal volumes
					Mound height > -25 feet MLLW	Continue monitoring	<ul style="list-style-type: none"> - Halt disposal - Physically level material

Goal	Technique	Sponsor	Rationale	Frequency	Threshold for Action	Management Options	
						Threshold Not Exceeded	Threshold Exceeded
Compliance	Disposal Site User Records	Site User	<ul style="list-style-type: none"> - Ensure management requirements are being met - To assist in site monitoring 	Daily during the project	Disposal records required by SMMP are not submitted or are incomplete	Continue monitoring	- Restrict site user until requirements are met
					Review of records indicated a dump occurred outside ODMDS boundaries		- Notify EPA, Region 4/USACE, and investigate why egregious dump(s) occurred - EPA may take appropriate enforcement action
					Review of records indicated a dump occurred outside of ODMDS target area		- Direct placement to occur as specified

3.5 Reporting and Data Formatting. Disposal monitoring data are expected to be provided to EPA Region 4 electronically on a weekly basis. Data shall be provided per the EPA Region 4 XML format (USEPA, Region 4, 2007) and delivered as an attachment to an email to DisposalData.R4@epa.gov. The XML format is available from EPA Region 4.

Disposal summary reports shall be provided to EPA within 90 days after project completion. These reports should include: dates of disposal; dredging project; volume disposed, number of loads completed, type of material disposed; contractor conducting the work, permit and/or contract number; identification of any misplaced material; and dates of bathymetric surveys of the ODMDS. The disposal summary reports should be accompanied by the bathymetry survey results (paper plot and X, Y, Z ASCII data file), track plots for each disposal trip, a scatter plot of all dump locations, and a summary table of the information required by Section 3.2. If all data are provided in the required XML format, track plots, scatter plots and summary tables will not be necessary.

The user will be required to prepare and submit to the USACE daily reports of operations and a monthly report of operations for each month or partial month's work. The user is also required to notify the USACE and the EPA within 24 hours (or next business day) if a violation of the permit and/or contract conditions occur during disposal operations. In the case of large new work projects where the material is expected to consist of stiff

clays, it is recommended that mid-project bathymetric surveys be conducted of the disposal area to ensure that mounding limits are not being exceeded.

4.0 ANTICIPATED SITE USE

It is anticipated that there will be a need for use of the Brunswick ODMDS for many years. The site will be used to dispose of approximately 1 million cy per year. This projection is based on 1964-2012 dredging records, currently available dredged material disposal options, and the USACE planning documents. This volume may be reduced with continued USACE use of the nearshore feeder berms.

5.0 MODIFICATION OF THE BRUNSWICK ODMDS SMMP

If the results of the monitoring surveys or valid reports from other sources indicate that continued use of the ODMDS would lead to unacceptable effects, the ODMDS management will be modified to mitigate the effects. The SMMP will be reviewed and updated at least every 10 years or if site use changes significantly. For example, the SMMP will be reviewed if the quantity or type of dredged material placed at the site changes significantly or if conditions at the site indicate a need for revision. The plan should be updated in conjunction with activities authorizing use of the site.

6.0 IMPLEMENTATION OF THE BRUNSWICK ODMDS SMMP

This plan is effective from the date of signature for a period not to exceed 10 years.

The plan shall be reviewed and revised more frequently if site use and conditions at the sites indicate a need for revision. The EPA and the USACE shall share responsibility for implementation of the SMMP. Site users may be required to undertake monitoring activities as a condition of their permit. The USACE will be responsible for implementation of the SMMP for Federal maintenance projects.

7.0 REFERENCES

Anamar, 2010. Brunswick Harbor Navigation Project Section 103 Report, Prepared for the Savannah District USACE under contract W91278-08-D-0053 by ANAMAR Environmental Consulting, Inc. Final June 2010.

Evans Hamilton, 2004. Data Report for Field Measurement Program in Support of Investigation of Dredged Sediment Movement and Fate at the Entrance to Brunswick Harbor, Georgia. Draft V1.0 March 16, 2004, Prepared for United States Army Corps of Engineers Engineering Research and Development Center by Evans Hamilton Inc., Charleston, South Carolina 29412, under Contract No. DACW39-99-D-008, Delivery Order No. 33

Fredette, Thomas J., Nelson, David A., Clausner, James E., and Anders, Fred J. 1990. *Guidelines for Physical and Biological Monitoring of Aquatic Dredged Material*

Disposal Sites, Technical Report D-90-12, US Army Engineer Waterways Experiment Station, Vicksburg, MS.

Pequegnat, Willis E., Gallaway, Benny J., and Wright, Thomas D., 1990. *Revised Procedural Guide for Designation Surveys of Ocean Dredged Material Disposal Sites*, Technical Report D-90-8, US Army Engineer Waterways Experiment Station, Vicksburg, MS.

US Army Corps of Engineers (USACE). 2002. *Hydrographic Surveying*. Engineering Manual 1110-2-1003, Department of the Army, Washington D.C.

US Environmental Protection Agency, 2007. *Brunswick ODMDS - Status and Trends, December 2007*. US Environmental Protection Agency, Region 4, Water Management Division, Wetlands, Coastal & Nonpoint Source Branch, Coastal Section, SNAFC, 61 Forsyth St. SW, Atlanta, GA 30303.

US Environmental Protection Agency, Region 4, 2007. *Dredged Material Ocean Disposal Verification System - Specifications for Data Submittal*, revised October 30, 2007. Prepared by Wetlands and Marine Regulatory Section.

US Environmental Protection Agency and US Army Corps of Engineers, 1991. *Evaluation of Dredged Material Proposed for Ocean Disposal (Testing Manual)*, February 1991. Prepared by Environmental Protection Agency Office of Marine and Estuarine Protection and Department of Army United States Army Corps of Engineers under EPA Contract No. 68-C8-0105.

US Environmental Protection Agency and US Army Corps of Engineers, 1996. *Guidance Document for Development of Site Management Plans for Ocean Dredged Material Disposal Sites*, February 1996. Prepared by Environmental Protection Agency Office of Water and Department of Army United States Army Corps of Engineers.

US Environmental Protection Agency Region 4 and US Army Corps of Engineers South Atlantic Division, 2007. *Memorandum of Understanding Between US EPA Region 4 and the USACE South Atlantic Division on Ocean Dredged Material Disposal*, March 2007.

US Environmental Protection Agency, Region 4 and US Army Corps of Engineers South Atlantic Division, 2008. *Southeast Regional Implementation Manual (SERIM) Requirements and Procedures for Evaluation of the Ocean Disposal of Dredged Material in Southeastern U.S. Atlantic and Gulf Coastal Waters*, August 2008.

APPENDIX A

**WATER COLUMN EVALUATIONS
NUMERICAL MODEL (STFATE) INPUT PARAMETERS**

This page left blank intentionally.

Water Column Evaluations
Numerical Model (STFATE) Input Parameters
Brunswick ODMDS

SITE DESCRIPTION

Parameter	Value	Units
Number of Grid Points (left to right)	76	
Number of Grid Points (top to bottom)	76	
Spacing Between Grid Points (left to right)	250	ft
Spacing Between Grid Points (top to bottom)	250	ft
Constant Water Depth	30	ft
Roughness Height at Bottom of Disposal Site	.005 ¹	ft
Slope of Bottom in X-Direction	0	Deg.
Slope of Bottom in Z-Direction	0	Deg.
Number of Points in Ambient Density Profile Point ²	4	
Ambient Density at Depth = 0 ft	1.0229	g/cc
Ambient Density at Depth = 10 ft	1.0230	g/cc
Ambient Density at Depth = 16 ft	1.0235	g/cc
Ambient Density at Depth = 30 ft	1.0236	g/cc

AMBIENT VELOCITY DATA

Parameter	Value	Units
Water Depth	30	ft
Profile ³	2 Point	
X-Direction Velocity at depth = 0.2 feet	0.79	ft/sec
Z-Direction Velocity at depth = 0.2 feet	0.01	ft/sec
X-Direction Velocity at depth = 23.1 feet	0.16	ft/sec
Z-Direction Velocity at depth = 23.1 feet	-0.49	ft/sec

DISPOSAL OPERATION DATA

Parameter	Value	Units
Location of Disposal Point from Top of Grid	9,375	ft
Location of Disposal Point from Left Edge of Grid	9,375	ft
Dumping Over Depression	0	

INPUT, EXECUTION AND OUTPUT

Parameter	Value	Units
Location of the Upper Left Corner of the Disposal Site - Distance from Top Edge	3,060	ft
Location of the Upper Left Corner of the Disposal Site - Distance from Left Edge	6,286	ft
Location of the Lower Right Corner of the Disposal Site - Distance from Top Edge	15,690	ft
Location of the Lower Right Corner of the Disposal Site - Distance from Left Edge	12,464	ft
Duration of Simulation	14,400	sec
Long Term Time Step	600	sec

COEFFICIENTS

Parameter	Keyword	Value
Settling Coefficient	BETA	0.000 ¹
Apparent Mass Coefficient	CM	1.000 ¹
Drag Coefficient	CD	0.500 ¹
Form Drag for Collapsing Cloud	CDRAG	1.000 ¹
Skin Friction for Collapsing Cloud	CFRIC	0.010 ¹
Drag for an Ellipsoidal Wedge	CD3	0.100 ¹
Drag for a Plate	CD4	1.000 ¹
Friction Between Cloud and Bottom	FRICTN	0.010 ¹
4/3 Law Horizontal Diffusion Dissipation Factor	ALAMDA	0.001 ¹
Unstratified Water Vertical Diffusion Coefficient	AKYO	Pritchard Expression
Cloud/Ambient Density Gradient Ratio	GAMA	0.250 ¹
Turbulent Thermal Entrainment	ALPHAO	0.235 ¹
Entrainment in Collapse	ALPHAC	0.100 ¹
Stripping Factor	CSTRIP	0.003 ¹

¹Model Default Value


² EPA 2006 Brunswick ODMDS Trend Assessment Survey (EPA, 2007)

³From measurements at the Brunswick ODMDS 2002-2003 (ERDC, 2004)

Dilution Rates for Generic Material (6,000cy)

Minimum dilution outside of disposal site: 220 to 1; Minimum dilution after 4 hours: 550 to 1.

Brunswick ODMDS STFATE Input Parameters



Brunswick ODMDS Background Water Concentration	
Chemicals of Concern	Background Concentration Levels (µg/l)
Arsenic	1.49 ¹
Cadmium	0.01 ¹
Chromium (VI)	0.29 ¹
Copper	0.24 ¹
Lead	0.08 ¹
Mercury	0.1 ^{1,4}
Nickel	0.25 ¹
Selenium	0.20 ¹
Silver	0.01 ^{1,4}
Zinc	1.11 ¹
Ammonia	No Data
Cyanide	No Data
Tributyltin (TBT)	0.01 ^{3,4}
Aldrin	0.005 ^{1,4}
Chlordane	0.015 ^{2,4}
DDT	0.005 ^{1,4}
Dieldrin	0.005 ^{1,4}
alpha - Endosulfan	0.005 ^{1,4}
beta - Endosulfan	0.005 ^{1,4}
Endrin	0.005 ^{1,4}
gamma-BHC (Lindane)	0.005 ^{1,4}
Heptachlor	0.005 ^{1,4}
Heptachlor Epoxide	0.005 ^{1,4}
Toxaphene	0.25 ^{1,4}
Parathion	No Data
Pentachlorophenol	No Data

¹ 2010 Site Designation Studies for a New ODMDS offshore Jacksonville, FL

² EPA 2006 Brunswick ODMDS Trend Assessment Survey (EPA, 2007)

³ Reference Station Water from the 2006 Mayport Harbor 103 Evaluation

⁴ Analyte not detected. Value based on one half the reporting limit.

APPENDIX B

**TEMPLATE
for
GENERIC SPECIAL CONDITIONS
for
MPRSA SECTION 103 PERMITS**

This page left blank intentionally.

**TEMPLATE
GENERIC SPECIAL CONDITIONS
FOR MPRSA SECTION 103 PERMITS
Brunswick, GA ODMDS**

I. DISPOSAL OPERATIONS

A. For this permit, the term disposal operations shall mean the: navigation of any vessel used in disposal of operations, transportation of dredged material from the dredging site to the Brunswick ODMDS, proper disposal of dredged material at the disposal area within the Brunswick ODMDS, and transportation of the hopper dredge or disposal barge or scow back to the dredging site.

B. No more than [NUMBER] cubic yards of dredged material excavated at the location defined in [REFERENCE LOCATION IN PERMIT] are authorized for disposal at the Brunswick ODMDS.

C. The permittee shall use an electronic positioning system to navigate to and from the Brunswick ODMDS. For this section of the permit, the electronic positioning system is defined as a differential global positioning system or a microwave line of site system. If the electronic positioning system fails or navigation problems are detected, all disposal operations shall cease until the electronic positioning system is restored or navigation problems are corrected.

D. The permittee shall certify the accuracy of the electronic positioning system proposed for use during disposal operations at the Brunswick ODMDS. The certification shall be accomplished by direct comparison of the electronic positioning system's accuracy with a known fixed point.

E. The permittee shall not allow excessive water or dredged material placed in a hopper dredge or disposal barge or scow to flow over the sides or leak from such vessels during transportation to the Brunswick ODMDS. Excessive leakage is any change in draft exceeding 1.5 feet from the point of departure from the dredging site to the disposal site.

F. A disposal operations inspector and/or captain of any tugboat, hopper dredge or other vessel used to transport dredged material to the Brunswick , GA ODMDS shall ensure compliance with disposal operation conditions defined in this permit.

1. If the disposal operations inspector or the captain detects a violation, he/she shall report the violation to the permittee immediately.
2. The permittee shall contact the US Army Corps of Engineers, Savannah District's Regulatory Branch [1-800-448-2402] and EPA Region 4 at (404) 562-9386 to report the violation within twenty-four (24) hours after the violation occurs. A complete written explanation of any permit violation shall be included in the post-dredging report.

G. During disposal, no portion of the hopper dredge or disposal barge or scow shall be outside of the boundaries of the Brunswick ODMDS. Additionally, disposal shall occur within a specified disposal zone defined as [DEFINE COORDINATES AND SIZE OF DISPOSAL ZONE]. Disposal shall not occur closer than 1,500 feet to any oil and gas rigs that may be present within the site boundaries.

H. The permittee shall use an electronic tracking system (ETS) that will continuously track in real-time the horizontal location and draft condition (nearest 0.5 foot) of the disposal vessel (hopper dredge or disposal barge or scow) to and from the Brunswick ODMDS. Data shall be collected at least every 500 feet during travel to and from the ODMDS and every minute or every 200 feet of travel, whichever is smaller, while approaching within 1,000 feet and within the ODMDS. This information shall be provided to the Savannah District, in electronic format and on a daily basis, and is expected to be provided to EPA Region 4 on a weekly basis utilizing DQM specifications or approved (EPA and USACE) requirements (see Special Condition II.C).

Required digitally recorded data are:

- Contractor Name
- Load Number
- Disposal Vessel Name and Type (e.g. scow)
- Tow or Trawler Vessel Name (if applicable)
- Estimated Volume of each Load
- Description of Material Disposed
- Source of Dredged Material
- Date, Time and Location at Initiation and Completion of Disposal Event (State Plane Coordinates)

The permittee shall use Georgia State Plane or latitude and longitude coordinates (North American Datum 1983). State Plane coordinates shall be reported to the nearest 0.10 foot and latitude and longitude coordinates shall be reported as degrees and decimal minutes to the nearest 0.01 minutes.

I. The permittee shall conduct a bathymetric survey of the Brunswick ODMDS within 60 days following project completion.

1. The number and length of the survey transects shall be sufficient to encompass the defined disposal zone within the Brunswick ODMDS and a 500 foot wide area around the disposal zone. The transects shall be spaced at 500-foot intervals or less.

2. Vertical accuracy of the survey shall be ± 0.5 feet. Horizontal location of the survey lines and depth sounding points will be determined by an automated positioning system utilizing either microwave line of site system or differential global positioning system. The vertical datum will be referenced to prescribed

NOAA Mean Lower Low Water (MLLW) datum, 1983-2001 epoch, as shown on the Tidal Benchmark sheet for St. Simons Island, GA (Station ID: 8677344). MLLW is 3.23 feet below NGVD 1929. The horizontal datum will be Georgia State Plane (zone 1001 GA East, NAD 1983). State Plane coordinates shall be reported to the nearest 0.10 foot and latitude and longitude coordinates shall be reported as degrees and decimal minutes to the nearest 0.01 minutes.

J. The permittee has read and agrees to assure that they are in compliance with the requirements of the Brunswick ODMDS Site Management and Monitoring Plan.

II. REPORTING REQUIREMENTS

A. The permittee shall send the US Army Corps of Engineers, Savannah District's Regulatory Branch and EPA Region 4 Wetlands, Coastal and Oceans Branch (61 Forsyth Street, Atlanta, GA 30303) a notification of commencement of work at least fifteen (15) days before initiation of any dredging operations authorized by this permit.

B. The permittee shall submit to the Savannah District weekly disposal monitoring reports. These reports shall contain the information described in Special Conditions H and I.

C. Electronic data required by Special Conditions I.H are expected to be provided to EPA Region 4 on a weekly basis. Data shall be submitted as an eXtensible Markup Language (XML) document via Internet e-mail to DisposalData.R4@epa.gov. XML data file format specifications are available from EPA Region 4.

D. The permittee shall develop and send one (1) copy of the disposal summary report to the Savannah District's Regulatory Division and one (1) copy of the disposal summary report to EPA Region 4 documenting compliance with all general and special conditions defined in this permit. The disposal summary report shall be sent within 90 days after completion of the disposal operations authorized by this permit. The disposal summary report shall include the following information:

1. Dredging Project Title
2. USACE permit number and expiration date
3. Name of contractor(s) conducting the work
4. Name(s) and type of vessel(s) disposing the material in the ODMDS
5. Actual start date and completion date of dredging and disposal operations
6. Total cubic yards disposed (as paid *in situ* volume, total paid and un paid *in situ* volume, and gross volume reported by dredging contractor) at the Brunswick, GA ODMDS
7. Number of loads to ODMDS
8. Type of material disposed at the ODMDS
9. Locations of disposal events

10. Identification of any misplaced material (outside disposal zone or the ODMDS boundaries)
11. Dates of pre- and post- disposal bathymetric surveys of the ODMDS
12. Post disposal bathymetric survey results (in hard and electronic formats, plot and X, Y, Z ASCII data file)
13. Verification that all general and special permit conditions were met. Any violations of the permit shall be explained in detail.

APPENDIX C

**SAVANNAH DISTRICT
CORPS of ENGINEERS
GENERIC CONTRACT
SPECIFICATION LANGUAGE**

This page left blank intentionally.

Savannah District Corps of Engineers Contract Specification Language

I. Dredged Material Disposal

- A. Dredged material shall be placed within designated ocean disposal areas or zones, as shown on contract drawings.

Ocean Disposal Notification - The contractor shall notify EPA Region 4's Wetlands, Coastal and Oceans Branch (61 Forsyth Street, Atlanta, GA 30303) at least 15 calendar days, and the local Coast Guard Captain of the Port at least 5 calendar days, prior to the first ocean disposal. The notification will be by certified mail with a copy to the Contracting Officer.

The following information shall be included in the notification:

- a. Project designation; Corps of Engineers' Contracting Officer's name and contract number; and, the Contractor's name, address, and telephone number.
- b. Port of departure.
- c. Location of ocean disposal area (and disposal zone if required).
- d. Schedule for ocean disposal, giving date and time proposed for first ocean disposal.

The material excavated shall be transported to and deposited in the Brunswick ODMDS shown on the drawings. When dredged material is disposed, no portion of the hopper dredge or disposal barge or scow shall be outside of the boundaries of the Brunswick ODMDS as shown on the drawings. Additionally, disposal shall be initiated within the disposal release zone defined by the following coordinates:

[Insert coordinates for appropriate release zone]

Vertices	Geographic NAD 83		State Plane (Georgia) NAD 83	
Center				
North				
West				
South				
East				

Materials deposited outside of the specified disposal zone will be classified as misplaced material and will result in a suspension of dredging operations. Redredging of such materials will be required as a prerequisite to the resumption of dredging unless the Contracting Officer, at his discretion, determines that redredging of such material is not practical. If redredging of such material is not required then the quantity of such misplaced material shall be deducted from the Contractor's pay quantity. If the quantity for each misplaced load to be deducted cannot initially be agreed to by both the Contractor and Contracting Officer, then an average hopper/scow load quantity for the entire contract will be used in the determination. Misplaced loads may also be subject to penalty under the Marine, Protection,

Research and Sanctuaries Act. Materials deposited above the maximum indicated elevation or outside of the disposal area template shown will require the redredging or removal of such materials at the Contractor's expense. In addition, the Contractor must notify the Contracting Officer and the Environmental Protection Agency Region 4's Wetlands, Coastal and Oceans Branch (61 Forsyth Street, Atlanta, GA 30303) within 24 hours of a misplaced dump or any other violation of the Site Management and Monitoring Plan for the Brunswick ODMDS. Corrective actions must be implemented by the next dump and the Contracting Officer must be informed of actions taken.

B. Logs

The Contractor shall keep a log for each load placed in the Brunswick ODMDS. The log entry for each load shall include:

- a. Load Number
- b. Disposal Vessel or Scow Name
- c. Tow Vessel Name (if scow used)
- d. Estimated volume of Load
- e. Description of Material Disposed
- f. Source of Dredged Material
- g. Date, Time and Location (coordinates) at Start of Initiation and Completion of Disposal Event

At the completion of dredging and at any time upon request, the log(s) shall be submitted in paper and electronic formats to the Contracting Officer for forwarding to the appropriate agencies.

- C. The use of bottom dump barges and dredges, hydraulic unloading barges, hydraulic pipeline and hopper dredges to dispose of dredged material in the offshore disposal area is permitted. Excessive water and excavated material shall not overflow or spill out of barges, dump scows, or hopper dredges while in route to the disposal site. EPA has defined excessive leakage as any change in draft exceeding 1.5 feet from the point of departure from the dredging site to the disposal site. Overflow or spillage caused by the failure to repair leaks or change the method of operation will result in suspension of excavation operations and require prompt repair or change of operation to prevent overflow or spillage as a prerequisite to the resumption of excavation. Material shall be placed in the offshore disposal area below the -25 MLLW level, and at least 100 meters inside the boundary of the ODMDS. A depth of -30 feet is the warning threshold for monitoring and management purposes. If -30 feet MLLW is reached, then management decisions will be made on future sediment placement to avoid exceeding the -25 foot MLLW threshold.

II. Electronic Tracking System (ETS) for Ocean Disposal Vessels

The Contractor shall furnish an ETS for surveillance of the movement and disposition of dredged material during dredging and ocean disposal. This ETS shall be

established, operated and maintained by the Contractor to continuously track in real-time the horizontal location and draft condition of the disposal vessel (hopper dredge or disposal barge or scow) for the entire dredging cycle, including dredging area and disposal area. The ETS shall be capable of displaying and recording in real-time the disposal vessel's draft and location.

[USE LANGUAGE BELOW FOR NON DQM PROJECTS]

A. ETS Standards

The Contractor shall provide automated (computer) system and components to perform monitoring in accordance with EM 1110-1-2909. A copy of the EM can be downloaded from the following web site: <http://www.usace.army.mil/inet/usace-docs/eng-manuals/em.htm>. The accuracy of the horizontal location shall be equal to or better than a standard DGPS system, (i.e., equal to or better than plus/minus 10 feet (horizontal repeatability). Vertical (draft) data shall have an accuracy of plus/minus 0.5 foot. Horizontal location and vertical data shall be collected in sets and each data set shall be referenced in real-time to date and local time (to nearest minute), and shall be referenced to the same state plane coordinate system used for the survey(s) shown in the contract plans. The ETS shall be calibrated, as required, in the presence of the Contracting Officer's Representative (COR) at the work location before disposal operations have started, and at 30-day intervals while work is in progress. The COR shall have access to the ETS in order to observe its operation. Disposal operations will not commence until the ETS to be used by the Contractor is certified by the COR to be operational and within acceptable accuracy. It is the Contractor's responsibility to select a system that will operate properly at the work location. The complete system shall be subject to the COR's approval.

B. Data Requirements and Submissions

1. The ETS for each disposal vessel shall be in operation for all dredging and disposal activities and shall record the entire trip for each loading and disposal cycle. [Note: A dredging and disposal cycle constitutes the time from commencement of dredging to complete discharge of the material.] The COR shall be notified immediately in the event of ETS failure and all dredging operations for the vessel shall cease until the ETS is fully operational. Any delays resulting from ETS failure shall be at the contractor's expense.

2. Data shall be collected at least every 500 feet during travel to and from the ODMDS and every minute or every 200 feet of travel, whichever is smaller, while approaching within 1,000 feet of the boundary of the ODMDS and within the ODMDS.

3. Plot Reporting (2 types):

(a) Tracking Plot - For each disposal event, data collected while the disposal vessel is in the vicinity of the disposal area shall be plotted in chart form, in 200-foot intervals, to show the track and draft of the disposal vessel approaching and traversing the disposal area. The plot shall identify the exact position at which the dump commenced.

(b) Scatter Plot - Following completion of all disposal events, a single and separate plot will be prepared to show the exact disposal locations of all dumps. Every plotted location shall coincide with the beginning of the respective dump. Each dump will be labeled with the corresponding Trip Number and shall be at a small but readable scale. To accompany the Scatter Plot, a single and separate table will be prepared of the corresponding ETS data for every dump location. The volume of material disposed for each trip will be included in this table.

(c) Summary Table – A spreadsheet which contains all of the information in the log(s) [Section I.B.] above shall be prepared and shall correspond to the exact dump locations represented on the Scatter Plot.

4. ETS data and log data are expected to be provided to EPA Region 4 on a weekly basis. Data shall be submitted to EPA Region 4 as an eXtensible Markup Language (XML) document via Internet e-mail to DisposalData.R4@epa.gov. XML data file format specifications are available from EPA Region 4. All digital ETS data shall be furnished to the COR within 24 hours of collection. The digital plot files should be in an easily readable format such as Adobe Acrobat PDF file, Microstation DGN file, JPEG, BMP, TIFF, or similar. The hard copy of the ETS data and tracking plots shall be both maintained onboard the vessel and submitted to the COR on a weekly basis.

[FOR DQM PROJECTS]

See: <http://dqm.usace.army.mil/Specifications/Index.aspx>



For scows, the monitoring profile, TDS profile or Ullage profile shall be used.

Appendix D
Brunswick ODMDS Bathymetry


The page left blank intentionally.

Brunswick Harbor

Ocean Dredged Material Disposal Site



ft MLLW



Surveyed February 2012