


SAVANNAH HARBOR EXPANSION GENERAL REEVALUATION REPORT



DREDGED MATERIAL PHYSICAL ANALYSIS REPORT



Savannah Harbor Deepening General Re-evaluation Report

Table of Contents

| <u>Section</u> | <u>Page</u> |
|--|--------------------|
| 1.0 Site Geology | 3 |
| 1.1 General..... | 3 |
| 1.2 Post-Miocene Units..... | 3 |
| 1.3 Miocene Units..... | 4 |
| 1.4 Oligocene Unit..... | 5 |
| 1.5 Eocene Units | 5 |
| 1.5.1 Upper Eocene Unit..... | 5 |
| 1.5.2 Middle Eocene Unit | 5 |
| 1.5.3 Lower Eocene Unit | 6 |
| 1.6 Paleocene Unit | 6 |
| 2.0 Subsurface Investigations | 6 |
| 2.1 Background | 6 |
| 2.2 Procedures..... | 7 |
| 3.0 Material Summary | 7 |
| 3.1 General..... | 7 |
| 3.2 Soils | 7 |
| 3.3 Rock | 8 |
| 4.0 Radiological Screening..... | 9 |
| 4.1 Purpose..... | 9 |
| 4.2 Procedures..... | 9 |
| 4.3 Results..... | 9 |

5.0 Possible Effects of the Project on Ground Water..... 9

6.0 Additional Geotechnical Requirements 10

Appendices

| | |
|-------------------|--|
| Appendix A | Boring Logs |
| Appendix B | Laboratory Data |
| Appendix C | Results of Radiological Screening |
| Appendix D | Boring Location Plans |

1.0 Site Geology

1.1 General

The study area is underlain with unconsolidated and partly consolidated Atlantic Coastal Plain sediments. These sediments generally consist of unconsolidated to semi-consolidated layers of sand and clay; and semi-consolidated to very dense limestone and dolomite and can achieve thicknesses of about 5,500 feet. They range in age from late Cretaceous (approximately 100 million years old) to recent, or Holocene. The Atlantic Coastal Plain sediments overlie sedimentary strata and volcanics of Triassic age to early Jurassic age (approximately 230 million years old to about 170 million years old, respectively). These rocks overlie crystalline basement rocks of Paleozoic age (from 680 to 230 million years old) consisting of igneous intrusives and low-grade metamorphic rocks. The rock record is not continuous and time gaps exist where either no sediment deposition occurred or where erosional forces removed the rock record. In the project area, the post-Cretaceous sediments (those deposited within the last 65 million years) are estimated to be about 1,800 to 2,500 feet thick. These strata intersect a horizontal plane in a northeast to southwest trend and dip and thicken to the southeast. A discussion of the post-Cretaceous Atlantic Coastal Plain sediments follows, in descending order of occurrence. For the purpose of this discussion, the strata will be referred to based on time-rock units (i.e., rocks deposited during the same geologic time division).

1.2 Post-Miocene Units

The post-Miocene units consist of sediments deposited during the Pliocene, Pleistocene, and Holocene (recent) geologic ages (12 million years old and younger). These sediments are comprised of interbedded floodplain deposits of reworked alluvial and beach material and reworked Miocene sediments. Typically, these floodplain sediments are tan, gray, or greenish gray in color.

The post-Miocene unit sediments are found at the surface throughout the area. They consist of phosphatic, micaceous, and clayey sands of Pliocene age; feldspathic sands and gravels with clay beds of Pleistocene age; and varying mixes of clays, silts, sands, and gravels of Holocene age. There is very little fossil material in these sediments. In some areas, Pliocene and Pleistocene sediments may be missing from the geologic record. It is uncertain if these sediments exist within the project area.

The Holocene (recent) sediments generally consist of varying mixtures of clays, silts, sands, and, occasionally, gravels. Within the project area, these sediments are represented by low and high liquid-limit clays with varying amounts of sand and organic matter (CL and CH); inorganic, low and high liquid-limit silts (ML and MH); silty sands containing up to 40 percent silts, some clay and mica (SM); and cleaner, poorly graded sands containing less than 12 percent silts and clays (SP, SP-SM). The consistency of the fine-grained soils (silts and clays) can be described as very soft to soft. The coarse-grained soils (sands) can be described as very loose to dense, with the majority being

medium. The materials are somewhat cohesive when small amounts of silt or clay are present; however, they tend to slough below the water table when there is little fine material.

The Holocene materials are often associated with beaches and dunes. They were carried from topographically high areas from the Piedmont and upstream Coastal Plains and deposited during the formation of the floodplain of the Savannah River. The sediments are mixed by hydraulic action of the waters in the river and by erosion and redeposition of the riverbank and river shoals as the river meanders. There is no active method for sediment accumulation beyond the banks of the river. Consequently, with the exception of accumulations of organic material, there are no materials being deposited there.

Immediately below the Holocene Unit is the Pleistocene series of sediments. These sediments generally consist of arkosic sands and gravels with discontinuous lignitic and fossiliferous clay beds and overlying micaceous sands. These are underlain by the Pliocene sediments, which consist of phosphatic, micaceous, and clayey sands with limestone and dolomite beds. These sediment beds are thin and have not been regularly identified in the project area.

1.3 Miocene Units

According to Clarke and others (1990), the Miocene units (20 to 12 million years old) can be subdivided into three sub-units (Miocene unit A, B, and C), each consisting of three geologically similar beds. The lowest bed of each sub-unit consists of a basal carbonate layer of sandy, phosphatic limestone or dolomite. A layer of interlaminated silty clay and clayey silt overlies the basal carbonate layer. The upper beds consist of sand layers of poorly sorted, very fine to granule-sized quartz sand with some phosphatic and dolomitic grains. Each three-bed unit is separated from the beds above and below it by an erosional surface, or unconformity. These layers are of importance because they form the primary confining layer for the principal artesian aquifer in the area.

The Miocene units at the project extend to a depth of about 220 feet in the upper reaches of the project area. They can achieve a thickness of about 470 feet along the coastal area, but range from about 60 to 175 feet thick under the project area. Miocene Unit C, the lowest unit, appears to be missing in the project area.

The beds of the Miocene were deposited during transgressions and regressions (rising and lowering) of the sea. The basal carbonates were deposited in open marine water during full transgressions. During this time, the land surface was at its greatest depth below the water surface. As the sea regressed, the interlayered silts and clays were deposited in a shallower, nearshore environment that allowed for the settling of the fine silts and clays. In this environment, coarser materials were already removed from the sediment and calcareous materials were not a major contributor. The upper sand beds were deposited in a shallow water, nearshore environment. At this time, the

water was at its shallowest. Materials deposited during the period the sea transgressed inland were, apparently, removed during some erosional event. As the next sea regression occurred, the next sequence of beds was deposited until the final sequence, Miocene Unit A, was deposited.

1.4 Oligocene Unit

Sediments of the Oligocene units were deposited between 35 and 20 million years ago. This unit can be as thick as 120 feet, and in some areas it is missing. The unit is estimated at approximately 60 thick under the project area, based on geophysical data.

The Oligocene unit sediments are typically tan colored limestones with varying amounts of micrite (dense, non-porous limestone), fine fossil foraminifera shells, and silt and clay-sized phosphate. The sediments were deposited in an offshore mounded carbonate bank environment, with some sand material being deposited where the bank nears the shore.

1.5 Eocene Units

Immediately below the Oligocene Unit are the Eocene Units. The Eocene sediments, deposited between 55 and 35 million years ago, are subdivided into three sub-units: the upper, middle, and lower Eocene Units. It is the source of the principal artesian aquifer in the Savannah area, the Floridan Aquifer.

1.5.1 Upper Eocene Unit

The upper Eocene Unit throughout most of the coastal area of Georgia consists of the massive, fossiliferous, Ocala Limestone. There is some glauconite at the base of the unit and an increase in clastic material in the northern coastal areas, including the project area. This unit is more than 200 feet thick throughout the coastal area, and achieves a thickness of 400 feet in some areas. These sediments were deposited in a warm, shallow water, nearshore carbonate bank environment, similar to the other Eocene units.

1.5.2 Middle Eocene Unit

The middle Eocene Unit is separated from the lower and upper units by erosional surfaces, or unconformities. It is lithologically similar to the lower unit, and can be distinguished based on the abundance of microfossils. The upper beds of this unit are more dolomitic than the upper beds of the lower unit and contrast with the lower limestone beds of the upper Eocene Unit. This unit can be up to 1,000 feet thick in some areas. At Hutchinson Island and Fort Pulaski, near Savannah, Georgia, the unit is 700 and 540 feet thick, respectively. This unit is most likely more than 700 feet thick in the study area. These sediments were deposited in an environment similar to that of the lower Eocene Unit.

1.5.3 Lower Eocene Unit

This unit unconformably overlies the Paleocene unit below it. It consists of carbonate sediments, predominantly glauconitic limestones and dolomites, with sand beds in the upper part. These beds attain a thickness of up to 800 feet in the southern coastal area of Georgia but are only 120 to 180 feet thick in the project area. This unit was deposited in a nearshore warm, shallow, open marine environment.

1.6 Paleocene Unit

Sediments of the Paleocene Unit were deposited between 65 and 55 million years ago. The Paleocene Unit in the northern coastal Georgia area consists of glauconitic sand, argillaceous sand, and medium to dark gray clays. The uppermost beds of the unit consist of a hard, sandy, glauconitic, fossiliferous limestone. The Paleocene Unit can be over 425 feet thick, but there is little data in the coastal area to develop accurate estimates in the project area. The Paleocene time marked the beginning of a regional sea transgression that lasted through the Eocene. The sediments represent marine to marginal marine, nearshore depositional environments. This unit unconformably overlies late Cretaceous age sediments.

2.0 Subsurface Investigations

2.1 Background

The Geology/Hydrogeology and HTRW Design Section, U.S. Army Corps of Engineers, Savannah District, has performed a number of subsurface investigations within the project area over the last 35 years. Several hundred borings have been drilled within and adjacent to the Savannah Harbor. The majority of these borings were along the north side of the channel and were drilled for the Savannah Harbor Widening and the Savannah Harbor Deepening projects, both completed at the end of the last century. These borings were constructed for the purpose of evaluating the in-situ materials within specific areas of the channel for harbor modification projects. The majority of the borings were water-borne; however, land-based borings have been completed to identify soil materials within the channel side slopes for the purpose of determining the most probable channel side slopes resulting for each proposed harbor modification. The investigations have used a variety of methods to obtain subsurface data, including Vibracore, splitspooning, coring, and sub-bottom sonic profiling. Standard penetration sampling using a split-barrel sampler was the method most often used. Using this method, a 1-3/8 inch inner diameter standard split barrel sampler was driven through the material using a 140-pound hammer with a 30-inch fall. The sampler was retrieved and the material was described in accordance with the Unified Soil Classification System. Selected samples were submitted for a variety of mechanical analyses, including grain size analysis, Atterberg limits, natural moisture content, and specific gravity calculations.

2.2 Procedures

The majority of the borings constructed within the channel were drilled from a floating barge using a variety of core drills to recover the samples. The barges were somewhat stabilized using steel spuds or anchors. They raised and lowered with the tide cycle. Drilling was very difficult off these platforms and often had to be terminated due to strong tides that would not allow the drill crew to maneuver the barge to a boring location. Wakes caused by high winds and ship traffic also greatly hampered the ability to drill from such a platform.

This drilling platform was also used to construct the Vibracore borings. This method involved vibrating a plastic tube through the subsurface soils to collect a sample that provided a more representative indication of the in-situ nature of the soils. This method could recover soft muds and loose sands that were often lost using standard penetration methods with a split-barrel sampler. However, this method generally did not penetrate stiff silts and clays or medium dense sands, or other materials exhibiting some degree of cementation, induration, or other characteristic of lithification. Also, this method did not provide adequate data that could be easily related to the relative strengths of the soils penetrated using other drilling methods.

During the mid 1980's, drilling was conducted using the U.S. Army Corps of Engineers self-elevating barge Explorer. This barge was a powered vessel that could maneuver on its own using twin diesel motors. It also had the ability to elevate itself above the water on three legs to eliminate the actions of the tide cycles and wave action. Drilling from this platform proved to be much more efficient and allowed the employment of more consistent drilling techniques. In addition, the Explorer allowed drilling in areas that were inaccessible to the standard barge due to rapid tide currents, deep water, and extreme distances from land.

3.0 Material Summary

3.1 General

The sediments underlying the project area are largely a result of varying depositional environments. As such, the sediments are discontinuous both vertically and horizontally and numerous variations occur over short distances. Boring logs completed for these investigations are included in Appendix A of this document. Analytical results of the mechanical analyses of the samples collected during these investigations are provided in Appendix B. The plans showing the locations of the borings are provided as Appendix D.

3.2 Soils

The uppermost sediments consist of varying mixtures of poorly-graded sands (SP), silty sands (SM), poorly-graded gravels (GP), organic silts (OH), low liquid-limit and high liquid-limit silts (ML and MH), clayey sands (SC), and low liquid-limit and high liquid-limit clays (CL and CH). Standard penetration tests from borings indicate the consistency of the fine-grained soils (silts and clays) range from very soft (0 to 4 blows per foot) to very dense (50 or greater blows per foot), while the coarse-grained soils (sands and gravels) range in consistency from dense (30 to 50 blows per foot) to very dense (50 or greater blows per foot). Typically, these soils vary in color from tan, gray, brown, light brown, and greenish to bluish gray. Generally, soils at the river bottom exhibit lower consistency than the deeper soils. The bottom soils are often very loose and semi-liquid and can extend from the bottom of the river channel to only a few inches to several feet deep.

The underlying soils consist of silty sands (SM), clayey sands (SC), high liquid-limit silts (MH), and low liquid-limit and high liquid-limit clays (CL and CH). Standard penetration tests indicate the consistencies of the fine-grained soils range from stiff (8 to 15 blows per foot) to hard (30 or greater blows per foot), while the coarse-grained soils range in density from dense (30 to 50 blows per foot) to very dense (50 or greater blows per foot). In general, these soils are characterized by a significant increase in blow counts, consistency, and cohesiveness. These soils are often described as gray, grayish green, green, and olive green.

3.3 Rock

Lenses of moderately hard to hard limestone have been encountered in borings constructed around the project area; however, its occurrence has been below the depths of concern for this project. In addition, borings drilled in 1969 identified compaction shale in the northern end of the channel, near Kings Island turning basin. This lithology has not been identified in any of the more recent borings and this material may be analogous to the greenish-gray to olive green, stiff to hard, fat silts and dense to very dense silty sands that have been described in later borings.

A high resolution, sub-bottom acoustic survey was performed in the channel during the early 1990's as part of the investigation program for the recently completed harbor deepening. This survey showed an area of high acoustic impedance within the middle channel (stations 70+000 to 24+000). Borings drilled in this area and subsequent dredging indicated this material was similar to the greenish-gray to olive green, stiff to hard, fat clays and dense to very dense silty sands described above.

Thin layers of rock were identified in a boring constructed in 2002 at the interface between the post-Miocene sediments and the top of the Miocene. The layer was no more than a few centimeters thick and was a green, fine-grained, sandstone. These more recent borings also describe black gravels and oblong rock fragments within the Miocene sediments, consistent with the geological descriptions of the phosphatic materials within the Miocene sediments provided above in Section 1.3. These materials were encountered both within and below the project depth.

4.0 Radiological Screening

4.1 Purpose

The Savannah Harbor Deepening project area is located downstream from the Savannah River Site, where radioactive materials are processed. Releases of radioactive materials from the site have been documented over the years, raising concern as to whether such releases could cause accumulation of these materials within the sediments that are to be removed from within the project area. The likelihood of this occurring has been considered improbable; nevertheless, a decision was made to screen selected sediment samples that were collected during the 2002 investigations for gross radioactivity.

4.2 Procedures

All samples collected during the 2002 subsurface investigations were placed in sample jars, labeled, inventoried, boxed, and shipped to the Savannah District Army Corps of Engineers' Environmental and Materials Unit located in Marietta, Georgia. Initially, the entire stack of sample boxes was screened, and then selected individual samples. Prior to performing the analyses described in Section 2.1, above, randomly selected jar samples from every boring hole was screened for gross radioactivity. This process involved using a Bicron Geiger Mueller gauge equipped with a pancake probe. The probe was placed approximately 1 centimeter above the soil samples, and the highest reading was recorded. Readings were also collected from around the facility to determine ambient background levels.

4.3 Results

All results were measured in milli-Rems per hour (mRem/hr). Background values varied between 0.01 and 0.03 mRem/hr. Values from the sediment samples ranged from 0.02 to 0.04 mRem/hr. These results are consistent with the background values, with only a few samples exhibiting an increase of 0.01 mRem/hr over the background range. This should be anticipated, since these soils contain phosphatic and glauconitic minerals, along with other clays, that exhibit naturally-occurring levels above background levels. These results are two magnitudes below acceptable action levels approved by OSHA and the EPA that range between 1 mRem/hr and 5mRem/hr. Based on these results, it is believed that the levels of gross radioactivity measured in the samples is naturally occurring and poses no hazards to the environment.

5.0 Possible Effects of the Project on Ground Water

In the past, any proposed deepening of Savannah Harbor has raised questions about the possible effects this action would have on the confining layer of the principal artesian aquifer, known at the Floridan aquifer, and, ultimately, on the aquifer itself.

In light of some of the seemingly conflicting data, additional information was needed to adequately assess the possible effects of a deepened channel on the Upper Brunswick aquifer (as described by Clarke and others, 1990) and the Upper Floridan (principal artesian) aquifer that underlies the entire project area. It was decided that further studies should be conducted to verify the generalized data available from previous studies (mentioned above) of these aquifers. These studies would look at the potential impacts to the confining layer due to removing some confining and relict stream channel material. The results of these additional studies completed to date are provided in a separate document. Additional studies have yet to be completed. They are planned for completion in 2004.

6.0 Additional Geotechnical Requirements

Changes in channel geometry due to deepening, widening, realignment, slope stability, or feature avoidance require re-evaluation of existing data. As channel geometry continues to change, older geotechnical data is no longer adequate to evaluate these changes for a number of reasons. One concern is that there may be an insufficient number of borings located in areas that were naturally deeper than proposed project depths but no longer are. Another concern is that older borings, drilled for a much shallower project, were completed at depths that are shallower than proposed project depths. Also, as channels become deeper to accommodate larger vessels bend wideners are often added in areas that have not been previously investigated. These concerns were considered prior to the performance of the investigations conducted for the re-evaluation of this project. However, as additional changes in channel geometry are identified these concerns will be re-evaluated and additional subsurface investigations will be required.

APPENDIX A

SAVANNAH HARBOR BORING LOGS

SAVANNAH HARBOR BORING LOGS

**Kings Island
Turning Basin**

| | | | | |
|--|--|--|-------------------------------|--|
| DRILLING LOG | | DIV 4 South Atlantic | INSTALLATION Savannah, Ga. | L. I. File No. SHEET 1 OF 2 SHEETS |
| 1. PROJECT Savannah Harbor Widening and Deepening, Phase 2 | | 10. SIZE AND TYPE OF PIT 1-3/8" Splitspoon, R | | |
| 2. LOCATION (Coordinates of Station) See Plan | | 11. DATUM FOR ELEVATION SHOWN (TIDE or MSL) Core Bit MLW | | |
| 3. DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 C.D. #8 | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 1 UNDISTURBED 0 | | |
| 5. NAME OF DRILLER Creamer | | 14. TOTAL NUMBER CORE BOXES 2 | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER 0.0' - Tidal | | |
| 7. THICKNESS OF OVERTURDEN | | 16. DATE HOLE STARTED 19 Mar 69 COMPLETED 20 Mar 69 | | |
| 8. DEPTH DRILLED INTO ROCK | | 17. ELEVATION TOP OF HOLE -14.3' | | |
| 9. TOTAL DEPTH OF HOLE 45.5' | | 18. TOTAL CORE RECOVERY FOR BORING 58% | | |
| | | 19. SIGNATURE OF INSPECTOR Allen Merritt, Robert L. Slesen, Geologist | | |

| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
|-----------|-------|--------|--|-------------------------|--|--|
| | 0 | | Water | | | No Sample obtained of OL materials, stratum very thin |
| | 5 | | Very thin, very soft, layer of OL-organic silt above sand | | | |
| | 10 | | | | | |
| -14.3' | 15 | • • • | SM-Gray, very fine grained, silty sand | Jar 1 | 14.3' to 16.5' Washed out while setting casing | |
| | 20 | • • • | ML-Greenish gray, clayey to sandy silt, moderate resistance to knife blade penetration from 18.0' to 24.5' | 100 | Splitspoon 16.5' to 13.0 4" Casing set to 18.5' | Pull #1, 18.0' to 19.5' Run 1.5', Rec 1.5' |
| | 25 | • • • | SM-Gray, silty, very fine grained sand, moderate resistance to knife blade penetration from 24.5' to 29.5' | 86 | Pull #2, 19.5' to 24.5' Run 5.0', Rec 4.3' C1 0.7' | |
| | 30 | • • • | SM - - - Continued on Sheet #2 - - - | 40 | Pull #3, 24.5' to 29.5' Run 5.0', Rec 2.0' C1 3.0' | |

(Revised by Amendment No. 0001)

DRILLING LOG (Cont Sheet)

"VATION TOP OF HOLE

-14.3°

Hole No.

1

**PROJECT Savannah Harbor
Widening and Deepening, Phase 2**

INSTALLATION

Savannah, Ga.

SHEET 2
OF 2 SHEETS

| ELEVATION a | DEPTH. b | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV. ERY e | BOX OR SAMPLE NO. f | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g | |
|----------------|-------------|-------------|---|------------------------------|------------------------------|---|---|
| | | | | | | | |
| | | | SN-Tan, very fine grained, silty sand, slight resistance to knife blade penetration from 39.5' to 41.6' | 24 | | Pull #4, 29.5' to 34.5' Run 5.0', Rec 1.2' Cl 3.8' | |
| 35 | | | | 44 | 1 | Pull #5, 34.5' to 38.8' Run 4.3', Rec 1.9' Cl 2.4' | |
| 40 | | | | 72 | | Pull #6, 38.8' to 41.6' Run 2.8', Rec 2.0' Cl 0.8' | |
| 45 | | | Compaction shale, gray, sandy, moderate resistance to knife blade penetration BOTTOM OF HOLE 45.5' | 80 | | Pull #7, 41.6' to 45.5' Run 3.9', Rec 3.1' Cl 0.8' | |
| | | | Soils field classified in accordance with the Unified Soil Classification System. | | | Used 150 to 250 lbs pressure while coring | ONLY C-1 C-2 C-3 C-4 C-5 C-6 C-7 C-8 C-9 C-10 C-11 C-12 C-13 C-14 C-15 C-16 C-17 C-18 C-19 C-20 C-21 C-22 C-23 C-24 C-25 C-26 C-27 C-28 C-29 C-30 C-31 C-32 C-33 C-34 C-35 C-36 C-37 C-38 C-39 C-40 C-41 C-42 C-43 C-44 C-45 C-46 C-47 C-48 C-49 C-50 C-51 C-52 C-53 C-54 C-55 C-56 C-57 C-58 C-59 C-60 C-61 C-62 C-63 C-64 C-65 C-66 C-67 C-68 C-69 C-70 C-71 C-72 C-73 C-74 C-75 C-76 C-77 C-78 C-79 C-80 C-81 C-82 C-83 C-84 C-85 C-86 C-87 C-88 C-89 C-90 C-91 C-92 C-93 C-94 C-95 C-96 C-97 C-98 C-99 C-100 C-101 C-102 C-103 C-104 C-105 C-106 C-107 C-108 C-109 C-110 C-111 C-112 C-113 C-114 C-115 C-116 C-117 C-118 C-119 C-120 C-121 C-122 C-123 C-124 C-125 C-126 C-127 C-128 C-129 C-130 C-131 C-132 C-133 C-134 C-135 C-136 C-137 C-138 C-139 C-140 C-141 C-142 C-143 C-144 C-145 C-146 C-147 C-148 C-149 C-150 C-151 C-152 C-153 C-154 C-155 C-156 C-157 C-158 C-159 C-160 C-161 C-162 C-163 C-164 C-165 C-166 C-167 C-168 C-169 C-170 C-171 C-172 C-173 C-174 C-175 C-176 C-177 C-178 C-179 C-180 C-181 C-182 C-183 C-184 C-185 C-186 C-187 C-188 C-189 C-190 C-191 C-192 C-193 C-194 C-195 C-196 C-197 C-198 C-199 C-200 C-201 C-202 C-203 C-204 C-205 C-206 C-207 C-208 C-209 C-210 C-211 C-212 C-213 C-214 C-215 C-216 C-217 C-218 C-219 C-220 C-221 C-222 C-223 C-224 C-225 C-226 C-227 C-228 C-229 C-230 C-231 C-232 C-233 C-234 C-235 C-236 C-237 C-238 C-239 C-240 C-241 C-242 C-243 C-244 C-245 C-246 C-247 C-248 C-249 C-250 C-251 C-252 C-253 C-254 C-255 C-256 C-257 C-258 C-259 C-260 C-261 C-262 C-263 C-264 C-265 C-266 C-267 C-268 C-269 C-270 C-271 C-272 C-273 C-274 C-275 C-276 C-277 C-278 C-279 C-280 C-281 C-282 C-283 C-284 C-285 C-286 C-287 C-288 C-289 C-290 C-291 C-292 C-293 C-294 C-295 C-296 C-297 C-298 C-299 C-300 C-301 C-302 C-303 C-304 C-305 C-306 C-307 C-308 C-309 C-310 C-311 C-312 C-313 C-314 C-315 C-316 C-317 C-318 C-319 C-320 C-321 C-322 C-323 C-324 C-325 C-326 C-327 C-328 C-329 C-330 C-331 C-332 C-333 C-334 C-335 C-336 C-337 C-338 C-339 C-340 C-341 C-342 C-343 C-344 C-345 C-346 C-347 C-348 C-349 C-350 C-351 C-352 C-353 C-354 C-355 C-356 C-357 C-358 C-359 C-360 C-361 C-362 C-363 C-364 C-365 C-366 C-367 C-368 C-369 C-370 C-371 C-372 C-373 C-374 C-375 C-376 C-377 C-378 C-379 C-380 C-381 C-382 C-383 C-384 C-385 C-386 C-387 C-388 C-389 C-390 C-391 C-392 C-393 C-394 C-395 C-396 C-397 C-398 C-399 C-400 C-401 C-402 C-403 C-404 C-405 C-406 C-407 C-408 C-409 C-410 C-411 C-412 C-413 C-414 C-415 C-416 C-417 C-418 C-419 C-420 C-421 C-422 C-423 C-424 C-425 C-426 C-427 C-428 C-429 C-430 C-431 C-432 C-433 C-434 C-435 C-436 C-437 C-438 C-439 C-440 C-441 C-442 C-443 C-444 C-445 C-446 C-447 C-448 C-449 C-450 C-451 C-452 C-453 C-454 C-455 C-456 C-457 C-458 C-459 C-460 C-461 C-462 C-463 C-464 C-465 C-466 C-467 C-468 C-469 C-470 C-471 C-472 C-473 C-474 C-475 C-476 C-477 C-478 C-479 C-480 C-481 C-482 C-483 C-484 C-485 C-486 C-487 C-488 C-489 C-490 C-491 C-492 C-493 C-494 C-495 C-496 C-497 C-498 C-499 C-500 C-501 C-502 C-503 C-504 C-505 C-506 C-507 C-508 C-509 C-510 C-511 C-512 C-513 C-514 C-515 C-516 C-517 C-518 C-519 C-520 C-521 C-522 C-523 C-524 C-525 C-526 C-527 C-528 C-529 C-530 C-531 C-532 C-533 C-534 C-535 C-536 C-537 C-538 C-539 C-540 C-541 C-542 C-543 C-544 C-545 C-546 C-547 C-548 C-549 C-550 C-551 C-552 C-553 C-554 C-555 C-556 C-557 C-558 C-559 C-560 C-561 C-562 C-563 C-564 C-565 C-566 C-567 C-568 C-569 C-570 C-571 C-572 C-573 C-574 C-575 C-576 C-577 C-578 C-579 C-580 C-581 C-582 C-583 C-584 C-585 C-586 C-587 C-588 C-589 C-590 C-591 C-592 C-593 C-594 C-595 C-596 C-597 C-598 C-599 C-600 C-601 C-602 C-603 C-604 C-605 C-606 C-607 C-608 C-609 C-610 C-611 C-612 C-613 C-614 C-615 C-616 C-617 C-618 C-619 C-620 C-621 C-622 C-623 C-624 C-625 C-626 C-627 C-628 C-629 C-630 C-631 C-632 C-633 C-634 C-635 C-636 C-637 C-638 C-639 C-640 C-641 C-642 C-643 C-644 C-645 C-646 C-647 C-648 C-649 C-650 C-651 C-652 C-653 C-654 C-655 C-656 C-657 C-658 C-659 C-660 C-661 C-662 C-663 C-664 C-665 C-666 C-667 C-668 C-669 C-670 C-671 C-672 C-673 C-674 C-675 C-676 C-677 C-678 C-679 C-680 C-681 C-682 C-683 C-684 C-685 C-686 C-687 C-688 C-689 C-690 C-691 C-692 C-693 C-694 C-695 C-696 C-697 C-698 C-699 C-700 C-701 C-702 C-703 C-704 C-705 C-706 C-707 C-708 C-709 C-710 C-711 C-712 C-713 C-714 C-715 C-716 C-717 C-718 C-719 C-720 C-721 C-722 C-723 C-724 C-725 C-726 C-727 C-728 C-729 C-730 C-731 C-732 C-733 C-734 C-735 C-736 C-737 C-738 C-739 C-740 C-741 C-742 C-743 C-744 C-745 C-746 C-747 C-748 C-749 C-750 C-751 C-752 C-753 C-754 C-755 C-756 C-757 C-758 C-759 C-760 C-761 C-762 C-763 C-764 C-765 C-766 C-767 C-768 C-769 C-770 C-771 C-772 C-773 C-774 C-775 C-776 C-777 C-778 C-779 C-780 C-781 C-782 C-783 C-784 C-785 C-786 C-787 C-788 C-789 C-790 C-791 C-792 C-793 C-794 C-795 C-796 C-797 C-798 C-799 C-800 C-801 C-802 C-803 C-804 C-805 C-806 C-807 C-808 C-809 C-8010 C-8011 C-8012 C-8013 C-8014 C-8015 C-8016 C-8017 C-8018 C-8019 C-8020 C-8021 C-8022 C-8023 C-8024 C-8025 C-8026 C-8027 C-8028 C-8029 C-8030 C-8031 C-8032 C-8033 C-8034 C-8035 C-8036 C-8037 C-8038 C-8039 C-8040 C-8041 C-8042 C-8043 C-8044 C-8045 C-8046 C-8047 C-8048 C-8049 C-8050 C-8051 C-8052 C-8053 C-8054 C-8055 C-8056 C-8057 C-8058 C-8059 C-8060 C-8061 C-8062 C-8063 C-8064 C-8065 C-8066 C-8067 C-8068 C-8069 C-8070 C-8071 C-8072 C-8073 C-8074 C-8075 C-8076 C-8077 C-8078 C-8079 C-8080 C-8081 C-8082 C-8083 C-8084 C-8085 C-8086 C-8087 C-8088 C-8089 C-8090 C-8091 C-8092 C-8093 C-8094 C-8095 C-8096 C-8097 C-8098 C-8099 C-80100 C-80101 C-80102 C-80103 C-80104 C-80105 C-80106 C-80107 C-80108 C-80109 C-80110 C-80111 C-80112 C-80113 C-80114 C-80115 C-80116 C-80117 C-80118 C-80119 C-80120 C-80121 C-80122 C-80123 C-80124 C-80125 C-80126 C-80127 C-80128 C-80129 C-80130 C-80131 C-80132 C-80133 C-80134 C-80135 C-80136 C-80137 C-80138 C-80139 C-80140 C-80141 C-80142 C-80143 C-80144 C-80145 C-80146 C-80147 C-80148 C-80149 C-80150 C-80151 C-80152 C-80153 C-80154 C-80155 C-80156 C-80157 C-80158 C-80159 C-80160 C-80161 C-80162 C-80163 C-80164 C-80165 C-80166 C-80167 C-80168 C-80169 C-80170 C-80171 C-80172 C-80173 C-80174 C-80175 C-80176 C-80177 C-80178 C-80179 C-80180 C-80181 C-80182 C-80183 C-80184 C-80185 C-80186 C-80187 C-80188 C-80189 C-80190 C-80191 C-80192 C-80193 C-80194 C-80195 C-80196 C-80197 C-80198 C-80199 C-80200 C-80201 C-80202 C-80203 C-80204 C-80205 C-80206 C-80207 C-80208 C-80209 C-80210 C-80211 C-80212 C-80213 C-80214 C-80215 C-80216 C-80217 C-80218 C-80219 C-80220 C-80221 C-80222 C-80223 C-80224 C-80225 C-80226 C-80227 C-80228 C-80229 C-80230 C-80231 C-80232 C-80233 C-80234 C-80235 C-80236 C-80237 C-80238 C-80239 C-80240 C-80241 C-80242 C-80243 C-80244 C-80245 C-80246 C-80247 C-80248 C-80249 C-80250 C-80251 C-80252 C-80253 C-80254 C-80255 C-80256 C-80257 C-80258 C-80259 C-80260 C-80261 C-80262 C-80263 C-80264 C-80265 C-80266 C-80267 C-80268 C-80269 C-80270 C-80271 C-80272 C-80273 C-80274 C-80275 C-80276 C-80277 C-80278 C-80279 C-80280 C-80281 C-80282 C-80283 C-80284 C-80285 C-80286 C-80287 C-80288 C-80289 C-80290 C-80291 C-80292 C-80293 C-80294 C-80295 C-80296 C-80297 C-80298 C-80299 C-80300 C-80301 C-80302 C-80303 C-80304 C-80305 C-80306 C-80307 C-80308 C-80309 C-80310 C-80311 C-80312 C-80313 C-80314 C-80315 C-80316 C-80317 C-80318 C-80319 C-80320 C-80321 C-80322 C-80323 C-80324 C-80325 C-80326 C-80327 C-80328 C-80329 C-80330 C-80331 C-80332 C-80333 C-80334 C-80335 C-80336 C-80337 C-80338 C-80339 C-80340 C-80341 C-80342 C-80343 C-80344 C-80345 C-80346 C-80347 C-80348 C-80349 C-80350 C-80351 C-80352 C-80353 C-80354 C-80355 C-80356 C-80357 C-80358 C-80359 C-80360 C-80361 C-80362 C-80363 C-80364 C-80365 C-80366 C-80367 C-80368 C-80369 C-80370 C-80371 C-80372 C-80373 C-80374 C-80375 C-80376 C-80377 C-80378 C-80379 C-80380 C-80381 C-80382 C-80383 C-80384 C-80385 C-80386 C-80387 C-80388 C-80389 C-80390 C-80391 C-80392 C-80393 C-80394 C-80395 C-80396 C-80397 C-80398 C-80399 C-80400 C-80401 C-80402 C-80403 C-80404 C-80405 C-80406 C-80407 C-80408 C-80409 C-80410 C-80411 C-80412 C-80413 C-80414 C-80415 C-80416 C-80417 C-80418 C-80419 C-80420 C-80421 C-80422 C-80423 C-80424 C-80425 C-80426 C-80427 C-80428 C-80429 C-80430 C-80431 C-80432 C-80433 C-80434 C-80435 C-80436 C-80437 C-80438 C-80439 C-80440 C-80441 C-80442 C-80443 C-80444 C-80445 C-80446 C-80447 C-80448 C-80449 C-80450 C-80451 C-80452 C-80453 C-80454 C-80455 C-80456 C-80457 C-80458 C-80459 C-80460 C-80461 C-80462 C-80463 C-80464 C-80465 C-80466 C-80467 C-80468 C-80469 C-80470 C-80471 C-80472 C-80473 C-80474 C-80475 C-80476 C-80477 C-80478 C-80479 C-80480 C-80481 C-80482 C-80483 C-80484 C-80485 C-80486 C-80487 C-80488 C-80489 C-80490 C-80491 C-80492 C-80493 C-80494 C-80495 C-80496 C-80497 C-80498 C-80499 C-80500 C-80501 C-80502 C-80503 C-80504 C-80505 C-80506 C-80507 C-80508 C-80509 C-80510 C-80511 C-80512 C-80513 C-80514 C-80515 C-80516 C-80517 C-80518 C-80519 C-80520 C-80521 C-80522 C-80523 C-80524 C-80525 C-80526 C-80527 C-80528 C-80529 C-80530 C-80531 C-80532 C-80533 C-80534 C-80535 C-80536 C-80537 C-80538 C-80539 C-80540 C-80541 C-80542 C-80543 C-80544 C-80545 C-80546 C-80547 C-80548 C-80549 C-80550 C-80551 C-80552 C-80553 C-80554 C-80555 C-80556 C-80557 C-80558 C-80559 C-80560 C-80561 C-80562 C-80563 C-80564 C-80565 C-80566 C-80567 C-80568 C-80569 C-80570 C-80571 C-80572 C-80573 C-80574 C-80575 C-80576 C-80577 C-80578 C-80579 C-80580 C-80581 C-80582 C-80583 C-80584 C-80585 C-80586 C-80587 C-80588 C-80589 C-80590 C-80591 C-80592 C-80593 C-80594 C-80595 C-80596 C-80597 C-80598 C-80599 C-80600 C-80601 C-80602 C-80603 C-80604 C-80605 C-80606 C-80607 C-80608 C-80609 C-80610 C-80611 C-80612 C-80613 C-80614 C-80615 C-80616 C-80617 C-80618 C-80619 C-80620 C-80621 C-80622 C-80623 C-80624 C-80625 C-80626 C-80627 C-80628 C-80629 C-80630 C-80631 C-80632 C-80633 C-80634 C-80635 C- |

| DRILLING LOG | | | DIVISION South Atlantic | INSTALLATION Savannah | HOLE NO. 2. | SHEET 1 OF 2 SHEETS |
|--|-------|--------|--|--------------------------|-------------------|---|
| 1. PROJECT Savannah Harbor Widening and Deepening, Phase 2 | | | 10. SIZE AND TYPE OF PIT 1-3/8" Splitspoon, R | | | |
| 2. LOCATION (Coordinate or Section) See Plan | | | 11. DATUM FOR ELEVATION SHOWN (TIDE or MSL) Core Bit N.W. | | | |
| 3. DRILLING AGENCY Savannah District | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 C.D. -78 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | | 13. TOTAL NO. OF OVER. BURDEN SAMPLES TAKEN DISTURBED 1 Jar UNDISTURBED 0 | | | |
| 5. NAME OF DRILLER King | | | 14. TOTAL NUMBER CORE BOXES 2 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | 15. ELEVATION GROUND WATER 0.0 - Tidal | | | |
| 7. THICKNESS OF OVERTBURDEN | | | 16. DATE HOLE STARTED 21 Mar 69 COMPLETED 21 Mar 69 | | | |
| 8. DEPTH DRILLED INTO ROCK | | | 17. ELEVATION TOP OF HOLE -14.0' | | | |
| 9. TOTAL DEPTH OF HOLE 46.2' | | | 18. TOTAL CORE RECOVERY FOR BORING 55% | | | |
| | | | 19. SIGNATURE OF INSPECTOR Allen Merritt, Robert Siesen, Geologist | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | CORE RECOVERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | | | Water, very thin layer, very soft OL-organic silt above sand | | | Casing drilled in 2.0' ONLY FOR |
| -14.0 | 15 | | SP-Tan-gray, very fine sand, slightly silty | | Jar 1 | Splitspoon 14.0' to 15.5' |
| | | | SM-Gray, silty, very fine grained to medium grained sand, micaceous, with thin layers of ML-sandy silt, moderate resistance to blade penetration from 15.5' to 19.0' | 71 | | Pull #1, 15.5' to 19.0' Run 3.5', Rec 2.5' CL 1.0' |
| | 20 | | Siltstone, moderate resistance to knife blade penetration from 19.0' to 31.0' | 90 | | Pull #2, 19.0' to 24.0' Run 5.0', Rec 4.5' CL 0.5' |
| | 25 | | | 43 | | Pull #3, 24.0' to 31.0' Run 7.0', Rec 3.0' CL 4.0' |
| | 30 | | - - - - - Continued on Sheet #2 | | 1 | Soft spots recorded this run |
| (Revised by Amendment No. 0001) | | | | | | |

DRILLING LOG (Cont Sheet) | ELEVATION TOP OF HOLE

-14.0°

Holčí řád


2

**PROJECT Savannah Harbor
Widening and Deepening, Phase 2**

INSTALLATION

Savannah, Ga.

SHEET 2
OF 2 SHEETS

| ELEVATION a | DEPTH b | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV. ERY e | BOX OR SAMPLE NO. f | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g |
|----------------|------------|-------------|---|------------------------------|------------------------------|---|
| | | — — — | Siltstone | | | |
| 35 | | • • • | SM-Gray, very fine grained, slightly silty sand, very slight resistance to knife blade penetration from 31.0' to 36.0', SM sand and ML sandy silt with generally slight and spotty moderately resist- ance to knife blade penetration from 36.0' to 46.2' | 60 | | Pull #4, 31.0' to 36.0' Run 5.0', Rec 3.0' CI 2.0' |
| 40 | | • • • | Core recovery less than 10%. Driller reported material as soft while coring. | 32 | | Pull #5, 36.0' to 38.5' Run 2.5', Rec 1.7' CI 0.8' |
| 45 | | • • • | BOTTOM OF HOLE 46.2' | 68 | | Pull #6, 38.5' to 41.0' Run 2.5', Rec 1.7' CI 0.8' |
| | | • • • | Soils field classified in accordance with the Unified Soil Classification System. | 8 | | Pull #7, 41.0' to 46.2' Run 5.2', Rec 0.4' CI 4.8' |
| | | | | | 2 | |
| | | | | | |  |


(Revised by Amendment No. 0001)

HOLE NO. 3

SHEET 1
OF 2 SHEET

| | | | | | |
|--|--|--|------------------------|---------------------------|--|
| | | South Atlantic | | LOCATION Savannah, GA. | |
| 1. PROJECT Savannah Harbor Widening and Deepening, Phase 2 | | 10. SIZE AND TYPE OF PIT 1-3/8" Splitspoon/R Core | | | |
| LOCATION (Coordinates or Station) See Plan | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) | | | |
| 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 C.D. #8 | | Bit NLW | | | |
| 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED 1 Jar | UNDISTURBED 0 | | |
| 14. TOTAL NUMBER CORE BOXES 2 | | 15. ELEVATION GROUND WATER 0.0 - Tidal | | | |
| 16. DATE HOLE 24 Mar 69 | | STARTED 24 Mar 69 | COMPLETED 24 Mar 69 | | |
| 17. ELEVATION TOP OF HOLE -13.5' | | 18. TOTAL CORE RECOVERY FOR BORING 60 % | | | |
| 19. SIGNATURE OF INSPECTOR Allen Merritt, Robert L. Siesen, Geologist | | | | | |

| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
|-----------|-------|--------|--|-------------------------|-------------------------|--|
| | b | c | d | e | f | g |
| | | | Water | | | |
| | 5 | | OL-Very thin soft layer organic silt above sand | | | |
| | 10 | | | | | |
| -13.5' | 15 | | SM-Tan, gray, silty, fine grained sand | | Jar 1 | Splitspoon from 13.5' to 19.5' |
| | 20 | | Fine grained to medium grained, slightly clayey, slight to moderate resistance to knife penetration from 19.5' to 24.5' 80 | | | Used from 150 to 200 lbs pressure to core. |
| | 25 | | SH-Tan to gray, slightly silty, very fine grained sand with few thin layers of SN sand, generally slight resistance to knife blade penetration from 24.5' to 37.6' | 68 | | Pull #1, 19.5' to 24.5' Run 5.0', Rec 4.0' Cl 1.0' |
| | 30 | | ----- Continued on Sheet #2 ----- | | | Pull #2, 24.5' to 37.1' Run 6.6', Rec 4.5' Cl 1.1' |

| DRILLING LOG (Cont Sheet) | | | (ELEVATION TOP OF HOLE) | -13.5' | Hole No. | 3 |
|--|-------|--------|--|-------------------|-------------------|--|
| PROJECT Savannah Harbor Widening and Deepening, Phase 2 | | | INSTALLATION | Savannah, Ga. | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | | | SM-Tan to gray, slightly silty, very fine grained sand | 1 | | |
| 35 | | | | 52 | | Pull #3, 31.1' to 35.3' Run 4.2', Rec 2.2' C1 2.0' |
| -37.6' | | | | 43 | | Pull #4, 35.3' to 37.6' Run 2.3', Rec 1.0' C1 1.3' |
| 40 | | | Compaction shale, gray; very fine grained, silt and sand with layers of CL-sandy clay, moderate to fairly high resistance to knife blade penetration | 49 | | Pull #5, 37.6' to 46.4' Run 8.8', Rec 4.3' C1 4.5' |
| 45 | | | BOTTOM OF HOLE 46.4' | 2 | | |
| -46.4 | | | Soils field classified in accordance with the Unified Soils Classification System. | | |  |

DRILLING LOG

DIVISION

So

Atlantic

HOLE NO. 4

1

or 2

SHEETS

1. PROJECT Savannah Harbor Widening and Deepening, Phase 2
 2. LOCATION (Coordinates or Station) See Plan.

3. DRILLING AGENCY

Savannah District

4. HOLE NO. (As shown on drawing title and file number)

4

5. NAME OF DRILLER

Creamer

6. DIRECTION OF HOLE

 VERTICAL INCLINED

DEG. FROM VERT.

7. THICKNESS OF OVERBURDEN

8. DEPTH DRILLED INTO ROCK

9. TOTAL DEPTH OF HOLE

44.6'

INSTALLATION

Savannah GA.

HOLE NO. 4

10. SIZE AND TYPE OF BIT 1-3/8" Splitspoon/R Core Bit

11. DATUM FOR ELEVATION SHOWN (T.B.M or MSL)

M.L.W.

12. MANUFACTURER'S DESIGNATION OF DRILL

Filling 314 C.D. #8

13. TOTAL NO. OF OVERTURDEN SAMPLES TAKEN

DISTURBED

UNDISTURBED

1

0

14. TOTAL NUMBER CORE BOXES

2

15. ELEVATION GROUND WATER

0.0 - Tidal

16. DATE HOLE

STARTED

3 Apr 69

COMPLETED

3 Apr 69

17. ELEVATION TOP OF HOLE

-13.5'

18. TOTAL CORE RECOVERY FOR BORING

69

19. SIGNATURE OF INSPECTOR

Allen Merritt Robert L. Siesen, Geologist

| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water level, depth of weathering, etc., if significant) |
|-----------|-------|--------|--|----------------------|-------------------------|---|
| | | | Water | | | |
| 5 | | | | | | |
| 11 | | | | | | |
| -13.5' | | | | | | |
| 15 | | | SM-Gray, very fine grained, silty sand, slight resistance to knife blade penetration from 15.0' to 18.5' | 100 | Jar 1 | Splitspoon 13.5' to 15.0' Pull #1, 15.0' to 18.5' Run 3.5', Rec 3.5' |
| 20 | | | Moderate resistance to knife blade penetration from 18.5' to 24.6' | | | Pull #2, 18.5' to 24.6' Run 6.1', Rec 4.5' Cl 1.6' |
| 25 | | | Slight to moderate resistance to penetration of knife blade from 24.6' to 34.6" | 74 | | Pull #3, 24.6' to 34.6' Run 10.0', Rec 6.0' Cl 4.0' |
| 30 | | | Soft Layers | 60 | 1 | |
| | | | ----- Continued on Sheet #2 ----- | | | |
| | | | (Revised by Amendment No. 0001) | | | |

DRILLING LOG (Cont Sheet)

EL E V A T I O N T O P O F H O L E

-13.5°

Hole No. 1

4

2
2 SHEETS

INSTALLATION

Savannah, Ga.

DRILLING LOG (Cont Sheet)

EL E V A T I O N T O P O F H O L E

-15.0°

Hole No.

5

**Project Savannah Harbor
Widening and Deepening, Phase 2**

INSTALLATION

Savannah, Ga.


SHEET 2
OF 2 SHEETS

| DRILLING LOG | | DIVISION | INSTALLATION | Hole No. | SHEET / OF 2 SHEETS | |
|--|-------|--|--|---|-------------------------|--|
| | | SOUTH ATLANTIC | | SAVANNAH RIVER, GA. | | |
| 1. PROJECT SAVANNAH HARBOR | | 10. SIZE AND TYPE OF BIT 1 1/2" ID SPLITSPON | | 11. DATUM FOR ELEVATION SHOWN (TIDE, MSL) | | |
| KINGS ISLAND TURNING BASIN LOCATION (Coordinates or Station) | | | | | | |
| TE PLAN LLING AGENCY | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL CME 75 | | |
| SAVANNAH DISTRICT | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED | UNDISTURBED | |
| 4. MOLE NO. (As shown on drawing title) and file number | | 5 | | 5 | 0 | |
| 5. NAME OF DRILLER T. W. SCOTT | | 14. TOTAL NUMBER CORE BOXES | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER | | | | |
| 7. THICKNESS OF OVERTURDEN 55.0' | | 16. DATE HOLE STARTED COMPLETED | | 16 FEB. 1978 16 FEB. 1978 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' MSL | | | | |
| 9. TOTAL DEPTH OF HOLE -55.0' MSL | | 18. TOTAL CORE RECOVERY FOR BORING | | | | |
| | | 19. SIGNATURE OF INSPECTOR Charles D. Griffin | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0.0 MSL | 0' | | WATER | 0 | 1 | |
| -2.5 | | | BOTTOM OF RIVER -2.5' MSL | JAR | | BLOWS |
| 5' | | | MH - GREENISH GRAY SOFT CLAYEY SILT | | 1 | 0 |
| 10' | | | | | | 0 |
| 15' | | | | | | 0 |
| -17.5 | | | | | | 0 |
| 20' | | | SP. TAN POORLY GRADED SAND | | 2 | 0 |
| 25' | | | | | | 0 |
| 30.0 | 30' | | CONTINUED ON SHEET 2 | | | 0 |
| NOTE: Soils field classified in accordance with the Unified Soil Classification System. | | | | BLOWS PER FOOT: Number required to drive 1 1/2" ID splitspoon w/140 lb hammer falling 30". | | |

| DRILLING LOG (Cont Sheet) | | | TOP OF HOLE | 0-0 MSLW | Hole No. 511-12 | |
|---------------------------|----------------|--------|---|------------------------|-------------------------|--|
| PROJECT | Savannah River | | INSTALLATION | SHEET 3 OF 2 SHEETS | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | 30' | C | SP-TAN POORLY GRADED SAND | | 3 | 30 36 40 58 61 47 |
| | 35' | | WITH SOME GRAVEL | | | |
| 38.5 | 40' | | MH-GREEN HARD CLAYEY SILT WITH SILTY SAND LAYERS AND TRACES OF FINE MICA | | 4 | 40 58 66 81 90 79 |
| | 45' | | | | 5 | 100 83 100/0.9 94 90 |
| | 50' | | | | | |
| -55.0 | 55' | | BOTTOM OF HOLE -55.0' MSLW | | | |

Hole No. SH-14

| | | | | |
|---|--|--|---|--------------------------------|
| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah River, Savannah, GA | SHEET 1 OF 3 SHEETS |
| 1. PROJECT Enlargement of Kings Island Turnip Basin | | 10. SIZE AND TYPE OF BIT 4" Auger, 1 3/8" ID | | |
| 2. LOCATION (Coordinates or Station) N 778,045 E 818,310 | | 11. DATUM FOR ELEVATION SHOWN (TBM w/ ASL) Splitspoon MLW 7 1/4" Fishtail | | |
| 3. DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL CME-75 | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-14 | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN | DISTURBED 17 | UNDISTURBED 0 |
| 5. NAME OF DRILLER T. W. Scott | | 14. TOTAL NUMBER CORE BOXES | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | 15. ELEVATION GROUND WATER 15.1' | | |
| 7. THICKNESS OF OVERTBURDEN | | 16. DATE HOLE STARTED 16 May 78 COMPLETED 18 May 78 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE -20.5' MLW 25.0' | | |
| 9. TOTAL DEPTH OF HOLE 81.0' | | 18. TOTAL CORE RECOVERY FOR BORING | | |
| 19. SIGNATURE OF INSPECTOR DAWN MARIE HARTLEY | | | | |




| DRILLING LOG (Cont Sheet) | | | TOP OF HOLE MLW | Hole No. | SH-14 | |
|-------------------------------------|-------|--------|--|------------------------|-----------------------|---|
| Enlargement of Kings Island Turning | | | INSTALLATION | SHEET 2 OF 3 SHEETS | | |
| ELEVATION | DEPTH | LEGEND | BASIN CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| s | 30 | c | d | e | f | R BLOWS |
| - 6.0' | 30 | | SC - Gray, fine grained clayey sand, w/occasional clay layers saturated | | | 6 |
| | 35 | | SM - Gray-brown, medium to fine grained silty sand, saturated | | 77 | 18 |
| | | | Fine to medium grained W/fine gravel and gray clay layers | | 8 | 25 |
| | 40 | | Gray, fine grained, no gravel | | | 25 |
| | | | No clay, w/a fine gravel layer | | 9 | 12 |
| | 45 | | Fine to medium grained | | 10 | 18 |
| | | | Traces of decomposing organic matter | | | 24 |
| | 50 | | | | | 28 |
| | | | | | | 30 |
| | 55 | | | | | 22 |
| | | | | | | 50 |
| | 60 | | | | | 33 |
| | | | | | | 40 |
| | 65 | | | | | 40 |
| | | | | | | 26 |
| | 70 | | | | | 26 |
| | | | | | | 26 |
| -30.5' | 55 | | SC - Gray, fine grained, clayey sand | | 11 | 39 |
| -32.5' | 60 | | SM - Gray, fine to medium grained silty sand | | 12 | 45 |
| | | | W/fine gravel | | 13 | 58 |
| | 65 | | Coarse grained w/gray clay patches | | | 50 |
| | | | No clay | | | 55 |
| | 70 | | MH - Dark gray-green, plastic silt, w/ fine mica flakes & some fine gravel | | 14 | 30 |
| | | | | | | 23 |
| | | | | | | 23 |
| | | | | | | 34 |

| DRILLING LOG (Cont Sheet) | | | TOP OF HOLE | 25.0' | Hole No. | SH-14 | |
|-------------------------------------|------------|-------------|---|------------------------------|--------------------------------|--|--|
| Enlargement of Kings Island Turning | | | INSTALLATION | Savannah River, Savannah, GA | SHEET | 3 or 3 SHEETS | |
| ELEVATION a | DEPTH b | LEGEND c | BASIN CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV. ERY e | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | BLOWS f |
| | 78. | | MH MH - Dark gray-green plastic silt w/patches of fine grain gray sand throughout, w/fine mica flakes but no gravel | | 15 | | 25 27 70 27 65 70 27 90 |
| -56.0 | 75 | | | | 16 | | |
| | 80 | | Approximately 50% sand | | 17 | | |
| | 85 | | Bottom of hole 81.0' | | | | |

Hole No. SII-17

| | | | | |
|--|--|--|---|---|
| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah River, Savannah, GA | SHEET 1 OF 3 SHEETS |
| 1. PROJECT | | Enlargement of Kings Island Turning Basin | | |
| 2. LOCATION (Coordinates or Section) | | 4777480 E318730 | | |
| 3. DRILLING AGENCY | | Savannah District | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-17 | 10. SIZE AND TYPE OF BIT 1 3/8" ID Splitspoon | |
| | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) 4" Spiral MTW 7" Fishtail | |
| 5. NAME OF DRILLER | | T. W. Scott | | |
| 6. DIRECTION OF HOLE | | <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | |
| 7. THICKNESS OF OVERTURDEN | | 81.0' | 12. MANUFACTURER'S DESIGNATION OF DRILL CME 75 | |
| 8. DEPTH DRILLED INTO ROCK | | 0.0' | 13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN DISTURBED 15 UNDISTURBED 0 | |
| 9. TOTAL DEPTH OF HOLE | | 81.0' | 14. TOTAL NUMBER CORE BOXES | |
| | | | 15. ELEVATION GROUND WATER | |
| | | | 16. DATE HOLE | STARTED 18 May 78 COMPLETED 25 May 78 |
| | | | 17. ELEVATION TOP OF HOLE 25.0' MTW | |
| | | | 18. TOTAL CORE RECOVERY FOR BORING | |
| | | | 19. SIGNATURE OF INSPECTOR DAWN MARIE HARTLEY | |



| DRILLING LOG (Cont Sheet) | | | FIG | 4 TOP OF HOLE | 25.0' MLW | Hole No. | SH-17 |
|---------------------------|--|--------|--|----------------|-------------------------|-------------------------|--|
| PROJECT | Enlargement of Kings Island Turning Basin | | INSTALLATION | Savannah River | | Savannah, GA | SHEET 2 OF 3 SHEETS |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | | % CORE RECOV. ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| a | b | c | d | e | f | g | h |
| | 30. | | SM - Gray fine grained silty sand with mica flakes and green and dark brown plastic silty layers No silt, with organic matter | | | 7 | |
| | 35 | | No organic matter | | | 8 | |
| | 40 | | | | | 9 | |
| | 45 | | Fine to medium grained With wood chunks | | | 10 | |
| | 50 | | Fine grained, without wood chunks | | | 11 | |
| | 55 | | | | | 12 | |
| | 60 | | Fine to medium grained Medium to fine grained with small gray clay patches | | | 13 | |
| | 65 | | Medium grained Medium to coarse grained With wood chunks Fine to medium grained, no wood chunks, with a trace of clay | | | | |
| | 70 | | MH - Dark green plastic silt with small pockets of sand throughout, with fine mica flakes | | | | |
| | | | Continued on sheet 3 | | | | |

| DRILLING LOG (Cont Sheet) | | | ELI "TOP OF HOLE" | 25.0' MLW | Hole No. SH-17 | |
|---------------------------|--|---------|---|-------------------------|--------------------------------|--|
| PROJECT | Enlargement of Kings Island Turning Basin | | INSTALLATION | SHEET 3 of 3 SHEETS | | |
| ELEVATION | DEPTH | LEGS? C | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| a | b | c | d | e | f | g |
| | 70 | | MH - Dark green plastic silt, with fine mica flakes and small pockets of sand through- out | | | 100 |
| | | | No sand | | | 89 |
| | 75 | | | | | 55 |
| | | | | | | 30 |
| | 80 | | With occassional thin gray fine grained sand lenses | | | 31 |
| | | | | | | 36 |
| | | | | | | 40 |
| | | | | | | 30 |
| | | | Bottom of Hole 81.0' | | | |

File No. SH-18

| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah River, Savannah, GA | SHEET 1 OF 2 SHEETS | | |
|--|-------|--|---|---|--------------------------------|---|
| 1. PROJECT Enlargement of Kings Island Turning Basin | | 10. SIZE AND TYPE OF BIT 1 3/8" ID Splicespoon | | | | |
| 2. LOCATION (Coordinates or Station) N777075 E818800 | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) 4" Auger MLW | | | | |
| 3. DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL CME 75 | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-18 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 12 UNDISTURBED 0 | | |
| 5. NAME OF DRILLER T. W. Scott | | 14. TOTAL NUMBER CORE BOXES | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER | | | | |
| 7. THICKNESS OF OVERTURDEN 67.5' | | 16. DATE HOLE STARTED 1 Jun 78 COMPLETED 2 Jun 78 | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 12.7' MLW | | | | |
| 9. TOTAL DEPTH OF HOLE 67.5' | | 18. TOTAL CORE RECOVERY FOR BORING % | | | | |
| | | 19. SIGNATURE OF INSPECTOR DAWN MARIE HARTLEY | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (DESCRIPTION) | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) BLOWS |
| | 0 | | SC - Orange-tan, fine to medium grained clayey sand, moist, with gray clay layers | 1 | | W. T. 4.0' Date 1 Jun 78 Depth to water during drilling. |
| | 5 | | Saturated | 2 | | W. T. 3.5' Water Table reading 24 hrs. after hole completed. |
| | 10 | | SM - Brown, gray, fine grained, silty sand with occasional clay layers | 3 | | |
| | 10 | | OL - Dark brown, soft fat, clayey organic silt | 4 | | |
| | 10 | | SM - Tan, gray, fine grained silty sand with fine mica flakes | 5 | | |
| | 15 | | Gray | 6 | | |
| | 20 | | | 7 | | |
| | 25 | | MII - Gray-green, soft plastic silt with a trace of organic matter | 8 | | |
| | 25 | | SM - Gray, fine to medium grained silty sand | 9 | | |
| | 30 | | Fine gravel layer with occasional thin gray clay layers | 10 | | |
| | 30 | | Continued on sheet 2 | 11 | | |
| NOTE: Soils field classified in accordance with the Unified Soil Classification System. | | | | | | |
| BLOWS PER FOOT: Number required to drive 1 3/8" ID split-spoon w/140 lb. hammer falling 20" | | | | | | |

| DRILLING LOG (Cont Sheet) | | | at top of hole | 12.7' MLW | Hole No. | SH-18 | | |
|--|-------|--------|--|------------------------------|-------------------------|--|---|--|
| PROJECT Enlargement of Kings Island Turning Basin | | | INSTALLATION | Savannah River, Savannah, GA | SHEET 2 OR 2 SHEETS | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | R | BLOWS |
| | 30 | | SM - Gray, fine grained silty sand with occasional thin gray clay layers With a thin layer of fine gravel With mica flakes but no clay or gravel Fine to medium grained Medium to coarse grained with some fine gravel | | 8 | | | 22 16 22 20 15 30 20 27 33 38 30 33 34 49 40 41 49 57 89 40 40 80 33 41 |
| | 35 | | | | 9 | | | |
| | 40 | | | | 10 | | | |
| | 45 | | Fine grained, no gravel | | 11 | | | |
| | 50 | | MF - Green plastic silt with fine mica flakes | | 12 | | | |
| | 55 | | | | | | | |
| | 60 | | | | | | | |
| | 65 | | | | | | | |
| | 70 | | Bottom of Hole 67.5' | | | | | |

Hole No. SH-20

| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah River, Savannah, GA | SHEET 1 OF 2 SHEETS | | |
|--|-------|--|---|--------------------------------|---|--|
| 1. PROJECT Enlargement of Kings Island Turning Basin | | 10. SIZE AND TYPE OF BIT 1 3/8" ID Splitspoon | | | | |
| - LOCATION (Coordinates or Station) N776665 E819180 | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) 4" Auger MLW 7" Fishra. | | | | |
| 2. DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL CME 45; CME 75 | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-20 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 15 UNDISTURBED 0 | | | | |
| 5. NAME OF DRILLER T. W. Scott | | 14. TOTAL NUMBER CORE BOXES | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER | | | | |
| 7. THICKNESS OF OVERTBURDEN 70.5' | | 16. DATE HOLE STARTED 24 Apr 78 COMPLETED 30 May 78 | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 13.5' MLW | | | | |
| 9. TOTAL DEPTH OF HOLE 70.5' | | 18. TOTAL CORE RECOVERY FOR BORING % | | | | |
| 19. SIGNATURE OF INSPECTOR C. GRIFFIN/D. HARLEY | | | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | 0 | | ML - Tan inorganic silt with traces of fine sand and mica | 1 | | BLOWS 7 |
| | 5 | | becomes more sandy | 2 | | W. T. 5.0' Date 24 Apr 78 12 |
| | 5 | | SM - Dark gray and brown, fine to medium silty sand with soft silt layers | 3 | | Depth to water 8 during drilling. 7 |
| | 10 | | Dark gray and green, fine grained saturated, with no silt layers | 4 | | W. T. 3.5' Water table reading 24 hrs. after hole completed. 7 |
| | 10 | | Dark green with gray layers | 4 | | 7 |
| | 10 | | Gray with some pieces of rotten wood, no clay | 4 | | 7 |
| | 10 | | Green, no wood | 4 | | 7 |
| | 15 | | MH - Dark brown, soft fat clayey silt with traces of fine mica | 5 | | 2 0 3 0 0 0 1 4 9 8 10 111 20 1 |
| | 20 | | With tan sand layers | 6 | | |
| | 20 | | SM - Brown, fine to medium grained silty sand | 6 | | |
| | 20 | | Tan and brown | 6 | | |
| | 25 | | Gray, fine grained | 7 | | |
| | 25 | | | 7 | | |
| | 30 | | Continued on sheet 2 | | | |
| NOTE: Soils field classified in accordance with the Unified Soil Classification System. | | | | | BLOWS PER FOOT: Number required to drive 1 3/8" ID Splitspoon w/140 lb. hammer falling 20" | |

| PROJECT Enlargement of Kings Island Turning Basin | | | PLANE & TOP OF HOLE 13.5' MLW | Hole No. SH-20 | | | |
|--|-------|--------|---|-------------------------|-------------------------|--|------------------------|
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | SHEET 2 OF 2 SHEETS |
| a | b | c | d | e | f | R | BLOWS |
| | | | SM - Tan, gray, medium grained silty sand with occasional large size gravel | | | | |
| | | | Gray with gray clay layers | | | | 16 |
| 35 | | | | | | | 16 |
| | | | | | | | 15 |
| | | | | | | | 40 |
| | | | | | | | 35 |
| | | | No gravel | | | | 42 |
| 40 | | | | | | | 45 |
| | | | | | | | 24 |
| | | | No Clay | | | | 46 |
| 45 | | | | | | | 36 |
| | | | With patches of green silt | | | | 30 |
| | | | | | | | 30 |
| | | | No silt | | | | 18 |
| 50 | | | | | | | 36 |
| | | | With small gray clay patches | | | | 26 |
| | | | | | | | 26 |
| | | | MH - Green plastic silt with occasional fine grained sand lenses | | | | 35 |
| 55 | | | | | | | 32 |
| | | | | | | | 40 |
| | | | With fine mica flakes | | | | 42 |
| 60 | | | | | | | 42 |
| | | | | | | | 40 |
| | | | | | | | 40 |
| 65 | | | | | | | 44 |
| | | | No sand lenses | | | | 80 |
| 70 | | | | | | | 60 |
| | | | Bottom of Hole 70.5' | | | | |

File No. SH-22

SH-22

SHEET 1
OF 2 SHEETS

| DRILLING LOG | | DIVISION | INSTALLATION | | Hole No. SH-22 | |
|---|-------|--|---|-------------------------|--------------------------------|--|
| 1. PROJECT | | South Atlantic | Savannah River, Savannah, GA | | SHEET 1 OF 2 SHEETS | |
| Enlargement of Kings Island Turning Basin | | | 10. SIZE AND TYPE OF BIT 1 3/8" ID Splitspoon | | | |
| 2. LOCATION (Coordinates or Station) | | N776200 E819310 | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) | | 4" Auger MLW 7" Flight | |
| 3. DRILLING AGENCY | | Savannah District | 12. MANUFACTURER'S DESIGNATION OF DRILL | | CME 75 | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-22 | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED 12 | UNDISTURBED 0 |
| 5. NAME OF DRILLER | | T. W. Scott | 14. TOTAL NUMBER CORE BOXES | | | |
| 6. DIRECTION OF HOLE | | <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | 15. ELEVATION GROUND WATER | | | |
| 7. THICKNESS OF OVERTBURDEN | | 67.5' | 16. DATE HOLE | | STARTED 30 May 78 | COMPLETED 1 Jun. 78 |
| 8. DEPTH DRILLED INTO ROCK | | 0.0' | 17. ELEVATION TOP OF HOLE | | 12.5' MLW | |
| 9. TOTAL DEPTH OF HOLE | | 67.5' | 18. TOTAL CORE RECOVERY FOR BORING | | % | |
| | | | 19. SIGNATURE OF INSPECTOR | | DAWN MARIE HARTLEY | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | 0 | | SM - Brown, fine grained silty sand, moist, with mica flakes, with organic matter | 1 | | BLOWS |
| | 1 | | SC - Tan, fine grained clayey sand, damp, with mica flakes | 2 | | 12 |
| | 2 | | SM - Orange-tan, fine to medium grained silty sand, damp, with mica flakes | 3 | | W. T. 6.0' Date 30 May 78 |
| | 3 | | Saturated | 4 | | 23 25 6 |
| | 4 | | MH - Dark brown, soft fat clayey silt, with fine mica flakes | 5 | | 6 |
| | 5 | | SM - Light gray, fine grained silty sand, with mica flakes | 6 | | 7 |
| | 6 | | With occassional thin layers of organic matter | 7 | | 16 |
| | 7 | | No organic layers | 8 | | 9 |
| | 8 | | With occassional organic layers | 9 | | 15 |
| | 9 | | | 10 | | 12 |
| | 10 | | | 11 | | 12 |
| | 11 | | | 12 | | 15 |
| | 12 | | | 13 | | 12 |
| | 13 | | | 14 | | 12 |
| | 14 | | | 15 | | 12 |
| | 15 | | | 16 | | 12 |
| | 16 | | | 17 | | 12 |
| | 17 | | | 18 | | 12 |
| | 18 | | | 19 | | 12 |
| | 19 | | | 20 | | 12 |
| | 20 | | | 21 | | 14 |
| | 21 | | | 22 | | |
| | 22 | | | 23 | | |
| | 23 | | | 24 | | |
| | 24 | | | 25 | | |
| | 25 | | | 26 | | |
| | 26 | | | 27 | | |
| | 27 | | | 28 | | |
| | 28 | | | 29 | | |
| | 29 | | | 30 | | |
| | 30 | | Continued on sheet 2 | | | |
| NOTE: Soils field classified in accordance with the Unified Soil Classification System. | | | | | | |

| DRILLING LOG (Cont Sheet) | | | ELEV. + TOP OF HOLE | 12.5' MLW | Hole No. | SH-22 |
|--|-------|--------|---|-------------------------------|--------------------------------|--|
| PROJECT Enlargement of Kings Island Turning Basin | | | INSTALLATION | Savannah River, Savannah, GA, | SHEET 2 OF 2 SHEETS | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| a | b | c | d | e | f | g |
| | 30' | | SM - Light gray, fine grained silty sand, with mica flakes and occassional organic layers | | | 33 |
| | | | | | | 20 |
| | | | | | | 20 |
| 35 | | | | | 8 | 29 |
| | | | Gray, fine to medium grained | | | 17 |
| | | | | | | 17 |
| 40 | | | With occassional layers of fine gravel | | | 19 |
| | | | | | | 20 |
| | | | Fine grained, no gravel | | | 14 |
| 45 | | | Fine to medium grained | | 9 | 11 |
| | | | | | | 11 |
| | | | | | | 17 |
| 50 | | | Fine grained | | | 40 |
| | | | | | | 37 |
| | | | MH - Green plastic silt with fine mica flakes | | | 23 |
| 55' | | | | | 10 | 19 |
| | | | | | | 34 |
| | | | | | | 36 |
| 60 | | | | | | 34 |
| | | | | | | 34 |
| | | | | | | 40 |
| 65 | | | | | 11 | 66 |
| | | | | | | 70 |
| | | | | | 12 | 70 |
| | | | Bottom of Hole 67.5' | | | |
| 70 | | | | | | |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | Hole No. SH-149 | | |
|--|--|----------------------------|---|--|--------------------------------|---|
| 1. PROJECT | SAVANNAH HARBOR DEEPENING | | | SHEET 1 OF 2 SHEETS | | |
| 2. LOCATION (Coordinates or Station) | X = 817840; Y = 778530 (GA EAST) | | | 10. SIZE AND TYPE OF BIT 1 3/8" I.D. SPLIT SPOON | | |
| 3. DRILLING AGENCY | SAVANNAH DISTRICT | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | |
| 4. HOLE NO. (As shown on drawing title and file number) | SH-149 | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | |
| 5. NAME OF DRILLER | D. JUSTISS | | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN 15 DISTURBED 0 UNDISTURBED 0 | | |
| 6. DIRECTION OF HOLE | <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | 14. TOTAL NUMBER CORE BOXES 0 | | |
| 7. THICKNESS OF OVERTBURDEN | 60.0' | | | 15. ELEVATION GROUND WATER SEE REMARKS | | |
| 8. DEPTH DRILLED INTO ROCK | 0.0' | | | 16. DATE HOLE STARTED 18 Oct 91 COMPLETED 18 Oct 91 | | |
| 9. TOTAL DEPTH OF HOLE | 60.0' | | | 17. ELEVATION TOP OF HOLE | | |
| | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A % | | |
| | | | | 19. SIGNATURE OF INSPECTOR J. Justiss, P.G. | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0 | 0 | b | (SM) BROWN, SILTY FINE TO MEDIUM SAND, TRACE OF ROOTS, SLIGHTLY DAMP. | • | 1 | CLEANED OUT HOLE WITH 4" SPIRAL AUGER FROM 1.5' TO 4.5' & 6.0' TO 9.0'. JAR SAMPLE #2 TAKEN FROM AUGER FROM 1.5' TO 4.5'. |
| 5 | 5 | c | (SP) LIGHT BROWN TO TAN, POORLY GRADED FINE TO MEDIUM SAND, TRACE OF SILT, SLIGHTLY DAMP. | | 2 | BOGAN USING 5 1/2" FISHTAIL & ZEIGEL DRILLING MUD AT 10.5'. |
| 10 | 10 | | (SM) BROWN, SILTY, FINE TO MEDIUM SAND, DAMP. MEDIUM SAND, WET. / MEDIUM TO COARSE SAND, SOME FINE TO MEDIUM SAND FROM 10.3' TO 10.5'. WASH | | 3 | SPLIT SPOON DRIVES TAKEN AT 4.5' INTERVALS. |
| 15 | 15 | | (SC) GREENISH GRAY, CLAYBY, FINE TO MEDIUM SAND, SOME SILT, TRACE OF MICA, WET. | | 4 | WATER LEVEL 6.5' DEPTH TO WATER DURING DRILLING. |
| 20 | 20 | | WASH | | 5 | WATER LEVEL NOT ENCOUNTERED 21 Oct 91. TAPEO HOLE TD 5.0'. |
| 25 | 25 | | (SM) TANNISH GRAY, SILTY, MEDIUM TO COARSE SAND, TRACE OF CLAY, WET. | | 6 | |
| 30 | 30 | - | WASH | | 7 | |
| | | | SAME AS 22.5' TO 24.0'! WASH | | 8 | |
| CONTINUED ON SHEET #2 NOTE: SOILS VISUALLY FIELD CLASSIFIED IN ACCORDANCE WITH THE UNIFIED SOIL CLASSIFICATION SYSTEM. | | | | BLOWS PER FOOT: NUMBER REQUIRED TO DRIVE 1 3/8" I.D. SPLIT- SPOON WITH 140 LB. HAMMER FALLING 30". | | |

| DRILLING LOG (Cont. Sheet) | | | ELEVATION TOP OF HOLE | | | Hole No. SH-149 | |
|--------------------------------------|-------|--------------|---|-----------------|--------------------------|--|----|
| PROJECT SAVANNAH HARBOR DEEPENING | | | INSTALLATION SAVANNAH, GA. | | | SHEET 2 OF 2 SHEETS | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOVERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) BLOWS | |
| 30 | 30 | c | | | | | |
| | | | Wash. | | | | |
| | | | (SM) Grey, fine to med. silty SAND. Trace of mica, wet. | | 9 | | 24 |
| | | | Wash. | | | | |
| 35 | 35 | | (SP) Grey, med. to coarse, poorly graded SAND. Trace of silt & mica, wet. | | 10 | | 39 |
| | | | Wash. | | | | |
| 40 | 40 | | Same as 36.0' to 37.5' but coarse sand, Trace of fine gravel. | | 11 | | 46 |
| | | | Wash. | | | | |
| 45 | 45 | | Same as 40.5' to 42.0'. | | 12 | | 33 |
| | | | Wash. | | | | |
| 50 | 50 | | (GP) Greenish-grey, fine, poorly graded GRAVEL. Trace of silt & coarse sand, wet. | | 13 | | 17 |
| | | | Wash. NOTE: Wash return contained some sand and clay. | | | | |
| 55 | 55 | /\ / \ / \ / | (CL) Greyish-green, silty, lean CLAY. Trace of mica & fine sand, slightly damp. | | 14 | | 36 |
| | | | Wash | | | | |
| 60 | 60 | /\ / \ / \ / | Bottom of Boring 60.0' | | 15 | | 45 |
| | | | Same as 54.0' to 55.5' but dry. | | | | |

Hole No. SH-10U

| DRILLING LOG | | VISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 2 SHEETS | | |
|--|------------|---|--|----------------------------|--------------------------------|---|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " splitspoon, 4" spiral auger, 5 $\frac{1}{2}$ " fishtail | | | | |
| 2. LOCATION (Coordinates or Station) X-817555 Y-779145 GA. EAST | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-150 | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | DISTURBED 18 UNDISTURBED 0 | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | 14. TOTAL NUMBER CORE BOXES 0 | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER SEE REMARKS | | | | |
| 7. THICKNESS OF OVERTBURDEN 64.5' | | 16. DATE HOLE STARTED 16 OCT 91 COMPLETED 17 OCT 91 | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE | | | | |
| 9. TOTAL DEPTH OF HOLE 64.5' | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | | |
| 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | | | | |
| ELEVATION a | DEPTH b | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc. If significant) |
| | 0 | . | (SP) Tan, coarse, poorly graded SAND. Damp. | | 1 | |
| | 5 | . | (SC) Olive, fine clayey SAND. Some silt, damp. | | 2 | Cleaned out hole with spiral auger to 4.5'. Jar #2 taken from auger from 1.5' to 4.5'. Splitspoon drive taken at each 4.5' interval to 55.5'. Began using 5 $\frac{1}{2}$ " fishtail & Zeogel drilling mud at 6.0'. |
| | 10 | . | Fine to med. sand, trace of fine gravel, wet. | | 3 | Water level 2.0' depth to water during drilling. |
| | 15 | . | Wash. NOTE: Wash return contained large amount of clay. | | 4 | Water level 1.7' depth to water on 21 Oct 91. Taped hole to 19.8' depth. |
| | 20 | . | Same as 4.5' to 6.0'. | | 5 | |
| | 25 | . | Wash. | | 6 | |
| | 30 | . | (SP) Olive grey, med., poorly graded SAND. Trace of silt, wet. | | 7 | |
| | 35 | . | Wash. | | 8 | |
| | 40 | . | (SM) Olive-grey, med., silty SAND, wet. | | | |
| | 45 | . | Wash. | | | |
| | 50 | . | Note: Traces of wood in wash. | | | |
| | 55 | . | (SP) Light brown, med. to coarse, poorly graded SAND. Trace of silt, wet. | | | |
| | 60 | . | Wash. | | | |
| | 65 | . | Same as 22.5' to 24.0', but with traces of fine gravel. | | | |
| | 70 | . | Wash. | | | |
| | 75 | . | Continued on sheet #2 | | | |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". |

DRILLING LOG (Cont.Sheet)

ELEVATION TOP OF HOLE


Hole No. SH-150

PROJECT
SAVANNAH HARBOR DEEPENINGINSTALLATION
SAVANNAH, GA.SHEET 2
OF 2 SHEETS


| ELEVATION | DEPTH ^a _b | LEGEND ^c | CLASSIFICATION OF MATERIALS ^d (Description) | % CORE RECOV- ERY ^e | BOX OR SAMPLE NO. JAR ^f | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) ^g | BLOWS ^h |
|-----------|---------------------------------------|------------------------|---|---|--|--|-----------------------|
| | 30 | | Wash. (SP) Light brown,fine to med poorly graded SAND. Trace of silt, wet. | | 9 | | 33 |
| 35 | | | Wash. | | 10 | | 30 |
| | 31.5 | | Same as 31.5' to 33.0' but med. to coarse sand. | | | | |
| 40 | | | Wash. | | 11 | | 26 |
| | 36.0 | | Same as 36.0' to 37.5' but with some wood. | | 12 | | 27 |
| 45 | | | Wash. | | 13 | | 31 |
| | 44.5 | | (SP) Greyish-brown,coarse,poor- ly graded SAND. Trace of fine gravel & silt, wet. | | 14 | | |
| 50 | | | Wash. | | 15 | | 54 |
| | 49.5 | | (CL) Greyish-green,silty lean CLAY. Trace of Mica & fine sand, dry. | | 16 | | |
| 55 | | | Wash | | 17 | | |
| | 51.0 | | Same as 49.5' to 51.0' but greyish-green. | | 18 | | |
| 60 | | | Wash. | | | Began continuous splitspoon drives at 58.5'. | |
| | 58.5 | | | | | | 100/0.8 |
| 65 | | | (SM) Grey & greenish-grey,fine silty SAND. Trace of Mica,dry. | | | | 78 |
| | 63.5 | | (SC) Greyish-green,fine clayey SAND. Some silt, dry. | | | | 42 |
| 65 | | | Bottom of Boring 64.5' | | | | 43 |

Hole No. SH-15 /

| | | | | | | | |
|--|--|--------------------------|--|--|---------------|-----------------|------------------------|
| DRILLING LOG | | VISION SOUTH ATLANTIC | | INSTALLATION | SAVANNAH, GA. | | SHEET 1 OF 1 SHEETS |
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " split spoon, $5\frac{1}{2}$ " fishtail | | | |
| 2. LOCATION (Coordinates or Station) X-817067 Y-779191 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-157 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED 15 | UNDISTURBED 0 |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERTBURDEN 59.6' (Water 38.6') | | | | 16. DATE HOLE STARTED 10 DEC 91 COMPLETED 10 DEC 91 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 59.6' | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | |
| | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |



| | | | | | | | |
|--|--|--------------------------|--|---|---------------|--|------------------------|
| DRILLING LOG | | VISION SOUTH ATLANTIC | | INSTALLATION | SAVANNAH, GA. | | SHEET 1 OF 1 SHEETS |
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " splitspoon, $5\frac{1}{2}$ " fishtail | | | |
| 2. LOCATION (Coordinates or Station) x-817368 Y-779194 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-158 | | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN. 6 DISTURBED 0 UNDISTURBED | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERBURDEN 60.0' (WATER 34.5') | | | | 16. DATE HOLE STARTED 6 DEC 91 COMPLETED 16 DEC 91 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 60.0' | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A % | | | |
| 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | | | | | |



| DRILLING LOG | | VISION SOUTH ATLANTIC | | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 1 SHEETS | |
|--|-------------|---|--|-------------------------------|--------------------------------|--|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | 10. SIZE AND TYPE OF BIT 1 $\frac{1}{8}$ " splitspoon, 5 $\frac{1}{2}$ " fishtail | | | | |
| 2. LOCATION (Coordinates or Station) X-816934 Y-778722 GA. EAST | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-159 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 4 DISTURBED 0 UNDISTURBED 0 | | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | 14. TOTAL NUMBER CORE BOXES 0 | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | | | |
| 7. THICKNESS OF OVERTBURDEN 50.3' (Water 41.3') | | 16. DATE HOLE STARTED 14 JAN 92 COMPLETED 14 JAN 92 | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | | | |
| 9. TOTAL DEPTH OF HOLE 50.3' | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | | |
| | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | | |
| ELEVATION 0.0 | DEPTH 0, | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY e | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) f |
| | | | Water | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 42.3'. |
| 40 | | | Bottom of Harbor 41.3' | | | |
| -41.3' | | | (SC) Olive-grey, fine clayey SAND. Trace of mica. | 1 | | |
| -42.8' | | | (SM) Dark grey, fine silty SAND. Trace of clay & mica. | 2 | | 5 |
| -45.8' | | | (SC) Dark grey, fine clayey SAND. Some silt, trace of mica. | 3 | | 33 |
| -47.3' | | | Trace of silt. | | | 62 |
| -50.3' | | | Bottom of Boring 50.3' | 4 | | 29 |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | 39 |
| | | | | | | 52 |
| | | | | | | BLOWS PER FOOT: Number required to drive 1 $\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". |

| DRILLING LOG | | VISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 1 SHEETS | | | |
|--|------------|---|--|-------------------------|--------------------------------|--|-------|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " Splitspoon, $5\frac{1}{2}$ " Fishtail | | | | | |
| 2. LOCATION (Coordinates or Station) X=817039 Y=778184 GA. EAST | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-160 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 15 DISTURBED 10 UNDISTURBED | | | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | 14. TOTAL NUMBER CORE BOXES 0 | | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | | | | |
| 7. THICKNESS OF OVERTBURDEN 50.8' (Water 40.3') | | 16. DATE HOLE STARTED 14 JAN 91 COMPLETED 14 JAN 91 | | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | | | | |
| 9. TOTAL DEPTH OF HOLE 50.8' | | 18. TOTAL CORE RECOVERY FOR BORING N/A % | | | | | |
| | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | | | |
| ELEVATION 0.0 | DEPTH 0 | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | BLOWS |
| | | | Water | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 43.4'. | |
| -40.3' | 40 | | Bottom of Harbor 40.3' | | | | |
| -40.3' | 38 | | (MH) Dark grey to black clayey SILT. | | 1 | Weight of rods drove splitspoon from 40.3' to 42.6'. Cont'd. drive to 43.3' with three hammer blows. Jar sample 2 from approx. 42.6' to 43.3'. | 0 |
| -42.6' | 42 | | (SC) Dark grey, fine to medium clayey SAND. | | 2 | | |
| -43.3' | 43 | | (SM) Dark grey, fine silty SAND. Trace of clay. | | 3 | | |
| -46.3' | 46 | | (SC) Grey, fine clayey SAND. Some silt. Trace of mica. | | 4 | | |
| -50.8' | 50 | | Bottom of Boring 50.8' | | 5 | | |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". | |

| DRILLING LOG | | | VISION SOUTH ATLANTIC | INSTALLATION | AVANNAH, GA. | | SHEET 1 OF 1 SHEETS |
|--|-------|--------|--|-------------------------|--------------------------------|---|------------------------|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{2}$ " Splitspoon, $5\frac{1}{2}$ " Fishtail | | | | |
| 2. LOCATION (Coordinates or Station) X-818085 Y-778090 GA. EAST | | | 11. DATUM FOR ELEVATION SHOWN (TBM or NSL) MLW | | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-161 | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 4 DISTURBED 0 UNDISTURBED | | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | 14. TOTAL NUMBER CORE BOXES 0 | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | 15. ELEVATION GROUND WATER N/A | | | | |
| 7. THICKNESS OF OVERTBURDEN 50.9' (Water 38.9') | | | 16. DATE HOLE STARTED 14 JAN 91 COMPLETED 14 JAN 91 | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | 17. ELEVATION TOP OF HOLE 0.0' | | | | |
| 9. TOTAL DEPTH OF HOLE 50.9' | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | | |
| | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | |
| 0.0 | 0' | | Water | | | BLOWS | |
| | 35 | | | | | Scale change at 35.0'. Set 6" diameter casing by own weight to 44.9'. | |
| -38.9' | 40 | | (MH) Very dark grey clayey SILT. | | | Weight of rods drove splitspoon from 38.9' to 44.9'. Jar sample 2 from approx. 44.0' to 44.9'. | |
| -44.0' | 45 | | (SC) Dark grey, fine to medium clayey SAND. | 1 | | 0 | |
| -44.9' | 45 | | Fine sand, some silt, trace of mica. | 2 | | 23 | |
| -50.9' | 50 | | Bottom of Boring 50.9' | 3 | | 43 | |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | 4 | | 41 | |
| | | | | | | 45 | |
| | | | | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{2}$ " I.D. splitspoon w/140 lb. hammer falling 30". | |


Hole No. SH-162

| DRILLING LOG | | VISION SOUTH ATLANTIC | | INSTALLATION SAVANNAH, GA. | | SHEET 1 OF 1 SHEETS | |
|--|-------|--------------------------|--|--|--------------------------------|---|--|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " split spoon, $5\frac{1}{2}$ " fishtail | | | |
| 2. LOCATION (Coordinates or Station) X-817143 Y-777680 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSU) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-162 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 6 DISTURBED 10 UNDISTURBED | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERBURDEN 59.9' (Water 41.5') | | | | 16. DATE HOLE STARTED 26 JAN 92 COMPLETED 26 JAN 92 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 59.9' | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | |
| | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | |
| 0.0 | 0 | c | | | | BLOWS | |
| | | | Water | | | Scale change at 41.5'. Set 6" diameter casing by own weight to 43.3'. | |
| | 40 | | Bottom of Harbor 41.5' | | | | |
| -41.5' | | | (MH) Very dark grey to black clayey SILT. Some fine to coarse sand. | | 1 | Weight of rods drove split spoon from 41.5' to 43.4'. Jar sample 2, taken from approx. 43.0' to 43.4'. | |
| -43.0' | | | (SC) Very grey, fine clayey SAND. Some silt. | | 2 | 0 | |
| -43.4' | | | Trace of mica. | | 3 | 59 | |
| -46.4' | | | Trace of silt. | | 4 | 43 | |
| | 45 | | | | 5 | 43 | |
| | 50 | | | | 6 | 45 | |
| | 55 | | | | | 42 | |
| | 60 | | Bottom of Boring 59.9' | | | 41 | |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | 46 | |
| | | | | | | 45 | |
| | | | | | | 57 | |
| | | | | | | 59 | |
| | | | | | | 45 | |
| | | | | | | BLOWS PER FOOT: | |
| | | | | | | Number required to drive $1\frac{1}{8}$ " I.D. split spoon w/140 lb. hammer falling 30". | |

Hole No. SH-102


| DRILLING LOG | | VISION SOUTH ATLANTIC | | INSTALLATION SAVANNAH, GA. | | SHEET 1 OF 1 SHEETS | |
|--|-------------------------|--------------------------|--|---|------------------------------|--------------------------------|---|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " splitspoon, $5\frac{1}{4}$ " fishtail | | | |
| 2. LOCATION (Coordinates or Station) X-817375 Y-777535 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Falling 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-163 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | 6 | DISTURBED UNDISTURBED |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES | | 0 | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | | 16. DATE HOLE | | STARTED 16 Nov 91 | COMPLETED 16 NOV 91 |
| 7. THICKNESS OF OVERTBURDEN 59.8' (Water 41.8') | | | | 17. ELEVATION TOP OF HOLE | | 0.0' | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 18. TOTAL CORE RECOVERY FOR BORING | | N/A | % |
| 9. TOTAL DEPTH OF HOLE 59.8' | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |
| ELEVATION 0.0 | DEPTH 0 _b | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | | % CORE RECOV- ERY • | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g |
| | | | | | | | BLOWS |
| | | | Water | | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 45.8'. |
| | 40 | | Bottom of Harbor 41.8' | | | | |
| -41.8' | | | (MH) Dark grey, fat SILT. | | | 1 | Weight of hammer drove split- spoon from 41.8' to 44.3', Cont'd. drive with five blows to 44.8'. |
| -43.3' | | | (SC) Dark grey & grey, med. to coarse clayey SAND. | | | 2 | 0 |
| -44.8' | 45 | | (SM) Grey, fine silty SAND. Some clay in layers up to 0.3' thick, trace of mica. | | | 3 | 5 |
| -46.3' | | | (SC) Greenish grey, fine clayey SAND. Some silt, trace of mica. | | | 4 | 48 |
| | 50 | | | | | 5 | 36 |
| | 55 | | | | | | 53 |
| | | | | | | | 51 |
| | | | | | | | 35 |
| | | | | | | | 45 |
| | | | | | | | 53 |
| | | | | | | | 68 |
| | | | | | | | 61 |
| | | | | | | | 62 |
| -59.8' | 60 | | Bottom of Boring 59.8' NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". |

Hole No. SH-104

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | | INSTALLATION | SAVANNAH, GA. | | SHEET 1 OF 1 SHEETS |
|--|-------------------|--|--|--|--------------------------------|---|-------------------------|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT 1 1/8" SPLIT SPOON, 5 1/2" FISHTAIL | | | |
| 2. LOCATION (Coordinates or Station) X-818481 Y-777661 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-164 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED 6 | UNDISTURBED 0 |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERTBURDEN 60.5' (Water 38.6') | | | | 16. DATE HOLE STARTED 16 NOV 91 COMPLETED 16 NOV 91 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 60.5' | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | |
| ELEVATION 0.0 | DEPTH 0 | LEGEND  | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY • | BOX OR SAMPLE NO. UAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | |
| | | | Water | | | 9 BLOWS | |
| -38.6' | 35 | | Bottom of Harbor 38.6' | | | Scale change at 35.0'. Set 6" diameter casing by own weight to 43.6'. | |
| -38.6' | 40 |  | (MH) Dark grey, clayey SILT. Very wet & soft. | | 1 | Weight of hammer drove split spoon from 38.6' to 44.0'. Jar 2 from 43.7' to 44.0'. 0 | |
| -43.7' | 45 |  | (SC) Greenish-grey, fine clayey SAND. Some silt, trace of mica. | | 2 | | |
| -43.7' | 50 | | | | 3 | | |
| -43.7' | 55 | | | | 4 | | |
| -43.7' | 60 | | | | 5 | | |
| -60.5' | 60 | | Bottom of Boring 60.5' | | 6 | | |
| NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | | BLOWS PER FOOT: Number required to drive 1 1/8" I.D. split spoon w/140 lb. hammer falling 30". | | | |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 1 SHEETS | | |
|--|-------|----------------------------|--|--------------------------------|--------------------------------|---|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ "splitspoon, $5\frac{1}{2}$ " fishtail | | | |
| 2. LOCATION (Coordinates or Station) X-817521 Y-777184 GA. EAST | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-165 | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 16 | DISTURBED UNDISTURBED 10 | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERTBURDEN 50.8' (Water 38.8') | | | 16. DATE HOLE STARTED 14 JAN 92 | COMPLETED 14 JAN 92 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 50.8' | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | |
| | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0.0 | 0' | c | | | | BLOWS |
| -38.8' | 40' | | Water | | | Scale change at 35.0'. Set 6" diameter casing by own weight to 45.1'. |
| -38.8' | 40' | | | | | |
| -38.8' | 40' | | Bottom of Harbor 41.5' 38.8' | | | |
| -38.8' | 40' | | | | | |
| -38.8' | 40' | | (MH) Dark olive-grey, clayey SILT. | | | |
| -38.8' | 40' | | | | | |
| -42.8' | 45' | | (SC) Very dark grey to black, medium to coarse clayey SAND. Some silt. | | 1 | Weight of rods drove splitspoon from 38.8' to 43.3'. Jar sample 2 taken from approx. 42.8' to 43.3'. |
| -42.8' | 45' | | | | 2 | |
| -42.8' | 45' | | | | 3 | |
| -42.8' | 45' | | | | 4 | |
| -42.8' | 45' | | | | 5 | |
| -42.8' | 45' | | | | 6 | |
| -42.8' | 45' | | | | | |
| -44.8' | 45' | | (SM) Grey, fine silty SAND. Trace of clay & mica. | | | |
| -44.8' | 45' | | | | | |
| -44.8' | 45' | | | | | |
| -46.3' | 45' | | (SC) Grey, fine clayey SAND. Some silt, trace of mica. | | | |
| -46.3' | 45' | | | | | |
| -46.3' | 45' | | | | | |
| -50.8' | 50' | | Bottom of Boring 50.8' | | | BLOWS PER FOOT: |
| -50.8' | 50' | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | Number required to drive $1\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". |
| -50.8' | 50' | | | | | |
| -50.8' | 50' | | | | | |

| | | | | |
|--|--|---|-------------------------------|------------------------|
| DRILLING LOG | | VISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 1 SHEETS |
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | 10. SIZE AND TYPE OF BIT 1 $\frac{1}{8}$ "splitspoon, 5 $\frac{1}{2}$ "fishtail | | |
| 2. LOCATION (Coordinates or Station) x-817973 Y-777182 GA.EAST | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-166 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 6 DISTURBED 10 UNDISTURBED | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | 14. TOTAL NUMBER CORE BOXES 0 | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | |
| 7. THICKNESS OF OVERTBURDEN 60.8' (Water 41.3') | | 16. DATE HOLE STARTED 14 DEC 91 COMPLETED 14 DEC 91 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | |
| 9. TOTAL DEPTH OF HOLE 60.8' | | 18. TOTAL CORE RECOVERY FOR BORING N/A X | | |
| | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | |



| DRILLING LOG | | | VISION SOUTH ATLANTIC | INSTALLATION | AVANNAH, GA. | | SHEET 1 OF 1 SHEETS |
|--|-------|--------|--|--------------|---|-------------------------|--|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " split spoon, $5\frac{1}{2}$ " fishtail | | | | |
| 2. LOCATION (Coordinates or Station) X-819096 Y-777170 GA. EAST | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-167 | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 5 DISTURBED 10 UNDISTURBED | | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | 14. TOTAL NUMBER CORE BOXES 0 | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | 15. ELEVATION GROUND WATER N/A | | | | |
| 7. THICKNESS OF OVERTBURDEN 59.7' (WATER 42.6') | | | 16. DATE HOLE STARTED 24 JAN 92 COMPLETED 24 JAN 92 | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | 17. ELEVATION TOP OF HOLE 0.0' | | | | |
| 9. TOTAL DEPTH OF HOLE 59.7' | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | | |
| | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | | % CORE RECOV- ERY JAR | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0.0 | 0 | c | d | | ' | | BLOWS |
| -42.6' | 40 | | Water | | | | Scale change at 40.0'. |
| -42.6' | 42.6 | | Bottom of Harbor 34.5' | | | | Set 6" diameter casing by own weight to 45.1'. |
| -42.6' | 44.7 | | (CH) Dark grey, fat CLAY. Some fine sand. | | 1 | | Weight of rods drove split spoon from 42.6' to 44.7. |
| -42.6' | 45 | | (SC) Grey, fine clayey SAND. Some silt. | | 2 | | 0 |
| -42.6' | 50 | | | | 3 | | 33 |
| -42.6' | 55 | | | | 4 | | 40 |
| -42.6' | 59.7 | | Bottom of Boring 59.7' | | 5 | | 38 |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. split spoon w/140 lb. hammer falling 30". | | |

Hole No. SH-168

| | | | |
|--|--------------------------|---|--------------------------------------|
| DRILLING LOG | VISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 1 SHEETS |
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | 10. SIZE AND TYPE OF BIT $1\frac{3}{8}$ " split spoon, $5\frac{1}{2}$ " fishtail | |
| 2. LOCATION (Coordinates or Station) X-817468 Y-776786 GA. EAST | | 11. DATUM FOR ELEVATION SHOWN (TBM or NSL) MLW | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | |
| 4. HOLE NO. (As shown on drawing title and file number) | SH-168 | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | DISTURBED 4 UNDISTURBED 0 |
| 5. NAME OF DRILLER DAVID JUSTISS | | 14. TOTAL NUMBER CORE BOXES 0 | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | |
| 7. THICKNESS OF OVERTBURDEN 53.5' (Water 40.7') | | 16. DATE HOLE 25 JAN 92 | STARTED COMPLETED 25 JAN 92 |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | |
| 9. TOTAL DEPTH OF HOLE 53.5' | | 18. TOTAL CORE RECOVERY FOR BORING N/A % | |
| 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | | INSTALLATION SAVANNAH, GA. | | SHEET 1 OF 1 SHEETS | |
|--|--------------|----------------------------|--|--|--------------------------------|---|--|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " split spoon, $5\frac{1}{2}$ " fishtail | | | |
| 2. LOCATION (Coordinates or Station) X-817466 Y-776799 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-168A | | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 2 UNDISTURBED 0 | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERTBURDEN 59.5' (Water 38.3') | | | | 16. DATE HOLE STARTED 25 JAN 92 COMPLETED 25 JAN 92 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 59.5' | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | |
| | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |
| ELEVATION 0.0 | DEPTH 0.0 | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY • | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g BLOWS | |
| | | | Water | | | Scale change at 35.0'. Set 6" diameter casing by own weight to 44.5'. Hole SH-168A is a companion log to SH-168 which was completed to 53.5' before moving barge out of the shipping lane for traffic. | |
| -38.3' | 35 | | Bottom of Harbor 38.3' | | | Cleared out from 38.3' to 53.5' with $5\frac{1}{2}$ " fishtail. | |
| | 40 | | Wash (see remarks) | | | | |
| | 45 | | | | | | |
| | 50 | | | | | | |
| -53.5' | 55 | | (SC) Dark grey, fine clayey SAND. Trace of silt & mica. | | 1 | 75 | |
| | 60 | | Bottom of Boring 59.5' | | 2 | 62 | |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | 75 | |
| | | | | | | 57 | |
| | | | | | | BLOWS PER FOOT: | |
| | | | | | | Number required to drive $1\frac{1}{8}$ " I.D. split spoon w/140 lb. hammer falling 30". | |

Hole No. 2H-104

| DRILLING LOG | | VISION SOUTH ATLANTIC | | INSTALLATION | SAVANNAH, GA. | | SHEET 1 OF 1 SHEETS |
|--|-------------|--------------------------|--|---|--------------------------------|---|------------------------|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT 1 $\frac{1}{8}$ " SPLITSPOON, 5 $\frac{1}{2}$ " FISHTAIL | | | |
| 2. LOCATION (Coordinates or Station) X-818643 Y-776483 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSU) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-170 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 5 DISTURBED 0 UNDISTURBED | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERTBURDEN 59.8' (Water 41.8') | | | | 16. DATE HOLE STARTED 17 NOV 91 COMPLETED 17 NOV 91 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 59.8' | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A % | | | |
| | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |
| ELEVATION 0.0 | DEPTH 0, | LEGEND e | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY • | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc. If significant) g | |
| | | | Water | | | BLOWS | |
| | 40 | | Bottom of Harbor 41.8' | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 42.6'. | |
| -41.8' | | | (CL) Greenish-grey, silty lean CLAY. Trace of mica & fine sand. | | 1 | 20 | |
| -44.8' | 45 | | (SC) Greenish-grey, fine clayey SAND. Some silt, trace of mica. | | 2 | 27 | |
| | 50 | | | | 3 | 42 | |
| | 55 | | | | 4 | 36 | |
| | 60 | | | | 5 | 30 | |
| -59.8' | | | Bottom of Boring 59.8' | | | 52 | |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | 42 | |
| | | | | | | 65 | |
| | | | | | | 60 | |
| | | | | | | 63 | |
| | | | | | | 80 | |
| | | | | | | 64 | |
| | | | | | | BLOWS PER FOOT: | |
| | | | | | | Number required to drive 1 $\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". | |

| DRILLING LOG | | 'VISION SOUTH ATLANTIC | | INSTALLATION | SAVANNAH, GA. | | SHEET 1 OF 1 SHEETS |
|--|------------|---------------------------|--|---|--------------------------------|------------------------------|--|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " splitspoon, $5\frac{1}{2}$ " fishtail | | | |
| 2. LOCATION (Coordinates or Station) X-817736 Y-776361 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-171 | | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 6 DISTURBED 0 UNDISTURBED | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERTBURDEN 60.5' (WATER 39.5') | | | | 16. DATE HOLE STARTED 14 DEC 91 COMPLETED 14 DEC 91 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 60.5' | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A % | | | |
| ELEVATION 0.0 | DEPTH 0 | LEGEND c | CLASSIFICATION OF MATERIALS (Description) | | % CORE RECOV- ERY JAR | BOX OR SAMPLE NO. 1 | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | | | Water | | | | Scale change at 35.0'. Set 6" diameter casing by own weight to 45.7'. |
| | 35 | | Bottom of Harbor 39.5' | | | | |
| -39.5' | 40 | | (MH) Dark grey, clayey SILT. | | | 1 | Weight of rods drove splitspoon from 39.5' to 45.5'. |
| -44.5' | 45 | | (SC) Dark grey, fine to medium clayey SAND. | | | 2 | |
| -45.5' | 45 | | (CH) Grey, fat CLAY. Some silt & fine sand. | | | 3 | |
| -48.5' | 50 | | (SC) Grey, fine clayey SAND. | | | 4 | |
| -60.5' | 60 | | Bottom of Boring 60.5' | | | 5 | |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | 6 | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". |

| DRILLING LOG | | VISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 1 SHEETS | | |
|--|--------------|--------------------------|--|------------------------------------|--------------------------------|---|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " SPLIT SPOON, $5\frac{1}{2}$ " FISHTAIL | | | |
| 2. LOCATION (Coordinates or Station) X-818054 Y-775978 GA. EAST | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-172 | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 4 | DISTURBED 0 UNDISTURBED 0 | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERTBURDEN 59.9' (Water 43.4') | | | 16. DATE HOLE STARTED 25 JAN 92 | COMPLETED 25 JAN 92 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 59.9' | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | % | | |
| | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |
| ELEVATION 0.0 | DEPTH 0.0 | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY • | BOX OR SAMPLE NO. UAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) e |
| | | | Water | | | Blows |
| | | | | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 44.3'. |
| | | | | | | 0 |
| -43.4' | 40 | | | | | |
| -43.4' | 45 | | (CL) Dark grey, silty lean CLAY. Some fine sand. | | 1 | |
| -47.9' | 47 | | | | | 27 |
| -47.9' | 50 | | Dark (SC)-Olive-grey, fine clayey SAND. Some silt, trace of mica. | | 2 | 99 |
| -47.9' | 55 | | Olive-grey. | | 3 | 32 |
| -59.9' | 59 | | | | 4 | 31 |
| -59.9' | 60 | | Bottom of Boring 59.9' NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | 100/0.6 100/0.9 90 89 100/0.6 100/0.9 90 54 39 |
| | | | | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 1 SHEETS |
|--|-------|---|---|--|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | 10. SIZE AND TYPE OF BIT 1 $\frac{1}{8}$ " SPLITSPOON, 5 $\frac{1}{2}$ " FISHTAIL | | |
| 2. LOCATION (Coordinates or Station) X-818264 Y-775913 | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-173 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 15 DISTURBED 0 UNDISTURBED 0 | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | 14. TOTAL NUMBER CORE BOXES 0 | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | |
| 7. THICKNESS OF OVERTBURDEN 59.8' (Water 44.4') | | 16. DATE HOLE STARTED 27 JAN 92 COMPLETED 27 JAN 92 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | |
| 9. TOTAL DEPTH OF HOLE 59.8' | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | |
| | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOVERY BOX OR SAMPLE NO. UAR REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0.0 | 0.0 | | | 0 BLOWS |
| | | | Water | |
| | 40 | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 48.2'. |
| -44.4' | 45 | | Bottom of Harbor 44.4' | |
| -44.4' | 45 | | (MH) Very dark grey to black clayey SILT. | 1 Weight of rods drove splitspoon from 44.4' to 47.9'. Jar sample 2 taken from approx. 47.5' to 47.9'. 0 |
| -47.5' | 50 | | (SC) Dark grey, fine clayey SAND. Trace of silt. | 2 |
| -47.5' | 50 | | | 3 |
| -47.5' | 55 | | | 4 |
| -47.5' | 55 | | | 5 |
| -59.8' | 60 | | Bottom of Boring 59.8' | 100/0.9 |
| <p>NOTE: Soils visually field classified in accordance with the Unified Soil Classification System.</p> <p>BLOWS PER FOOT: Number required to drive 1$\frac{1}{8}$" I.D. splitspoon w/140 lb. hammer falling 30".</p> | | | | |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 1 SHEETS | | |
|--|--------------|--|--|------------------------------|------------------------------|---|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | 10. SIZE AND TYPE OF BIT 1 $\frac{1}{8}$ " SPLIT SPOON, 5 $\frac{1}{2}$ " FISHTAIL | | | | |
| 2. LOCATION (Coordinates or Station) X-818856 Y-775859 GA. EAST | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-174 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 6 UNDISTURBED 0 | | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | 14. TOTAL NUMBER CORE BOXES 0 | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | | | |
| 7. THICKNESS OF OVERTBURDEN 59.6' (Water 41.6') | | 16. DATE HOLE STARTED 27 JAN 92 COMPLETED 27 JAN 92 | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | | | |
| 9. TOTAL DEPTH OF HOLE 59.6' | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | | |
| | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | | |
| ELEVATION 0.0 | DEPTH 0.0 | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY • | BOX OR SAMPLE NO. e | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) f |
| | | | Water | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 41.9'. |
| | 40 | | Bottom of Harbor 41.6' | | | |
| -41.6' | | | (SC) Dark grey, fine clayey SAND. Some silt, trace of mica. | | 1 | |
| -43.1' | | | (SM) Dark grey, fine silty SAND. Some clay & mica. | | 2 | 30 |
| -45 | | | | | | 76 |
| -46.1' | | | (SC) Grey, fine clayey SAND. Trace of silt. | | 3 | 49 |
| -49.1' | | | | | 4 | 34 |
| -50 | | | | | | 38 |
| -55 | | | | | 5 | 44 |
| -59.6' | 60 | | Dark grey. | | 6 | 55 |
| | | | Bottom of Boring 59.6' | | | 61 |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | 64 |
| | | | | | | 68 |
| | | | | | | 92 |
| | | | | | | 80 |
| | | | | | | BLOWS PER FOOT: Number required to drive 1 $\frac{1}{8}$ " I.D. spoon w/140 lb. hammer falling 30". |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 1 SHEETS | | | |
|--|--------------|--|--|------------------------------|------------------------------|---|-------|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " SPLIT SPOON, $5\frac{1}{2}$ " FISHTAIL | | | | | |
| 2. LOCATION (Coordinates or Station) X-818516 Y-775447 GA. EAST | | 11. DATUM FOR ELEVATION SHOWN (TBM or NSL) MLW | | | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-175 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 5 UNDISTURBED 0 | | | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | 14. TOTAL NUMBER CORE BOXES 0 | | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | | | | |
| 7. THICKNESS OF OVERTBURDEN 60.1' (Water 43.6') | | 16. DATE HOLE STARTED 17 NOV 91 COMPLETED 17 NOV 91 | | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | | | | |
| 9. TOTAL DEPTH OF HOLE 60.1' | | 18. TOTAL CORE RECOVERY FOR BORING N/A % | | | | | |
| | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | | | |
| ELEVATION 0.0 | DEPTH 0.0 | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY e | BOX OR SAMPLE NO. f | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g | BLOWS |
| | | | Water | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 44.1'. | |
| -43.6' | 40 | | Bottom of Harbor 43.6' | | | | |
| -45.1' | 45 | | (SC) Greenish-grey, fine clayey SAND. Some silt, trace of mica. | 1 | | | 24 |
| -46.6' | 46 | | Light olive to greenish-grey. | | | | 37 |
| | 50 | | Greenish-grey. | 2 | | | 42 |
| | 55 | | | | 3 | | 42 |
| | 60 | | | | 4 | | 49 |
| -60.1' | 60 | | Bottom of Boring 60.1' | | 5 | | 74 |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | | 50 |
| | | | | | | | 57 |
| | | | | | | | 77 |
| | | | | | | | 77 |
| | | | | | | | 90 |
| | | | | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". | |

| | | | | |
|--|--|---|-------------------------------------|--|
| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah, GA | |
| 1. PROJECT Savannah Harbor Widening | | 10. SIZE AND TYPE OF BIT 3/8" ID splitspoon & | | |
| 2. LOCATION (Coordinates or Station) X-819190, Y-775340 | | 11. DATUM FOR ELEVATION SHOWN (TBM or ASL) 4X5½ MLW carhillloy | | |
| 3. DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL Falling 314 | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-84 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 11 UNDISTURBED 0 | | |
| 5. NAME OF DRILLER T.W. Scott, E. Mauldin | | 14. TOTAL NUMBER CORE BOXES | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL, <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER 0.0 MLW | | |
| 7. THICKNESS OF OVERTBURDEN 50.1' | | 16. DATE HOLE STARTED 12 Sep 83 COMPLETED 12 Sep 83 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0 MLW | | |
| 9. TOTAL DEPTH OF HOLE 50.1' | | 18. TOTAL CORE RECOVERY FOR BORING | | |
| | | 19. SIGNATURE OF INSPECTOR James E. Bolen Geologist <i>James E. Bolen</i> | | |

| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) BLOWS |
|-----------|-------|--------|--|----------------------|--------------------------------|--|
| 0.0 | 0' | c | Sea Water 0.0'-26.9' | / | | |
| | 10 | | | | | Note: Change of scale @ 20.0'. |
| | 20 | | | | | |
| | 25 | | | | | |
| -26.9 | | | Bottom of Harbor 26.9' | | | |
| | 30 | | SM-Gray silty coarse, medium sand low silt content | | 1 | Note: Weight of tool 26.9-27.5' |
| | 30 | | Gray, black with traces of fine gravel and clay | | 2 | Set 6" diameter steel casing to |
| | 30 | | Gray silty coarse medium sand, low silt content | | 3 | .29.2'. 15 |
| | 35 | | | | 4 | 14 |
| | 35 | | | | 5 | 15 |
| | 38.0 | | | | 6 | 58 |
| | 40 | | ML-Dark green clayey silt with 15% fine sand | | 7 | 50 Note: Change of scale at 40.0' 52 |
| | 42 | | | | 8 | 38 |
| | | | Continued on Sheet 2 Note: Soils field classified in accordance with the Unified Soil Classification System. | | | 59 Blows Per Foot: Number required to drive 1 3/8" ID splitspoon w/140 lb. hammer falling 30". |

| DRILLING LOG (Cont Sheet) | | | ELEVATION TOP OF HOLE 0.0MLW | Hole No. SH-84 | | |
|-------------------------------------|-------|--------|--|-----------------------|--------------------------------|---|
| PROJECT Savannah Harbor Widening | | | INSTALLATION Savannah, GA | | | SHEET 2 of 2 SHEETS |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. e | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g Blow |
| -42.0 | 42b | c | ML-Dark green clayey silt, with 15% fine sand | | 8 | Began Coring at 42.5' |
| -42.5 | | | Core Loss-42.5'-45.6' believed to be clayey silt, easily washed out, rapid bit penetration. | 0 RQD | | Pull 1 From 42.5' To 45.6' Run. 3.1' Rec 0.0' CL 3.1' All core washed out. |
| -45.6 | 45 | | ML-Dark green clayey silt, with 15% fine sand | | 45.6' | Note: Change of scale at 45.0' |
| -50.1 | 50 | | Bottom of Hole: 50.1' | | 9 10 11 | Note: Resume split- 82 spooning at 45.6' 43 65 Note: Depth figure in column 'e' is a taped depth after Pull. |

Hole No. SH-83

| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah, GA | SHEET 1 OF 1 SHEETS | | |
|---|-------|--|--|------------------------|------------------------|---|
| 1. PROJECT Savannah Harbor Widening | | 10. SIZE AND TYPE OF BIT 1-3/8" ID splitspoon, 5" | | | | |
| 2. LOCATION (Coordinates or Station) X-820005, Y-773530 | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) fishtail | | | | |
| 3. DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-83 | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN | | DISTURBED 8 | UNDISTURBED 0 | |
| 5. NAME OF DRILLER T.W. Scott | | 14. TOTAL NUMBER CORE BOXES | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL, <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER | | | | |
| 7. THICKNESS OF OVERBURDEN 45.8' | | 16. DATE HOLE | | STARTED 10 Sep 83 | COMPLETED 11 Sep 83 | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | | | |
| 9. TOTAL DEPTH OF HOLE 45.8' | | 18. TOTAL CORE RECOVERY FOR BORING | | | | |
| 19. SIGNATURE OF INSPECTOR James Arthur, Geologist | | | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOVERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0.0' | 0.6 | c | Sea Water 0.0'-17.3' | | | Blows |
| -17.3 | 17 | | Bottom of Harbor: 17.3' | | | Note change of scale at 17.0' |
| -20.3 | 22 | | SP-Gray medium to coarse poorly graded sand with trace of fine gravel | 1 | | Note: Set 6" casing to 17.3'. 2 |
| -23.3 | 22 | | Tannish gray with trace of silt | 2 | | Weight of rods with hammer drove split-spoon from 17.3' to 38 |
| -24.8 | 27 | | SM-Tannish gray fine to medium silty sand with layer of gray plastic silt | 3 | | 42 |
| -30.8 | 32 | | SP-Tannish gray fine to medium poorly graded sand with trace of silt | 4 | | drive to 18.8' 40 |
| -33.8 | 37 | | Gray, fine grained, trace of mica | | | Reset casing to 24.2', 34.0' 35.8' and 36.8'. 69 |
| -35.3 | 37 | | Tannish gray, fine to medium grained. | | | 30 |
| -39.8 | 42 | | Medium to coarse grained with 15% fine gravel | | | 30 |
| -45.8 | | | Fine to medium grained with trace of fine gravel. | | | 36 |
| | | | CL-Green micaceous lean clay | 7 | | 32.3' Ten blows required to drive 51 |
| | | | With 20% fine sand | 8 | | splitspoon from 33.7' to 33.8' 47 |
| | | | Bottom of Hole: 45.8' Note: Soils field classified in accordance with the Unified Soil Classification System. | | | 39.8' Casing stopped following wash with --43 fishtail 48 |
| | | | | | | 43 |
| | | | | | | Blows Per Foot: Number required to drive 1 3/8" ID splitspoon w/140 lb. hammer falling 30". |

Hole No. SH-85

SHEET 1
OF 2 SHEETS

| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah, GA | | | |
|---|-------------|--|--|------------------------------|--------------------------------|--|
| 1. PROJECT Savannah Harbor Widening | | 10. SIZE AND TYPE OF BIT 1 3/8" ID splitspoon | | | | |
| 2. LOCATION (Coordinates or Station) X-821038, Y-771926 | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | | |
| 3. DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-85 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED 12 | UNDISTURBED 0 | |
| 5. NAME OF DRILLER T.W. Scott and Earl Maulden | | 14. TOTAL NUMBER CORE BOXES | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL, <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER | | 0.0 MLW | | |
| 7. THICKNESS OF OVERTBURDEN 50.0' | | 16. DATE HOLE | | STARTED 13 Sep 83 | COMPLETED | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE | | 0.0 MLW | | |
| 9. TOTAL DEPTH OF HOLE 50.0' | | 18. TOTAL CORE RECOVERY FOR BORING | | % | | |
| | | 19. SIGNATURE OF INSPECTOR James E. Bolen Geologist | | James E. Bolen | | |
| ELEVATION 0.0' | DEPTH 0' | LEGEND a b c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY e | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | | | Sea Water 0.0'-21.5' | | | Blows |
| | 10 | | | | | |
| | 20 | | | | | |
| -21.5 | | | Bottom of Harbor: 21.5' | | | |
| -23.0 | | | Wood chips, fibers (old piling ?) | 1 | | |
| | 25 | | SM-Gray, brown silty coarse, medium sand (low silt content) | 2 | | |
| | 30 | | Gray silty medium grained sand, with a trace of coarse sand | 3 | | SAMPLE LAB |
| | 35 | | | 4 | | No. Class LL PL PI |
| | | | | 5 | | 14 |
| | | | | 6 | | 2 |
| | | | | 7 | | SP NP NP NP 12 |
| | | | | 8 | | 6 SP NP NP NP 12 |
| | | | | 9 | | 7 CH 99 31 68 |
| | | | | | | 10 CH 97 34 63 26 |
| | | | | | | |
| | | | | | | 17 |
| | | | | | | 27 |
| | | | | | | 25 |
| | | | | | | 19 |
| | | | | | | 27 |
| | | | | | | 30 |
| | | | | | | 16 |
| -39.5 | 40 | | Gray silty medium fine sand | | | 54 |
| | | | ML-Dark green clayey silt with 10% fine sand | 7 | | 93 |
| | | | | 8 | | |
| | | | | 9 | | |
| -45.0 | 45 | | Continued on Sheet 2 Note: Soils field classified in accordance with the Unified Soil Classification System. | | | Blows Per Foot: Number required to drive 1 3/8" ID splitspoon w/140 lb. hammer falling 30". |

DRILLING LOG (Cont Sheet)

ELEVATION TOP OF HOLE

0.0' MLW

Hole No. SH-85

PROJECT

Savannah Harbor Widening


INSTALLATION

Savannah, GA

SHEET 2
OF 2 SHEETS

| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. | JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | G | BLOW |
|-----------|-------|--------|---|-------------------------|-------------------------|-----|--|---|------|
| -49.0 | 45 b | c | ML-Dark green clayey silt with 10% fine sand With 15% fine sand | e | 9 | | | | 5 |
| | | | | | 10 | | | | 6 |
| | | | | | 11 | | | | 5 |
| -50.0 | 50 | | Bottom of Hole: 50.0' | | 12 | | | | 6 |

| | | | | | |
|--|--|--|------------------------------|------------------------|------------------|
| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah, GA | SHEET 1 OF 1 SHEETS | |
| 1. PROJECT Savannah Harbor Widening | | 10. SIZE AND TYPE OF BIT 1 3/8" ID splitspoon, 5" | | | |
| 2. LOCATION (Coordinates or Station) X-824219, Y-768031 | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) fishtail MLW | | | |
| 3. DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-86 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED 7 | UNDISTURBED 0 |
| 5. NAME OF DRILLER T.W. Scott | | 14. TOTAL NUMBER CORE BOXES | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER | | | |
| 7. THICKNESS OF OVERTURDEN 51.0' | | 16. DATE HOLE STARTED 14 Sep 83 COMPLETED 14 Sep 83 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' MLW | | | |
| 9. TOTAL DEPTH OF HOLE 51.0' | | 18. TOTAL CORE RECOVERY FOR BORING % | | | |
| | | 19. SIGNATURE OF INSPECTOR James E. Bolen & James Arthur, Geologist | | | |



Hole No. SH-87

| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah, GA | SHEET 1 OF 2 SHEETS |
|---|-------|--|---|---|
| 1. PROJECT Savannah Harbor Widening | | 10. SIZE AND TYPE OF BIT 3/8" ID splitspoon | | |
| 2. LOCATION (Coordinates or Station) X-826323, Y-765959 | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) | | |
| 3. DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | |
| 4. HOLE NO. (As shown on line 1 above) and file number SH-87 | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN DISTURBED 9 UNDISTURBED 0 | | |
| 5. NAME OF DRILLER E. Maulden & T. Scott | | 14. TOTAL NUMBER CORE BOXES | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL, <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER 0.0' MLW | | |
| 7. THICKNESS OF OVERBURDEN 50.0' | | 16. DATE HOLE STARTED 14 Sep 83 COMPLETED 15 Sep 83 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' MLW | | |
| 9. TOTAL DEPTH OF HOLE 50.0' | | 18. TOTAL CORE RECOVERY FOR BORING | | |
| 19. SIGNATURE OF INSPECTOR James E. Bolen, Geologist <i>James E. Bolen</i> | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOVERY BOX OR SAMPLE NO. JAR REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) Blows |
| 0.0' | 0 | b c | d | |
| | 10 | | Sea Water 0.0'-19.6' | |
| | 15 | | | Note: Change of scale at 10.0' |
| -19.6 | 20 | | Bottom of Harbor 19.6' | |
| | 25 | | SM-Gray, brown silty coarse, medium sand with 5% rounded fine gravel, subangular grains | |
| | 30 | | No Sample | |
| -28.0 | 30 | X | | Note: Weight of hammer 19.6'-20.5' |
| | 35 | | SM-Gray, brown silty coarse, medium sand with 5% rounded fine gravel | |
| -32.0 | 35 | X | Continued on Sheet 2 | |
| -35.0 | 35 | | Note: Soils field classified in accordance with the Unified Soil Classification System. | Blows Per Foot: Number required to drive 1 3/8" ID splitspoon with 140lb hammer falling 30". |

| DRILLING LOG (Cont Sheet) | | | ELEVATION TOP OF HOLE | 0.0' MLW | Hole No. | SH-87 |
|---------------------------|--------------------------|--------|--|-----------------------|--------------------------------|--|
| PROJECT | Savannah Harbor Widening | | INSTALLATION | Savannah, GA | SHEET 2 OF 2 SHEETS | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS <i>(Description)</i> | % CORE RECOV. e | BOX OR SAMPLE NO. JAR | REMARKS <i>(Drilling time, water loss, depth of weathering, etc., if significant)</i> |
| -35.0 | 35.6 | c | SM-Gray, brown silty coarse, medium sand with 10% fine gravel; low silt content, <u>subangular grains</u> Silty coarse sand with some fine gravel | | 6 | 40 43 33 18 26 51 17 12 37 62 |
| -48.0 | 45 | | | | 8 | |
| -50.0 | 50 | | ML-Dark green, clayey silt with 25% fine sand | | 9 | |
| | | | Bottom of Hole: 50.0' | | | |

| DRILLING LOG | | | DIVISION | INSTALLATION | | | Hole No. SH-70 | SHEET 1 OF 2 SHEETS |
|--|-------|--------|---|--------------|--|--|-------------------------|---|
| 1. PROJECT Savannah Harbor Widening | | | South Atlantic | | | Savannah, GA | | |
| 2. LOCATION (Coordinates or Station) X-828814, Y-763538 | | | | | | 10. SIZE AND TYPE OF BIT 1 3/8" ID splitspoon 4" | | |
| 3. DRILLING AGENCY Savannah District | | | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | | SH-70 | | | MLW | | |
| 5. NAME OF DRILLER T.W. Scott | | | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Sprague & Henwood | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | | | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN | | |
| 7. THICKNESS OF OVERTBURDEN 60.1' | | | | | | DISTURBED 6 UNDISTURBED 0 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | | | 14. TOTAL NUMBER CORE BOXES | | |
| 9. TOTAL DEPTH OF HOLE 60.1' | | | | | | 15. ELEVATION GROUND WATER | | |
| | | | | | | 16. DATE HOLE STARTED 8 Sep 82 COMPLETED 8 Sep 82 | | |
| | | | | | | 17. ELEVATION TOP OF HOLE 0.0' | | |
| | | | | | | 18. TOTAL CORE RECOVERY FOR BORING | | |
| | | | | | | 19. SIGNATURE OF INSPECTOR J. Attent, Geologist | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | | | % CORE RECOV- ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | 0 b | c | d | | | e | f | |
| | 20 | | Water | | | | | Note: Top of Hole established at 0.0' MLW. |
| | 25 | | | | | | | Note: Scale changed at 20.0' |
| -27.5 | | | Bottom of Harbor 27.5' | | | | | Note: Checked water depth using tape with heavy weight. |
| | 30 | | MH-Gray fat silt. | | | | JAR | Note: 27.5' to 30.7' weight of rod string drove splitspoon. 30.7'-43.6' weight of rod string plus hammer drove splitspoon. |
| | 35 | | | | | | 1 | 0 |
| | 40 | | | | | | | |
| -43.6 | | | SM-Gray fine to medium silty sand | | | | | |
| | 45 | | With layers of gray fat silt | | | | 2 | 18 |
| -47.5' | | | Continued on Sheet # 2 Note: Soils field classified in accordance with the Unified Soil Classification System. | | | | | 18 |
| | | | | | | | | Blows Per Foot: Number required to drive 1 3/8 ID splitspoon w/140 |

DRILLING LOG (Cont Sheet) ELEVATION TOP OF HOLE 0.0' MLW Hole No. SH-70

OBJECT Savannah Harbor Widening

INSTALLATION Savannah, GA

SHEET
OF 2 2 SHEETS

| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
|-----------|-------|--------|--|-------------------------|-------------------------|--|
| s | c | d | e | f | g | |
| | 47b.5 | | SM-Gray fine to medium silty sand with layers of gray fat silt. | | | 30 |
| | 50 | | Green medium to coarse silty sand with trace of fine gravel and mica | 3 | | 100/0.9 |
| -51.1 | | | MH-Green fat silt with some fine sand and mica | 4 | | 50 |
| -52.6 | | | SM-Green fine silty sand with some mica With trace of fine gravel | 5 | | 30 |
| | 55 | | | | | 50 |
| | 57 | | | | | 20 |
| -60.1 | 60 | | With no gravel | 6 | | 47 |
| | 62 | | Bottom of Hole: -60.1' | | | 45 |

| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah, GA | SHEET OF 1 SHEETS | | |
|--|-------------|---|--|-------------------------|------------------------------|--|
| 1. PROJECT Savannah Harbor Widening | | 10. SIZE AND TYPE OF BIT 1 3/8" ID 5" splitspoon | | | | |
| 2. LOCATION (Coordinates or Station) X-830688, Y-761519 | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) M.L.W | | | | |
| 3. DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL Sprague Henwood | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-69 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 2 UNDISTURBED 0 | | | | |
| 5. NAME OF DRILLER T. Scott | | 14. TOTAL NUMBER CORE BOXES | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER | | | | |
| 7. THICKNESS OF OVERRUNNEN | | 16. DATE HOLE STARTED 26 Jul 82 COMPLETED 28 Jul 82 | | | | |
| 8. DEPTH DRILLED INTO ROCK | | 17. ELEVATION TOP OF HOLE 0.0' MLW | | | | |
| 9. TOTAL DEPTH OF HOLE 57.0 | | 18. TOTAL CORE RECOVERY FOR BORING 19. SIGNATURE OF INSPECTOR B. Green & T. Scott | | | | |
| ELEVATION 0.0' | DEPTH 06 | LEGEND e | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. 1 | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | | | Water | | | |
| | 5 | | | | | |
| | 10 | | | | | |
| | 15 | | | | | |
| | 20 | | | | | |
| 22.0 | | | | | | |
| | 25 | | CH-Dark gray, fat clay, with seams of SC | | 1 | Note: Spoon pushed by weight of drill string and hammer |
| | 30 | | | | | |
| | 35 | | | | | |
| -37.0 | | | | | | |
| | 40 | | SP-Gray, medium-grained, poorly sorted sand, with some silt. | | 2 | |
| | 45 | | FN | | 3 | |
| -45.0 | | | CN | | 4 | |
| | 50 | | No Sample | | | |
| -57.0 | | | | | | |
| | 55 | | | | | |
| | 60 | | Bottom of Hole:-57.0' Note: Soils field classified in accordance with the Unified Soil Classification System. | | | Note: Hole abandoned at EL. -57.0 due to gravel in hole. Blows Per foot: Number required to drive 1 3/8" ID splitspoon w/140 lb. hammer falling. |

Hole No. SH-82

| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah, GA | SHEET 1 OF 1 SHEETS | | |
|--|------------|--|---|------------------------------|--------------------------------|--|
| 1. PROJECT Savannah Harbor Widening | | 10. SIZE AND TYPE OF BIT 3/8" TD Splitspoon 5" | | | | |
| LOCATION (Coordinates or Station) X-821690, Y-771180 | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) Fishtail | | | | |
| 3. DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL Falling 314 | | | | |
| 4. HOLE NO. (As shown on and file numbered) SH-82 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 9 UNDISTURBED 0 | | | | |
| 5. NAME OF DRILLER T.W. Scott | | 14. TOTAL NUMBER CORE BOXES 0 | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER | | | | |
| 7. THICKNESS OF OVERTBURDEN 49.6' | | 16. DATE HOLE STARTED 9 Sep 83 COMPLETED 10 Sep 83 | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | | | |
| 9. TOTAL DEPTH OF HOLE 49.6' | | 18. TOTAL CORE RECOVERY FOR BORING | | | | |
| | | 19. SIGNATURE OF INSPECTOR James Arthur, Geologist | | | | |
| ELEVATION 0.0' | DEPTH 0 | LEGEND b e | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY • | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | | | Sea Water 0.0'-22.8' | | | Note: Change of scale at 22.0' |
| -22.8 | 22 | | Bottom of Harbor: 22.8' | | | |
| -24.3 | | | SP-fine to medium poorly graded sand with trace of silt | | 1 | Note: Set 6" casing to 27.4'. Reset casing to 33.0', 37.9' and 40.1'. 8 |
| -25.8 | 27 | | Medium to coarse grained with trace of fine gravel | | | 7 |
| -28.8 | | | Fine to medium grained with no gravel | | | 14 |
| -31.8 | 32 | | Gray, medium to coarse grained. | | 2 | 26 |
| -33.3 | | | Coarse grained, no silt | | | |
| -34.8 | | | Trace of fine gravel, layer of blue fat clay from 34.5' to 34.8' | | 3 | SAMPLE LAB No. Class LL PL PI 17 |
| -37.8 | 37 | | Coarse grained with trace of silt, fine gravel and layer of fat clay from 35.8' to 36.0' | | 4 | 2 2 SP NP NP NP 19 |
| -42.3 | | | Medium to coarse grained | | 5 | 4 4 SP NP NP NT |
| -43.8 | | | Coarse grained with trace of fine gravel, thin layer of clayey sand from 43.2'-43.5' | | 6 | 8 8 SM - - - .. 48 |
| -46.8 | 47 | | With 15% fine gravel | | 7 | 80 |
| -49.6 | | | SM-Green fine silty sand with trace of mica and fine gravel. | | 8 | 26 |
| | | | Bottom of Hole: 49.6' Note: Soils field classified in accordance with the Unified Soil Classification System. | | 9 | 25 |
| | | | | | | 30 |
| | | | | | | 47 |
| | | | | | | 57 |
| | | | | | | 73 |
| | | | | | | 100 |
| | | | | | | 100 |
| | | | | | | 100/0 S |
| | | | | | | Note: 47.9'-48.3' cleaned out hole with fishtail. 100/0 f |
| | | | | | | Blows Per Foot: Number required to drive 1 3/4" ID splitspoon w/140 lb. hammer falling 30". 100/0 S |

HOLE NO. V-90A

| | | | | | | | |
|---|-------|--|--|---|-------------------|-----------------------------------|---|
| DRILLING LOG | | South Atlantic | | Savannah, Ga. | | 1 OF 1 SHEETS | |
| 1. PROJECT | | Widening & Deepening Savannah Harbor | | 10. SIZE AND TYPE OF BIT | | 3-1/2" ID Sampler | |
| 2. LOCATION (Coordinates or Name) | | Sta. 94B, N. Side | | 11. DATUM FOR ELEVATION SHOWN (ODD DRAWS, ETC.) | | MLW | |
| 3. DRILLING AGENCY | | Alpine Geophysical Assoc. | | 12. MANUFACTURER'S DESIGNATION OF DRILL | | Alpine 20' VIBROCore Sampler | |
| 4. DRILL NO. (If shown on drawing add and file number) | | V-90A | | 13. TOTAL NO. OF OVERBURDEN | | 0 | |
| 5. NAME OF DRILLER | | Al Stockel | | SAMPLES TAKEN | | 0 | |
| 6. DIRECTION OF HOLE | | <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 14. TOTAL NUMBER CORE BOXES | | 1 Plastic Tube | |
| 7. THICKNESS OF OVERBURDEN | | | | 15. ELEVATION GROUND WATER | | Tide Gage 6.3 | |
| 8. DEPTH DRILLED INTO ROCK | | | | 16. DATE HOLE | | STARTED 5-24-67 COMPLETED 5-24-67 | |
| 9. TOTAL DEPTH OF HOLE | | 7.5' | | 17. ELEVATION TOP OF HOLE | | -36.7 | |
| | | | | 18. TOTAL CORE RECOVERY FOR BORING | | 71 % | |
| | | | | 19. SIGNATURE OF INSPECTOR | | J. A. Albritton | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | | % CORE RECOV. ERT | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| -35.0 | | | | | | | Time Sec./Ft. |
| -35.0 | | | No Sample | | | | Zone-of-Core-Loss 0.5 |
| -40.0 | | | SM-Green, micaceous, fine, silty sand. | | 71 | V-90A | -36.7 to -38.9 0.5 1.0 1.0 |
| | | | ML-Green, dense, sandy silt, toward a compaction shale | | | | grading below -43.0' 3.0 2.0 |
| | | | BOTTOUM OF HOLE -44.2' | | | | 108. 310/0.5 |
| | | Soils field classified in accordance with the Unified Soil Classification System. | | | | | ONLY |

Hole No. CS-1

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | INSTALLATION SAVANNAH RIVER HARBOR | SHEET 1 OF 2 SHEETS | | |
|--|-------|---|--|--------------------------------|-------------------------|--|
| PROJECT MINGS ISLAND TAPPING ASSN | | 10. SIZE AND TYPE OF BIT 1 1/2" ID SPLIT SPOON | | | | |
| 2. LOCATION (Coordinates or Station) OFF SITE STA. 1001750 1 1/2 MILE EAST OF BLUFFETT ROAD IP | | 11. DATUM FOR ELEVATION SHOWN (TIDE OR MSL) 11 L 1/4 | | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL C.P.P.D. SURF & HENWOOD | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) CS 1 | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN DISTURBED 5 UNDISTURBED 0 | | | | |
| 5. NAME OF DRILLER J. Mc DONALD | | 14. TOTAL NUMBER CORE BOXES | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER | | | | |
| 7. THICKNESS OF OVERTBURDEN | | 16. DATE HOLE STARTED COMPLETED 3 MARCH 1973 3 APRIL 1973 | | | | |
| 8. DEPTH DRILLED INTO ROCK | | 17. ELEVATION TOP OF HOLE 0.0' MLW | | | | |
| 9. TOTAL DEPTH OF HOLE 15.1' BELOW MLW | | 18. TOTAL CORE RECOVERY FOR BORING % | | | | |
| | | 19. SIGNATURE OF INSPECTOR Ch. 74.01 D. Griffin | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | 0 | | | 100 | | BLOWS |
| | 5 | | | | | |
| | 10 | | | | | |
| -13.6 | | | WATER | | | |
| | 15 | | WATER DEPTH 13.6' AT MLW SM. GRAY SILTY FINE & MEDIUM SAND | | 1 | 88 |
| | 20 | | W/ GREEN | | 2 | 79 |
| | 25 | | OLIVE GREEN | | 3 | 81 |
| | 30 | | | | 4 | 68 |
| | | | | CONTINUED ON SHEET NO 2 - - 74 | | |

DRILLING LOG (Cont Sheet 2, ON TOP OF HOLE)

-13.6 BELOW NEW

Hole No.

CS 1

PROJECT: KUNIS ISLAND DRILLING EXP'DN INSTALLATION: CIVIL ENGINEERING SHEET 2
OF 2 SHEETS

| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | R. FL |
|-----------|-------|--------|--|-------------------------|-------------------------|--|-------|
| a | b | c | d | e | f | | |
| | | | SM - OLIVE GREEN SILTY FINE SAND | | | | 100 |
| | | | | | | | 99 |
| | | | | | | | 88 |
| 35 | | | | | | | 100 |
| | | | | | | | 94 |
| | | | | | | | 88 |
| 40 | | | | | | | 93 |
| | | | | | | | 76 |
| | | | | | | | 94 |
| 45 | | | | | | | 98 |

NOTE: Soils field classified
in accordance with the Unified
Soil Classification System.

BLOWS PER FOOT:

Number required to drive
1 $\frac{1}{2}$ " ID splitspoon w/140 lb.
hammer falling 30"

| DRILLING LOG | | DIVISION | INSTALLATION | | Hole No. | CS 2 | |
|--|---|--|--|--|---|-------------------------|--|
| PROJECT | | | | | SHEET 1 OF 1 SHEETS | | |
| <i>Killen Island Turnig Basin</i> | | | 10. SIZE AND TYPE OF BIT | | 10. SIZE AND TYPE OF BIT | | |
| 2. LOCATION (Coordinates or Site) | | 100' NE ON 16 | 11. DATUM FOR ELEVATION SHOWN (TAN = MSL) | | 11. DATUM FOR ELEVATION SHOWN (TAN = MSL) | | |
| 3. DRILLING AGENCY | | Oppy., 350' above M.L.W. F.D.G.F. | 12. MANUFACTURER'S DESIGNATION OF DRILL | | 12. MANUFACTURER'S DESIGNATION OF DRILL | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | CS-2 | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED | UNDISTURBED | |
| 5. NAME OF DRILLER | | ME Don, Jr. | 14. TOTAL NUMBER CORE BOXES | | 0 | | |
| 6. DIRECTION OF HOLE | | <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | 15. ELEVATION GROUND WATER | | In River | | |
| 7. THICKNESS OF OVERTURDEN | | | 16. DATE HOLE | | STARTED | COMPLETED | |
| 8. DEPTH DRILLED INTO ROCK | | | 17. ELEVATION TOP OF HOLE | | 5 Apr. 17 | 11 Am. 17 | |
| 9. TOTAL DEPTH OF HOLE | | 45.0' | 18. TOTAL CORE RECOVERY FOR BORING | | % | | |
| | | | 19. SIGNATURE OF INSPECTOR | | <i>E. J. Me Don, Jr.</i> | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | | % CORE RECOV- ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0' | 0' | | | | 1 | 1 | 3.5 in. S |
| 5' | 5' | | | | 2 | | |
| 10' | 10' | | | | 3 | | |
| 15' | 15' | | | | 4 | | |
| 20' | Water depth 17.6' at M.L.W. SP-Tan poorly graded sand | | | | 5 | | |
| 25' | ML - Green & Gray fine sandy silt micaceous slight plasticity | | | | 6 | | |
| 30' | SM - Green & Gray silty fine sand micaceous slight plasticity | | | | 7 | | |
| | | | | | 8 | | |
| | | | | | 9 | | |
| | | | | | 10 | | |
| | | | | | 11 | | |
| | | | | | 12 | | |
| | | | | | 13 | | |
| | | | | | 14 | | |
| | | | | | 15 | | |
| | | | | | 16 | | |
| | | | | | 17 | | |
| | | | | | 18 | | |
| | | | | | 19 | | |
| | | | | | 20 | | |
| | | | | | 21 | | |
| | | | | | 22 | | |
| | | | | | 23 | | |
| | | | | | 24 | | |
| | | | | | 25 | | |
| | | | | | 26 | | |
| | | | | | 27 | | |
| | | | | | 28 | | |
| | | | | | 29 | | |
| | | | | | 30 | | |
| | | | | | 31 | | |
| | | | | | 32 | | |
| | | | | | 33 | | |
| | | | | | 34 | | |
| | | | | | 35 | | |
| | | | | | 36 | | |
| | | | | | 37 | | |
| | | | | | 38 | | |
| | | | | | 39 | | |
| | | | | | 40 | | |
| | | | | | 41 | | |
| | | | | | 42 | | |
| | | | | | 43 | | |
| | | | | | 44 | | |
| | | | | | 45 | | |
| | | | | | 46 | | |
| | | | | | 47 | | |
| | | | | | 48 | | |
| | | | | | 49 | | |
| | | | | | 50 | | |
| | | | | | 51 | | |
| | | | | | 52 | | |
| | | | | | 53 | | |
| | | | | | 54 | | |
| | | | | | 55 | | |
| | | | | | 56 | | |
| | | | | | 57 | | |
| | | | | | 58 | | |
| | | | | | 59 | | |
| | | | | | 60 | | |
| | | | | | 61 | | |
| | | | | | 62 | | |
| | | | | | 63 | | |
| | | | | | 64 | | |
| | | | | | 65 | | |
| | | | | | 66 | | |
| | | | | | 67 | | |
| | | | | | 68 | | |
| | | | | | 69 | | |
| | | | | | 70 | | |
| | | | | | 71 | | |
| | | | | | 72 | | |
| | | | | | 73 | | |
| | | | | | 74 | | |
| | | | | | 75 | | |
| | | | | | 76 | | |
| | | | | | 77 | | |
| | | | | | 78 | | |
| | | | | | 79 | | |
| | | | | | 80 | | |
| | | | | | 81 | | |
| | | | | | 82 | | |
| | | | | | 83 | | |
| | | | | | 84 | | |
| | | | | | 85 | | |
| | | | | | 86 | | |
| | | | | | 87 | | |
| | | | | | 88 | | |
| | | | | | 89 | | |
| | | | | | 90 | | |
| | | | | | 91 | | |
| | | | | | 92 | | |
| | | | | | 93 | | |
| | | | | | 94 | | |
| | | | | | 95 | | |
| | | | | | 96 | | |
| | | | | | 97 | | |
| | | | | | 98 | | |
| | | | | | 99 | | |
| | | | | | 100 | | |

| DRILLING LOG | | DIVISION | INSTALLATION | | | Hole No. CS - 2 |
|--|-------|-----------------|---|-----------------|-------------------|--|
| 1. PROJECT Kings ISLAND | | | 10. SIZE AND TYPE OF BIT 11. DATUM FOR PLYGUMIN (FROM TO MSL.) 11.1 | | | SHEET 2 OF 2 |
| 2. LOCATION (Coordinates or Station) S-10 T-10 | | | 12. MANUFACTURER'S DESIGNATION OF DRILL | | | |
| 3. DRILLING AGENCY Soil Test Inc. | | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN | | | DISTURBED UNDISTURBED |
| 4. HOLE NO. (As shown on drawing title and file number) | | CS-2 | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 5. NAME OF DRILLER MC Donalld | | | 15. ELEVATION GROUND WATER | | | I |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED | | DEG. FROM VERT. | 16. DATE HOLE STARTED 5A.M. 7/73 | | | COMPLETED 11 A.M. 1/73 |
| 7. THICKNESS OF OVERTBURDEN | | | 17. ELEVATION TOP OF HOLE 7.7' S.F. MLL 61 | | | |
| 8. DEPTH DRILLED INTO ROCK | | | 18. TOTAL CORE RECOVERY FOR BORING | | | |
| 9. TOTAL DEPTH OF HOLE 45.0' | | | 19. SIGNATURE OF INSPECTOR | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOVERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 30' | | | | 6 | | 62 |
| 35' | | | ML - Green & Gray fine Sands w/lt micaceous slight plasticity | 7 | | 92 |
| 40' | | | | | | 75 |
| 45' | | | | | | 62 |
| | | | Soils field classified in accordance with the Unified Soil Classification System. | | | 100 |
| | | | | | | 45 |
| | | | | | | 46 |
| | | | | | | 44 |
| | | | | | | 47 |
| | | | | | | 50 |
| | | | | | | 52 |
| | | | | | | BLOWS PER FOOT: Number required to drive 1 1/2" ID splitspoon w/140 lb. hammer falling 30". |

Hole No. CS-3

SHEET NO 2
OF 2 SH

| DRILLING LOG | | DIVISION <i>South ATLANTIC</i> | INSTALLATION <i>Savannah River</i> | | | |
|---|--|-----------------------------------|---|--|---|---|
| 1. PROJECT | King Island TURBINE BASIN 5PC P1/2 | | M. SIZE AND TYPE OF BIT <i>1 1/2"</i> | 11. DATUM FOR ELEVATION SHOWN (T.M. or MSL) <i>191. W</i> | | |
| 2. LOCATION (Coordinates or Station) | | | 12. MANUFACTURER'S DESIGNATION OF DRILL <i>J. G. C. DRILL CO.</i> | | | |
| 3. DRILLING AGENCY | <i>Savannah River D. I. Inc.</i> | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN | DISTURBED <i>6</i> | UNDISTURBED | |
| 4. HOLE NO. (As shown on drawing title and file number) | <i>CS-3</i> | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 5. NAME OF DRILLER | <i>McDonald</i> | | 15. ELEVATION GROUND WATER IN FEET | | | |
| 6. DIRECTION OF HOLE | <input checked="" type="checkbox"/> VERTICAL | <input type="checkbox"/> INCLINED | DEG. FROM VERT. | 16. DATE HOLE | STARTED <i>19 Nov. 173</i> COMPLETED <i>19 Nov. 173</i> | |
| 7. THICKNESS OF OVERTBURDEN | | | 17. ELEVATION TOP OF HOLE 0.0 ft N.E. W | | | |
| 8. DEPTH DRILLED INTO ROCK | | | 18. TOTAL CORE RECOVERY FOR BORING | | | |
| 9. TOTAL DEPTH OF HOLE | <i>141. 5'</i> | | 19. SIGNATURE OF INSPECTOR <i>John P. McDonald</i> | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOVERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 55' | | | | | | 65 |
| 57' | | | | | | 57 |
| 59' | | | | | | 60 |
| 61' | | | | | | - |
| 63' | | | | | | - |
| 65' | | | | | | 73 |
| 67' | | | | | | 70 |
| 69' | | | | | | 65 |
| 71' | | | | | | 67 |
| 73' | | | | | | - |
| 75' | | | | | | - |
| 77' | | | | | | - |
| 79' | | | | | | - |
| 81' | | | | | | - |
| 83' | | | | | | - |
| 85' | | | <i>SM - Gray & Green Silty fine sand micaceous slight plasticity when wet</i> | | | - |
| 87' | | | <i>Cut out to steep with fish tail</i> | | 5 | - |
| 89' | | | <i>SM - Gray & Green Silty fine sand micaceous</i> | | 6 | 100/0.95 |
| 91' | | | <i>Soil field classified in accordance with the Unified Soil Classification System.</i> | | | <u>BLOWS PER FOOT:</u> Number required to drive 1 1/2" ID split spoon w/140 lb hammer falling 30". |

Hole No. CS-4

| | | | | | |
|--|-------|--|--|---|---|
| DRILLING LOG | | DIVISION South ATLANTIC | INSTALLATION SAVANNAH RIVER HARBOR | SHEET 1 OF 2 SHEETS | |
| 1. PROJECT | | 10. SIZE AND TYPE OF BIT | | | |
| KINGS ISLAND TURNING BASIN | | 11. DATUM FOR ELEVATION SHOWN (TBM OR MSL) | | | |
| 2. LOCATION (Coordinate or Station) | | 12. MANUFACTURER'S DESIGNATION OF DRILL | | | |
| 75° 19.87N 75° 25' ± 07.4' HEEL | | FALCON 314 | | | |
| 3. DRILLING AGENCY | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN | | | |
| Savannah District | | DISTURBED UNDISTURBED | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | 7 0 | | | |
| 5. NAME OF DRILLER | | 14. TOTAL NUMBER CORE BOXES | | | |
| J. McDonald | | 15. ELEVATION GROUND WATER | | | |
| 6. DIRECTION OF HOLE | | 16. DATE HOLE STARTED COMPLETED | | | |
| <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 22 APRIL 1973 22 APRIL 1973 | | | |
| 7. THICKNESS OF OVERTBURDEN | | 17. ELEVATION TOP OF HOLE 0.0 MLW | | | |
| 8. DEPTH DRILLED INTO ROCK | | 18. TOTAL CORE RECOVERY FOR BORING % | | | |
| 9. TOTAL DEPTH OF HOLE 46.0' ELLIN MLW | | 19. SIGNATURE OF INSPECTOR | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOVERY BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | 0 | | | | 8. BLOWS |
| | 5 | | SM - TAN SILTY FINE & MEDIUM SAND | 1 | 18 |
| | 10 | | | 2 | 10 |
| | 15 | | | 3 | 12 |
| | 20 | | | 4 | 18 |
| | 25 | | SP SM - TAN POORLY GRADED SAND | 5 | 17 |
| | 30 | | — CONTINUED ON SHEET NO 2 | 6 | 19 |
| | | | | | 16 |
| | | | | | 20 |
| | | | | | 21 |
| | | | | | 22 |
| | | | | | 35 |
| | | | | | 30 |
| | | | | | 34 |
| | | | | | 26 |
| | | | | | 29 |
| | | | | | 36 |
| | | | | | 21 |
| | | | | | 12 |

DRILLING LOG (Cont Sheet)

FAIRION TOP OF HOME

2.3 BELOW

Hole No.

C5-4

MEET 2
W 2 SINFIS

| ELEVATION a | DEPTH b | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV. ERY e | BOX OR SAMPLE NO. f | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | |
|----------------|------------|-------------|---|------------------------------|------------------------------|--|--|
| | | | | | | R | BLOWS |
| | | | CH - GRAY FAT CLAY SLIGHTLY MICACEOUS | | | | 51 |
| 35 | | | | | | | 49 |
| | | | | | | | 41 |
| | | | | | | | 68 |
| | | | | | | | 61 |
| | | | | | | | 59 |
| 40 | | | SP, SM - GREEN POORLY GRADED SAND | | 7 | | 71 |
| | | | | | | | 72 |
| | | | | | | | 68 |
| 45 | | | | | | | 59 |
| <i>-46.3</i> | | | NOTE: Soils field classified in accordance with the Unified Soil Classification System. | | | | <u>BLOWS PER FOOT:</u> Number required to drive 1 $\frac{1}{2}$ " ID splitspoon w/140 lb. hammer falling 30". |

| | | | | | |
|--------------|-------|--|--|---|------------------------|
| DRILLING LOG | | DIVISION SOUTH ATLANTIC | LOCATION 1. PROJECT KINGS ISLAND TURNING BASIN 2. LOCATION (Coordinates or Station) TD. 100+250 AT WATERS EDGE | INVESTIGATION 1. PLANNED SAVANNAH HARBOR | SHEET 1 OF 2 SHEETS |
| | | | 3. DRILLING AGENCY SAVANNAH DISTRICT | 4. SIZE AND TYPE OF BIT 1 1/2" 10 SPLIT SPOON | |
| | | | 5. LATITUDE AND LONGITUDE CS 5 | 6. DATUM FOR ELEVATION SHOWN (M.L.W., M.S.L., etc.) M.L.W. | |
| | | | 7. NAME OF DRILLER J. MC DONALD | 8. MANUFACTURER'S DESIGNATION OF DRILL FAILING 514 | |
| | | | 9. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN 2 | 10. DISTURBED 11. UNDISTURBED 0 | |
| | | | 12. TOTAL NUMBER CORE BOXES 1 | 13. ELEVATION GROUND WATER 0.0 M.L.W. | |
| | | | 14. DATE HOLE STARTED 26 APRIL 1973 | 15. DATE HOLE COMPLETED 26 APRIL 1973 | |
| | | | 16. ELEVATION TOP OF HOLE 0.0 M.L.W. | 17. TOTAL CORE RECOVERY FOR BORING 100% | |
| | | | 18. SIGNATURE OF INSPECTOR Charles D. Griffin | 19. REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) 1 BLOWS | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS: (Description) | | |
| | | | % CORE RECOVERY | BOX OR SAMPLE NO. | REMARKS |
| 0 | WATER | WATER DEPTH 1.5 AT M.L.W. | | | |
| 5 | | ML - GRAY INORGANIC SILT | 100 | FOR | |
| 10 | | | 100 | ONLY | |
| 15 | | | | | |
| 20 | | | | | |
| 25 | | SM - TAN & GRAY SILTY FINE MEDIUM SAND | 2 | | |
| 30 | | CONTINUED ON SHEET NO 2 | | | |

DRILLING LOG (Cont Sheet)

FROM TOP OF HOLE

PROJECT

KINGS ISLAND TURNING POINT

INSTALLATION

SILVANIAN CLEP 11/14/70

Hole No.

CS 5

SHEET 2

OF 2 SHEETS

| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water level, depth of weathering, etc., if significant) | R BLOWS |
|-----------|-------|--------|--|-------------------------|-------------------------|---|---------|
| 30 | 30 | c | CL - GREEN & GRAY SILTY SANDY CLAY | d | 3 | | 9 |
| 35 | 35 | | SP SM. GREEN POORLY GRADED STIFF SAND | | 4 | | 11 |
| 40 | 40 | | | | | | 21 |
| 45 | 45 | | | | | | 19 |
| | | | | | | | 20 |
| | | | | | | | 30 |
| | | | | | | | 34 |
| | | | | | | | 36 |
| | | | | | | | 46 |
| | | | | | | | 49 |

NOTE: Soils field classified
in accordance with the Unified
Soil Classification System.

BLOWS PER FOOT:

Number required to drive
1½" ID splitspoon w/140 lb.
hammer falling 30".

| | | | | |
|---|--|---|--|--|
| DRILLING LOG | | DIVISION SOUT ATLANTIC | INSTALLATION SAVANNAH RIVER HARBOR | Hole No. C S - 6 SHEET 1 OF 2 SHEETS |
| PROJECT KNOX ISLAND TURNING BASIN | | LOCATION (Coordinates or Station) NORTH 50' OF BN 14 | 10. SIZE AND TYPE OF BIT $1\frac{3}{8}''$ TD SPLIT SPOON | |
| DRILLING AGENCY CAVANNAH DISTRICT | | 11. DATUM FOR ELEVATION SHOWN (FATHOMS OR FEET) | MLW | |
| HOLE NO. (As shown on drawing, file and file number) CS 6 | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | |
| NAME OF DRILLER L. MC DONALD | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN | DISTURBED 4 | UNDISTURBED 0 |
| DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 14. TOTAL NUMBER CORE BOXES | | |
| THICKNESS OF OVERTURDEN | | 15. ELEVATION GROUND WATER | | |
| DEPTH DRILLED INTO ROCK | | 16. DATE HOLE STARTED 27 APRIL 1973 | COMPLETED 27 APRIL 1973 | |
| TOTAL DEPTH OF HOLE 29.8' BELOW MLW | | 17. ELEVATION TOP OF HOLE 0.0' MLW | | |
| ELEVATION DEPTH LEGEND | | 18. TOTAL CORE RECOVERY FOR BORING | | |
| (Description) | | 19. SIGNATURE OF INSPECTOR Charles D. Griffin | REMARKS (Drilling time, motor load, depth of weathering, etc., if significant) FLOWS | |
| 5 | | WATER | | |
| 10 | | | | |
| 15 | | | | |
| 20 | | WATER DEPTH 16.5 AT MLW | | |
| 25 | | ML - GRAY INORGANIC SILT W/SILTY SAND LAYERS | | |
| 30 | | CH - GRAY FAT CLAY W/GRAVEL | | |
| | | CONTINUED ON SHEET No. | | |

DRILLING LOG (Cont. Sheet)

TION TOP OF HOLE

16.5' BELOW ML.

Hole No.

CS 6

PROJECT

KINGS ISLAND TURNING BASIN

INSTALLATION

SAVANNAH RIVER HARBOR

SHEET 2 OF 2 SHEETS

ELEVATION

DEPTH

LEGEND

CLASSIFICATION OF MATERIALS
(Description)% CORE
RECOV.
ERY
eBOX OR
SAMPLE
NO.
fREMARKS
(Drilling time, water loss, depth of
weathering, etc., if significant)

8 BLOWS

30

SM - GRAY SILTY FINE
MEDIUM SAND

35

GREEN, SLIGHTLY
MICACEOUS

40

45

46.5

NOTE: Soils field classified
in accordance with the Unified
Soil Classification System.BLOWS PER FOOTNumber required to drive
1 $\frac{1}{2}$ " ID splitspoon w/140 lb
hammer falling 30".

| DRILLING LOG | | DIVISION <u>SOUL ATLANTIC</u> | INSTALLATION <u>SEAVANNAH RD ? HARBOR</u> | Hole No. <u>C 5 - 7</u> |
|--|-------|---|--|---|
| 1. PROJECT <u>KINGS ISLAND TURNING BASIN</u> | | 10. SIZE AND TYPE OF BIT <u>1 1/8" 10 SPLIT SPOON</u> | | |
| 2. LOCATION (Coordinates or Station) SEE PLAN | | 11. DATUM FOR ELEVATION SHOWN (TBM OR TLL) | | |
| OPPOSITE STA. 924500 AT WATERS EDGE | | MLW | | |
| 3. DRILLING AGENCY <u>SEAVANNAH DISTRICT</u> | | 12. MANUFACTURER'S DESIGNATION OF DRILL <u>ERLING 314</u> | | |
| 4. HOLE NO. (As shown on drawing 1100) and 1110 planned <u>CS 7</u> | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN <u>5</u> DISTURBED UNDISTURBED <u>0</u> | | |
| 5. NAME OF DRILLER <u>A. McDonald</u> | | 14. TOTAL NUMBER CORE BOXES | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER | | |
| 7. THICKNESS OF OVERTBURDEN | | 16. DATE HOLE STARTED <u>27 APRIL 1973</u> COMPLETED <u>27 APRIL 1973</u> | | |
| 8. DEPTH DRILLED INTO ROCK | | 17. ELEVATION TOP OF HOLE 0.0' MLW | | |
| 9. TOTAL DEPTH OF HOLE <u>25.5' BELOW MLW</u> | | 18. TOTAL CORE RECOVERY FOR BORING | | |
| | | 19. SIGNATURE OF INSPECTOR <u>Charles J. Griffin</u> | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | REMARKS (Drilling time, Major loss, depth of weathering, etc., if significant) |
| -0.8 | | | WATER DEPTH 0.8' AT MLW | |
| 5 | | | ML - GRAY INORGANIC SILT W/SILTY SAND LAYERS | |
| 10 | | | | |
| 15 | | | CH - GRAY FAT CLAY W/GRAVEL | |
| 20 | | | SM - GRAY SILTY FINE MEDIUM SAND | |
| 25 | | | | |
| 30 | | | GREEN, SLIGHTLY MICACEOUS | CONTINUED ON SHEET NO 2 |

DRILLING LOG (Cont Sheet)

TION TOP OF HOLE

PROJECT
KINGS ISLAND TURNING BASIN

O. B. 4' FLOW MIL.

INSTALLATION

SAVANNAH RIVER HARBOR

Hole No. CS 7

SHEET 2
OF 2 SHEETS

| EL E V A T I O N | D E P T H | L E G E N D | C L A S S I F I C A T I O N O F M A T E R I A L S (Description) | % C O R E R E C O V- E R Y | B O X O R S A M P L E N O. | R E M A R K S (Drilling time, water loss, depth of weathering, etc., if significant) |
|------------------|-----------|-------------|---|----------------------------------|----------------------------------|--|
| | 36 | | | | | 8 BLOWS |
| | 35 | | SAND, GREEN, SILTY, FINE SAND, SLIGHTLY MICACEOUS | | | 51 |
| | 35 | | | | | 54 |
| | 36 | | | | | 62 |
| | 37 | | | | | 64 |
| | 38 | | | | | 59 |
| | 39 | | | | | 61 |
| | 40 | | | | | 62 |
| | 41 | | | | | 60 |
| | 42 | | | | | 58 |
| 45.5 | 45 | | NOTE: Soils field classified in accordance with the Unified Soil Classification System. | | 5 | 51 |
| | | | | | | BLOWS PER FOOT |
| | | | | | | Number required to drive 1 1/8" ID splitspoon w/140 lb hammer falling 30". |

| DRILLING LOG | | | DIVISION Scd II, Atlantic | INSTALLATION S. U. S. A. - Vol. | Hole No. CS-8 | SHEET, / OF 2 SHEETS |
|--|-------|--------|---|------------------------------------|-------------------------|--|
| 1. PROJECT Kings Tidal Tunnels | | | 10. SIZE AND TYPE OF BIT / 5 1/2" I.D. 5 1/2" TSPOR | | | |
| 2. LOCATION (Coordinates or Station) OPPOSITE SD. 99+330 OPPOX. 140' FROM WATER'S EDGE | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY Divisional Drilling Service | | | 12. MANUFACTURER'S DESIGNATION OF DRILL 214 Foot 1/2" | | | |
| 4. HOLE NO. (As shown on drawing file) CS-8 and file number | | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN DISTURBED 4 UNDISTURBED | | | |
| 5. NAME OF DRILLER McDonald | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | 15. ELEVATION GROUND WATER Boiling In River | | | |
| 7. THICKNESS OF OVERTBURDEN | | | 16. DATE HOLE STARTED 30 April 73 COMPLETED 1 May 73 | | | |
| 8. DEPTH DRILLED INTO ROCK | | | 17. ELEVATION TOP OF HOLE | | | |
| 9. TOTAL DEPTH OF HOLE 35.0' | | | 18. TOTAL CORE RECOVERY FOR BORING | | | |
| 10. ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | 19. CORE RECOVERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0' | 5' | | | | | |
| 10' | 15' | | | | | |
| 20' | 25' | | Water | | | |
| 30' | 35.0' | | Depth at MLW, 30.0' | | | |

| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION S. Atlantic | Hole No. C-5-8 ET 2 OF 2 SHEETS | |
|--|--------------|--|---|--|---|
| 1. PROJECT Kings Tidwell Transition Basin, | | 10. SIZE AND TYPE OF BIT 1 1/4" ID 50.45000 | | | |
| 2. LOCATION (Coordinates or Station) See Plan | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) N.W. | | | |
| 3. DRILLING AGENCY St. Johns Dist. L. F. | | 12. MANUFACTURER'S DESIGNATION OF DRILL 314 Fan. 1.00 | | | |
| 4. HOLE NO. (As shown on drawing) 10 and file number CG-B | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 4 UNDISTURBED | | | |
| 5. NAME OF DRILLER McDonald | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER Boring II River | | | |
| 7. THICKNESS OF OVERBURDEN | | 16. DATE HOLE STARTED 30 Apr. 173 COMPLETED 1 May 73 | | | |
| 8. DEPTH DRILLED INTO ROCK | | 17. ELEVATION TOP OF HOLE | | | |
| 9. TOTAL DEPTH OF HOLE 45.0' | | 18. TOTAL CORE RECOVERY FOR BORING | | | |
| ELEVATION 30' | DEPTH 30' | LEGEND • • • | CLASSIFICATION OF MATERIALS (Description) SM - Gray silty sand with layers dark gray OH | 1. CORE RECOVERY Box or Sample No. 1 | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) NX Casing set at 33.4' advanced to 37.9' |
| 35' | 35' | • • | SP - Gray poorly graded sand | 2 | 14' 24' 30' 35' 50' 48' 53' 58' 52' |
| 40' | 40' | • • • | SM - Green silty fine sand. Micaceous slight plasticity. White, Wet | 3 | |
| 45' | 45' | • | Soils field classified in accordance with the Unified Soil Classification System. | 4 | BLOWS PER FOOT: Number required to drive 1 1/4" ID splitspoon w/140 lb hammer falling 30". |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | INSTALLATION Savannah River | SHEET 1 OF 2 SHEETS |
|--|-------|--|--|---|
| 1. PROJECT Kings Ferry Nuclear Power Plant | | 10. SIZE AND TYPE OF BIT 1 3/8" I.D. Split spoon | | |
| 2. LOCATION (Coordinates or Station) OPPOSITE SD. 994000 APPROX. 25' FROM WATER'S EDGE | | 11. DATUM FOR ELEVATION SHOWN (TBM = MSL) MLW | | |
| 3. DRILLING AGENCY Savannah District Office | | 12. MANUFACTURER'S DESIGNATION OF DRILL R-1 F-100 | | |
| 4. HOLE NO. (As shown on drawing sheet and file number) CS-9 | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN 6 | | |
| 5. NAME OF DRILLER McDonald | | 14. TOTAL NUMBER CORE BOXES 0 | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. EXCAVATION-GROUND WATER Boring In River | | |
| 7. THICKNESS OF OVERTURDEN | | 16. DATE HOLE STARTED 2 May 73 COMPLETED 2 May 73 | | |
| 8. DEPTH DRILLED INTO ROCK | | 17. ELEVATION TOP OF HOLE | | |
| 9. TOTAL DEPTH OF HOLE 25.4' | | 18. TOTAL CORE RECOVERY FOR BORING | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | 0' | | | |
| | 5' | | | |
| | 10' | | Water | |
| | 15' | | | |
| | 20' | | Water depth 20.2' MLW | |
| | 25' | | MH-Green elastic silt | NX Casing 15' at 25.4' |
| | 30' | | SP- Gray poorly graded sand | Advanced NX Casing to 29.9' |

| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah River | FILE NO. CS-9 | SHEET 2 OF 2 SHEETS | |
|---|-------------|--|---|--------------------|------------------------|---|
| 1. PROJECT: Kings Island Testing Basis | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " ID Split spoon | | | | |
| 2. LOCATION (Coordinates or Station) D. 137 | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | | |
| 3. DRILLING AGENCY | | 12. MANUFACTURER'S DESIGNATION OF DRILL E&L Equipment | | | | |
| 4. HOLE NO. (As shown on drawing) CS-9 | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN 6 DISTURBED UNDISTURBED | | | | |
| 5. NAME OF DRILLER McDonald | | 14. TOTAL NUMBER CORE BOXES 0 | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL. <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER Boring In River | | | | |
| 7. THICKNESS OF OVERBURDEN | | 16. DATE HOLE STARTED 2 May, 73 COMPLETED 2 May, 73 | | | | |
| 8. DEPTH DRILLED INTO ROCK | | 17. ELEVATION TOP OF HOLE | | | | |
| 9. TOTAL DEPTH OF HOLE 45.4' | | 18. TOTAL CORE RECOVERY FOR BORING | | | | |
| ELEVATION 306 | DEPTH 35 | LEGEND Soil field classified in accordance with the Unified Soil Classification System. | CLASSIFICATION OF MATERIALS (Description) | CORE RECOVERY % | BOX OR SAMPLE NO. 3 | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) Boring |
| | 35 | | SM - Gray silty fine sand micaceous 30.4 - 34.9' | 28 | | |
| | 40 | | Gray silty fine & medium sand 34.9 - 37.9' Green silty fine sand micaceous | 29 | 4 | Advanced 4X Casing to 35.7' 35.7' 35.40 |
| | 45 | | 37.9 - 45.4' | 38 | 5 | 35.7' 35.40 35.40 |
| | | | | 50 | 6 | 35.40 35.40 35.40 |
| | | | | 60 | | 35.40 35.40 35.40 |
| | | | | 60 | | 35.40 35.40 35.40 |
| | | | | 72 | | 35.40 35.40 35.40 |
| | | | | 83 | | 35.40 35.40 35.40 |
| | | | | | | BLOWS PER FOOT: Hammer required to drive 13" ID split spoon w/140 lb. hammer falling 50" |

| DRILLING LOG | | DIVISION <i>South Atlantic</i> | INSTALLATION <i>Savannah River</i> | | SHEET 1 OF 2 SHEETS | |
|--|-------|---|---|------------------------------|------------------------|---|
| PROJECT <i>Kings Island Tanning Basin</i> | | LOCATION (Coordinates or Station) <i>OPPOSITE SYD. 1001500</i> | 10. SIZE AND TYPE OF BIT <i>1 1/8" ID Sol. t 3000c</i> | | | |
| | | CORPOR. <i>COPPER. 270' FROM WATER'S EDGE</i> | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) <i>M.L.W.</i> | | | |
| TILLING AGENCY <i>Savannah District</i> | | 12. MANUFACTURER'S DESIGNATION OF DRILL <i>314- Failing</i> | | | | |
| 4. HOLE NO. (As shown on drawing file and file number) <i>CS-10</i> | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN <i>7</i> | | DISTURBED | UNDISTURBED | |
| 5. NAME OF DRILLER <i>McDonald</i> | | 14. TOTAL NUMBER CORE BOXES <i>0</i> | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER <i>Boring In River</i> | | | | |
| 7. THICKNESS OF OVERTBURDEN | | 16. DATE HOLE STARTED <i>3 May 73</i> | | COMPLETED <i>7 May 73</i> | | |
| 8. DEPTH DRILLED INTO ROCK | | 17. ELEVATION TOP OF HOLE | | | | |
| 9. TOTAL DEPTH OF HOLE 45.7' | | 18. TOTAL CORE RECOVERY FOR BORING | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | CORE RECOVERY. | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0' | 0' | | | | | <i>Balls</i> |
| 5' | 5' | | Water | F | | |
| 10' | 10' | | | | | |
| 15' | 15' | | Water depth 11.9' MLW | | | |
| 20' | 20' | | MH-Green elastic silt | | | NX Casing set at 14.8' |
| 25' | 25' | | SM-Gray silty fine & medium sand micaceous w/occasional small gravel 13.4'-17.9' 17.9'-45.7' Gray & Green silty fine sand micaceous | 3 | 2 | NX Casing advanced to 19.9' |
| 30' | 30' | | | 4 | | 45' 52' 49' 55' 58' 56' |

| DRILLING LOG | | DIVISION SOUL Atlantic | INSTALLATION 100 ft. above River | HOLE NO. L3-10 |
|---|--|---|--|---------------------------|
| 1. PROJECT Kings Island Towing Basin | 2. LOCATION (Coordinates or Station) 200 P/47 | 10. SIZE AND TYPE OF BIT 1 3/8" ID SPLIT SPOON | 11. DATUM FOR ELEVATION SHOWN (TBM = MSL) | 1. SHEET 2 OF 2 SHEETS |
| 3. DRILLING AGENCY Savannah District | 4. HOLE NO. (As shown on draw to hole 1 and 110 numbered) CS-10 | 12. MANUFACTURER'S DESIGNATION OF DRILL 314 Fac. 1, no. | | |
| 5. NAME OF DRILLER McDonald | 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN | DISTURBED | UNDISTURBED |
| 7. THICKNESS OF OVERTBURDEN | 8. DEPTH DRILLED INTO ROCK | 14. TOTAL NUMBER CORE BOXES | 0 | |
| 9. TOTAL DEPTH OF HOLE 45.7' | | 15. ELEVATION GROUND/WATER Boring In River | STARTED 3 May 73 | COMPLETED 7 May 73 |
| 10. ELEVATION DEPTH LEGEND | 11. CLASSIFICATION OF MATERIALS (Description) | 16. DATE HOLE | | |
| 30' | SM - Gray & Green Silty fine sand Micaceous | 17. ELEVATION TOP OF HOLE | | |
| 35' | | 18. TOTAL CORE RECOVERY FOR BORING | | |
| 40' | | 19. SIGNATURE OF INSPECTOR Elvin J. McIlroy | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) Blows | |
| 45' | Soils field classified in accordance with the Unified Soil Classification System. | 20. BLOWS PER FOOT Number required to drive 1 3/8" ID split spoon w/140 lb. hammer falling 30" | 55 56 59 ONLY 90 80 | |

SAVANNAH HARBOR BORING LOGS

From Station 97+750

To

Station 103+000

| DRILLING LOG | | | DIV | INSTALLED | | Hole No. | |
|---|-------|--------|--|-----------------|------------------------|---|--|
| | | | 4 | Savannah, Ga. | | 1 | |
| 1. PROJECT Savannah Harbor Widening and Deepening, Phase 2 | | | 10. SIZE AND TYPE OF PIT 1-3/8" Splitspoon, R | | SHEET 1 OF 2 SHEETS | | |
| 2. LOCATION (Coordinates of Station) | | | 11. DATUM FOR ELEVATION SHOWN (TMM or MSL) Core Bit (ML) | | | | |
| See Plan | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 C.D. #8 | | | | |
| 3. DRILLING AGENCY Savannah District | | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN DISTURBED 1 UNDISTURBED 0 | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) 1 | | | 14. TOTAL NUMBER CORE BOXES 2 | | | | |
| 5. NAME OF DRILLER Cremer | | | 15. ELEVATION GROUND WATER 0.0' - Tidal | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | 16. DATE HOLE STARTED 19 Mar 69 COMPLETED 20 Mar 69 | | | | |
| 7. THICKNESS OF OVERBURDEN | | | 17. ELEVATION TOP OF HOLE -14.3' | | | | |
| 8. DEPTH DRILLED INTO ROCK | | | 18. TOTAL CORE RECOVERY FOR BORING 58 % | | | | |
| 9. TOTAL DEPTH OF HOLE 45.5' | | | 19. SIGNATURE OF INSPECTOR Allan Merritt, Robert L. Siesen, Geologist | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOVERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | |
| | b | c | d | e | f | g | |
| | | | Water | | | No Sample obtained of OL materials, stratum very thin | |
| 5 | | | Very thin, very soft, layer of OL-organic silt above sand | | | | |
| 10 | | | | | | | |
| -14.3' | | | | | | | |
| 15 | | | SM-Gray, very fine grained, silty sand | | Jar 1 | 14.3' to 16.5' Washed out while setting casing | |
| 20 | | | ML-Greenish gray, clayey to sandy silt, moderate resistance to knife blade penetration from 18.0' to 24.5' | 100 | | Splitspoon 16.5' to 13.0' 4" Casing set to 18.5' Pull #1, 18.0' to 19.5' Run 1.5', Rec 1.5' | |
| 25 | | | | 86 | | Pull #2, 19.5' to 24.5' Run 5.0', Rec 4.3' CI 0.7' | |
| 30 | | | SM-Gray, silty, very fine grained sand, moderate resistance to knife blade penetration from 24.5' to 29.5' | 40 | | Pull #3, 24.5' to 29.5' Run 5.0', Rec 2.0' CI 3.0' | |
| 36 | | | Continued on Sheet #2 - | | | | |
| (Revised by Amendment No. 0001) | | | | | | | |

DRILLING LOG (Cont Sheet)

"VALION TOP OF HOLE

-14.3°

Hole No.

1

**Project Savannah Harbor
Widening and Deepening, Phase 2**

INSTALLATION

Savannah, Ga.

SHEET 2
OF 2 SHEETS

| ELEVATION | DEPTH. | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
|-----------|--------|--------|---|-------------------------|-------------------------|--|
| | | | SM-Tan, very fine grained, silty sand, slight resistance to knife blade penetration from 39.5' to 41.6' | 24 | i | Pull #4, 29.5' to 34.5' Run 5.0', Rec 1.2' C1 3.8' |
| 35 | | | | 44 | | Pull #5, 34.5' to 38.8' Run 4.3', Rec 1.9' C1 2.4' |
| 40 | | | | 72 | | Pull #6, 38.8' to 41.6' Run 2.8', Rec 2.0' C1 0.8' |
| 45 | | | Compaction shale, gray, sandy, moderate resistance to knife blade penetration BOTTOM OF HOLE 45.5' | 88 | | Pull #7, 41.6' to 45.5' Run 3.9', Rec 3.1' C1 0.8' |
| | | | Soils field classified in accordance with the Unified Soil Classification System. | | | Used 150 to 250 lbs pressure while coring |
| | | | | | | ONLY |

| DRILLING LOG | | | DIVISION | INSTALLATION | | | HOLE NO. | SHEET | |
|---|--|--|--|--------------|--|--|---------------|-------------------|---|
| | | | South Atlantic | Savannah | | | 2 | 1 OF 2 SHEETS | |
| 1. PROJECT | | | Savannah Harbor Widening and Deepening, Phase 2 | | | 10. SIZE AND TYPE OF PIT 1-3/8" Splitspoon, R | | | |
| 2. LOCATION (Coordinates or Section) | | | See Plan | | | 11. DATUM FOR ELEVATION SHOWN (TIME or MSL) Core Bit | | | |
| 3. DRILLING AGENCY | | | Savannah District | | | M.L.W. | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | | 2 | | | 12. MANUFACTURER'S DESIGNATION OF DRILL | | | |
| 5. NAME OF DRILLER | | | King | | | Falling 314 C.D.-78 | | | |
| 6. DIRECTION OF HOLE | | | <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | 13. TOTAL NO. OF OVER DISTURBED UNDISTURBED | | | |
| 7. THICKNESS OF OVERTBURDEN | | | | | | BURDEN SAMPLES TAKEN 1 Jar 0 | | | |
| 8. DEPTH DRILLED INTO ROCK | | | | | | 14. TOTAL NUMBER CORE BOXES 2 | | | |
| 9. TOTAL DEPTH OF HOLE | | | 46.2' | | | 15. ELEVATION GROUND WATER 0.0 - Tidal | | | |
| ELEVATION | | | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (DESCRIPTION) | | CORE RECOVERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| ft. | | | ft. | | | | | | |
| 5 | | | | | Water, very thin layer, very soft UL-organic silt above sand | | | | Casing drilled in 2.0' |
| 10 | | | | | | | | | ONLY |
| -14.0 | | | 15 | | SP-Tan-gray, very fine sand, slightly silty | | Jar 1 | | Splitspoon 14.0' to 15.5' |
| | | | 20 | | Stl-Gray, silty, very fine grained to medium grained sand, micaceous, with thin layers of ML-sandy silt, moderate resistance to blade penetration from 15.5 to 19.0' | | 71 | | Pull #1, 15.5' to 19.0' Run 3.5', Rec 2.5' C1 1.0' |
| | | | 25 | | Siltstone, moderate resistance to knife blade penetration from 19.0' to 31.0' | | 90 | | Pull #2, 19.0' to 24.0' Run 5.0', Rec 4.5' C1 0.5' |
| | | | 30 | | | | 43 | | Pull #3, 24.0' to 31.0' Run 7.0', Rec 3.0' C1 4.0' |
| - - - - - Continued on Sheet #2 - - - - - | | | | | | | | | |
| (Revised by Amendment No. 0001) | | | | | | | | | |

DRILLING LOG (Cont Sheet) ELEVATION TOP OF HOLE

-14.0°

Hole No.

2

INSTALLATION

Savannah, Ga.

SHEET 2 OF 2 SHEETS

| | | | | | | |
|---|-------|--------|--|---------------|-------------------|---|
| PROJECT Savannah Harbor Widening and Deepening, Phase 2 | | | LOCATION Savannah, GA. | | HOLE NO. 3 | SHEET 1 OF 2 SHEET |
| LOCATION (Coordinates or Station) See Plan | | | 10. SIZE AND TYPE OF PIT 1-3/8" Splitspoon/R Core Bit | | | |
| 3. DRILLING AGENCY Savannah District | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) NLW | | | |
| 4. HOLE NO. (As shown on drawing title- and file number) 3 | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 C.D. #8 | | | |
| 3. NAME OF DRILLER Creamer | | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN DISTURBED 1 Jar UNDISTURBED 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | 14. TOTAL NUMBER CORE BOXES 2 | | | |
| 7. THICKNESS OF OVERTBURDEN | | | 15. ELEVATION GROUND WATER 0.0 - Tidal | | | |
| 8. DEPTH DRILLED INTO ROCK | | | 16. DATE HOLE STARTED 24 Mar 69 COMPLETED 24 Mar 69 | | | |
| 9. TOTAL DEPTH OF HOLE 46.4' | | | 17. ELEVATION TOP OF HOLE -13.5' | | | |
| | | | 18. TOTAL CORE RECOVERY FOR BORING 60 % | | | |
| | | | 19. SIGNATURE OF INSPECTOR Allen Merritt, Robert L. Siezen, Geologist | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | CORE RECOVERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | b | c | Water | | | |
| | 5 | | OL-Very thin soft layer organic silt above sand | | | |
| | 10 | | | | | |
| -13.5' | 15 | | SM-Tan, gray, silty, fine grained sand | | Jar 1 | Splitspoon from 13.5' to 19.5' |
| | 20 | | Fine grained to medium grained, slightly clayey, slight to moderate resistance to knife penetration from 19.5' to 24.5' | 80 | | Used from 150 to 200 lbs pressure to core. |
| | 25 | | SM-Tan to gray, slightly silty, very fine grained sand with few thin layers of SM sand, generally slight resistance to knife blade penetration from 24.5' to 37.6' | 68 | | Pull #1, 19.5' to 24.5' Run 5.0', Rec 4.0' Cl 1.0' |
| | 30 | | - - - - Continued on Sheet #2 - - - | | | |

(Revised by Amendment No. 0001)

DRILLING LOG (Cont Sheet)

EL E V A T I O N T O P O F H O L E

-13.5°

Hole No.

5

**WORKS Savannah Harbor
Widening and Deepening, Phase 2**

INSTALLATION

Savannah, Ga.

SHEET 2
OF 2 SHEETS

| DRILLING LOG | | DIVISION | INSTALLATION | | Hole No. |
|--|-------|----------------|---|------------------------|--------------------------------------|
| I. PROJECT SAVANNAH HARBOR | | SOUTH ATLANTIC | SAVANNAH R. C. GR. | | SH-12 |
| LOCATION (Coordinates or Section) <i>KINGS ISLAND TURNING BASIN</i> | | | 10. SIZE AND TYPE OF BIT 1 1/2" ID SPLITSPOON | | Sheet/ OF 2 SHEETS |
| TE PLAN LLING AGENCY | | | 11. DATUM FOR ELEVATION SHOWN | | |
| SAVANNAH DISTRICT | | | 12. MANUFACTURER'S DESIGNATION OF DRILL CMF 75 | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-12 | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED 5 UNDISTURBED 0 |
| 5. NAME OF DRILLER <i>T. W. Scott</i> | | | 14. TOTAL NUMBER CORE BOXES | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | 15. ELEVATION GROUND WATER | | |
| 7. THICKNESS OF OVERTURDEN 55.0' | | | 16. DATE HOLE 14 FEB. 1978 | | STARTED COMPLETED 14 FEB. 1978 |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | 17. ELEVATION TOP OF HOLE 0.0' MSLW | | |
| 9. TOTAL DEPTH OF HOLE -55.0' MSLW | | | 18. TOTAL CORE RECOVERY FOR BORING | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (DESCRIPTION) | SCORE RECOV- ERY | BOX OR SAMPLE NO. |
| 0.0 MSLW | 0' | * | | * | 1 |
| -2.5 | | | WATER | | |
| | | | BOTTOM OF RIVER -2.5' MSLW | JAR | BLOWS |
| | 5' | | MH - GREENISH Gray SOFT CLAYEY SILT | | 0 |
| | 10' | | | | 0 |
| | 15' | | | | 0 |
| | -17.5 | | | | 0 |
| | 20' | | | | 0 |
| | 25' | | | | 0 |
| | 30.0 | | | | 0 |
| CONTINUED ON SHEET 2 | | | | | |
| NOTE: Soils field classified in accordance with the Unified Soil Classification System. | | | | | |
| BLOWS PER FOOT: Number required to drive 1 1/2" ID splitspoon w/140 lb. hammer falling 30". | | | | | |


| DRILLING LOG (Cont Sheet) | | | " 100' OF DEEP | 0.0 MSLW | Hole No. 511-12 | |
|---------------------------|--|--------|--|-------------------------|-------------------------|---|
| PROJECT | SAVANNAH RIVER Kings Island Turbine Basin | | INSTALLATION | SAVANNAH RIVER, GA. | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (USCSymbols) | % CORE RECOV. ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water level, depth of weathering, etc., if significant) |
| | 30' | C | | | 1A | BLOWS |
| | 30' | | SP. TAN POORLY GRADED SAND | | 3 | 30 |
| | 35' | | | | | 36 |
| | 38.5' | | WITH SOME GRAVEL | | | 40 |
| | 40' | | MH. GREEN HARD CLAYEY SILT WITH DIRTY SAND LAYERS AND TRACES OF FINE MICA | | 4 | 58 |
| | 45' | | | | | 61 |
| | 50' | | | | | 47 |
| | 55' | | BOTTOM OF HOLE - 55.0' MSLW | | 5 | 40 |
| | | | | | | 58 |
| | | | | | | 66 |
| | | | | | | 81 |
| | | | | | | 90 |
| | | | | | | 79 |
| | | | | | | 100 |
| | | | | | | 83 |
| | | | | | | 100/0.9 |
| | | | | | | 94 |
| | | | | | | 90 |

| | | | | | | |
|--|-----------|---|---|------------------------|------------------------|---|
| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah River, Savannah, GA | | Hole No. SH-14 | |
| 1. PROJECT Enlargement of Kings Island Turnings Basin | | 10. SIZE AND TYPE OF BIT 4" Auger, 1 3/8" ID | | SHEET 1 OF 3 SHEETS | | |
| - LOCATION (Coordinates or Station) N 778,045 E 818,310 | | 11. DATUM FOR ELEVATION SHOWN (TBM = MSL) SPLIT SPOON | | MLW 7 1/2" Fishtail | | |
| 3. DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL | | CME-75 | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN | | DISTURBED 17 | UNDISTURBED 0 | |
| SH-14 | | 14. TOTAL NUMBER CORE BOXES | | | | |
| 5. NAME OF DRILLER T. W. Scott | | 15. ELEVATION GROUND WATER | | 15.1' | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 16. DATE HOLE | | STARTED 16 May 78 | COMPLETED 18 May 78 | |
| 7. THICKNESS OF OVERTURDEN | | 17. ELEVATION TOP OF HOLE | | -20.5' MLW 25.0 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 18. TOTAL CORE RECOVERY FOR BORING | | | | |
| 9. TOTAL DEPTH OF HOLE 81.0' | | 19. SIGNATURE OF INSPECTOR | | DAWN MARIE HARTLEY | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOVERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water level, depth of weathering, etc., if significant, BLOWS) |
| 25.0' | 0 to 5' | | SM - Orange-brown, fine to medium grained, silty sand, moist, w/mica flakes | 1. | | 7 |
| | 5 to 10' | | W/ thin, tan, clay layers | 2 | | 7 |
| | 10 to 15' | | | 3 | | 3 |
| | 15 to 20' | | Gray fine grained w/a little clay, damp | 4 | | 7 |
| | 20 to 25' | | Orange-tan, fine to medium grained, wet | 5 | | 18 |
| | 25 to 30' | | SC - Gray, fine grained, clayey sand, saturated | 6 | | 22 |
| | 30' | | W/ occasional clay layers | | | 18 |
| | | | Continued on sheet 2 | | | 14 |
| | | | | | | 9 |
| | | | | | | 6 |
| | | | | | | 8 |
| | | | | | | 8 |
| | | | | | | 6 |
| | | | | | | 4 |
| | | | | | | 4 |
| | | | | | | 8 |
| | | | | | | 3 |
| | | | | | | 3 |
| | | | | | | 8 |
| | | | | | | 12 |
| | | | | | | 9 |
| <u>BLOWS PER FOOT:</u> Number required to drive 1 3/8" ID split spoon w/ 140 lb. hammer falling 20" | | | | | | |
| NOTE: Soils field classified in accordance with the Unified Soil Classification System. | | | | | | |

| BORING LOG (Cont Sheet) | | | TOP OF HOLE MLW | Hole No. SH-14 | | |
|-------------------------------------|-------|--------|---|-------------------------|-------------------------|---|
| enlargement of Kings Island Turning | | | INSTALLATION Savannah River, Savannah, GA | SHEET 2 OR 3 SHEETS | | |
| LEVATION | DEPTH | LEGEND | BASIN CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if applicable) |
| | 30 | c | d | e | JAR | R BLOWS |
| 6.0' | | | SC - Gray, fine grained, clayey sand, w/occasional clay layers saturated | | 77 | 6 |
| | 35 | | SM - Gray-brown, medium to fine grained silty sand, saturated | | | 18 |
| | | | Fine to medium grained w/fine gravel and gray clay layers | | 8 | 25 |
| | 40 | | Gray, fine grained, no gravel | | | 25 |
| | | | No clay, w/a fine gravel layer | | 9 | 12 |
| | 45 | | Fine to medium grained | | 10 | 18 |
| | | | Traces of decomposing organic matter | | | 24 |
| | 50 | | SC - Gray, fine grained, clayey sand | | 11 | 28 |
| | | | SM - Gray, fine to medium grained silty sand | | 12 | 30 |
| | 55 | | W/fine gravel | | | 22 |
| | | | Coarse grained w/gray clay patches | | 13 | 50 |
| | 60 | | No clay | | | 33 |
| | | | MH - Dark gray-green plastic silt, w/ fine mica flakes & some fine gravel | | 14 | 40 |
| | 65 | | | | | 40 |
| | | | | | | 26 |
| | 70 | | | | | 26 |
| | | | | | | 26 |
| | | | | | | 40 |
| | 70 | | | | | 26 |
| | | | | | | 26 |
| | | | | | | 58 |
| | | | | | | 50 |
| | | | | | | 55 |
| | | | | | | 51 |
| | | | | | | 30 |
| | | | | | | 23 |
| | | | | | | 34 |

Hole No. SII-17

| | | | | |
|--|--|---|--|--|
| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah River, Savannah, GA | SHEET 1 OF 3 SHEETS |
| 1. PROJECT Enlargement of Kings Island Turning Basin | | 10. SIZE AND TYPE OF BIT 1 3/8" ID Splitspoon | | |
| 4. LOCATION (Coordinates or Surveyor's No. 777480 E318730 | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) 4" Spiral MTW 7" Fishbar | | |
| 3. DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL CME 75 | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-17 | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | DISTURBED 15 UNDISTURBED 0 |
| 5. NAME OF DRILLER T. W. Scott | | 14. TOTAL NUMBER CORE BOXES | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER | | |
| 7. THICKNESS OF OVERBURDEN 81.0' | | 16. DATE HOLE 18 May 78 | STARTED | COMPLETED 25 May 78 |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 25.0' MTW | | |
| 9. TOTAL DEPTH OF HOLE 81.0' | | 18. TOTAL CORE RECOVERY FOR BORING % | | |
| | | 19. SIGNATURE OF INSPECTOR DAWN MARIE HARTLEY | | |



| DRILLING LOG (Cont Sheet) | | | " TOP OF HOLE | 25.0' MLW | Hole No. | SH-17 |
|---------------------------|--|--------|---|-------------------------|--------------------------------|--|
| PROJECT | Enlargement of Kings Island Turning Basin | | INSTALLATION | Savannah River | Savannah, GA | SHEET 2 OR 3 SHEETS |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | 30 | c | SM - Gray fine grained silty sand with mica flakes and green and dark brown plastic silty layers No silt, with organic matter | | | R B |
| | 35 | | No organic matter | | 7 | |
| | 40 | | | | 8 | |
| | 45 | | Fine to medium grained With wood chunks | | 9 | |
| | 50 | | Fine grained, without wood chunks | | 10 | |
| | 55 | | | | 11 | |
| | 60 | | Fine to medium grained Medium to fine grained with small gray clay patches | | 12 | |
| | 65 | | Medium grained Medium to coarse grained | | 13 | |
| | 70 | | With wood chunks Fine to medium grained, no wood chunks, with a trace of clay MH - Dark green plastic silt with small pockets of sand throughout, with fine mica flakes | | | |
| | | | Continued on sheet 3 | | | |

| DRILLING LOG (Cont Sheet) | | | FID | TOP OF HOLE | 25.0' MLW | Hole No. SH-17 | | |
|---------------------------|--|--------|---|------------------------------|-------------------------|--------------------------------|--|------------------|
| PROJECT | Enlargement of Kings Island Turning Basin | | INSTALLATION | Savannah River, Savannah, GA | | | SHEET | 3 OR 3 SHEETS |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | | % CORE RECOV. ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | |
| s | m | c | d | e | f | g | BLOWS | |
| | 70 | | MH - Dark green plastic silt, with fine mica flakes and small pockets of sand through- out | | | | | 100 |
| | | | No sand | | | 14 | | 89 |
| | 75 | | | | | | | 55 |
| | | | | | | | | 30 |
| | 80 | | With occassional thin gray fine grained sand lenses | | | 15 | | 31 |
| | | | | | | | | 36 |
| | | | | | | | | 40 |
| | | | Bottom of Hole 81.0' | | | | | 30 |

| DRILLING LOG | | | DIVISION South Atlantic | INSTALLATION Savannah River, Savannah, GA | SHEET 1 OF 2 SHEETS | |
|--|---|---|---|--|--|--|
| 1. PROJECT Enlargement of Kings Island | 2. LOCATION (Coordinates or Station) N777075 E818800 | 3. DRILLING AGENCY Savannah District | | 10. SIZE AND TYPE OF BIT 1 3/8" ID Split spoon | 11. DATUM FOR ELEVATION SHOWN (TBM or MLW) | |
| | | | | MLW | 4" Auger | |
| 4. HOLE NO. (As shown on drawing title and file number) | SH-18 | 5. NAME OF DRILLER T. W. Scott | | 12. MANUFACTURER'S DESIGNATION OF DRILL CME 75 | 7" Fishrall | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | 7. THICKNESS OF OVERTBURDEN 67.5' | 8. DEPTH DRILLED INTO ROCK 0.0' | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN 12 | DISTURBED | UNDISTURBED 0 |
| 9. TOTAL DEPTH OF HOLE 67.5' | | 14. TOTAL NUMBER CORE BOXES | 15. ELEVATION GROUND WATER | 16. DATE HOLE 1 Jun 78 | STARTED | COMPLETED 2 Jun 78 |
| | | | | 17. ELEVATION TOP OF HOLE 12.7' MLW | | |
| | | | | 18. TOTAL CORE RECOVERY FOR BORING | | |
| | | | | 19. SIGNATURE OF INSPECTOR DAWN MARIE HARTLEY | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (DESCRIPTION) | CORE RECOVERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0 | 0 | | SC - Orange-tan, fine to medium grained clayey sand, moist, with gray clay layers | 1 | | W. T. 4.0' 12 Date 1 Jun 78 15 Depth to water during drilling. 15 |
| 5 | 5 | | Saturated | 2 | | W. T. 3.5' Water Table reading 24 hrs. after hole completed. 15 |
| 10 | 10 | | OL - Dark brown, soft fat, clayey organic silt SM - Tan, gray, fine grained silty sand with fine mica flakes | 3 | | 0 7 |
| 15 | 15 | | Gray | 4 | | 14 20 |
| 20 | 20 | | | 5 | | 6 6 7 |
| 25 | 25 | | MII - Gray-green, soft plastic silt with a trace of organic matter | 6 | | 14 15 21 |
| 30 | 30 | | SM - Gray, fine to medium grained silty sand Fine gravel layer with occasional thin gray clay layers | 7 | | 16 16 25 |
| | | | Continued on sheet 2 | | | |
| NOTE: Soils field classified in accordance with the Unified Soil Classification System. | | | | BLOWS PER FOOT: Number required to drive 1 3/8" ID split-spoon w/140 lb. hammer | | |

| DRILLING LOG (Cont Sheet) | | | 12.7' MLW | Hole No. | SH-18 | | |
|---------------------------|--|--------|--|-------------------------|--------------------------------|---|-------|
| PROJECT | Enlargement of Kings Island Turning Basin | | INSTALLATION | SHEET 2 OR 2 SHEETS | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Drill samples) | % CORE RECOV. ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth & weathering, etc., if significant) | BLOWS |
| | 30 | | S4 - Gray, fine grained silty sand with occasional thin gray clay layers | | | | 22 |
| | | | With a thin layer of fine gravel | | 8 | | 16 |
| | 35 | | With mica flakes but no clay or gravel | | | | 22 |
| | | | Fine to medium grained | | | | 20 |
| | | | Medium to coarse grained with some fine gravel | | 9. | | 15 |
| | 40 | | | | | | 30 |
| | | | | | | | 20 |
| | | | | | | | 27 |
| | | | | | | | 33 |
| | 45 | | Fine grained, no gravel | | | | 38 |
| | | | | | | | 30 |
| | 50 | | MH - Green plastic silt with fine mica flakes | | 10 | | 33 |
| | | | | | | | 34 |
| | | | | | | | 49 |
| | -55 | | | | | | 40 |
| | | | | | | | 41 |
| | 60 | | | | | | 49 |
| | | | | | | | 57 |
| | 65 | | | | | | 89 |
| | | | | | | | 40 |
| | | | | | | | 40 |
| | | | | | | | 80 |
| | | | | | | | 33 |
| | | | | | | | 41 |
| | | | Bottom of Hole 67.5' | | 11 | | |
| | 70 | | | | | | |

| DRILLING LOG | | DIVISION | INSTALLATION | | Hole No. SH-20 | |
|---|-------|--|---|-------------------------|--|--|
| 1. PROJECT | | South Atlantic | Savannah River, Savannah, GA | | SHEET 1 OF 2 SHEETS | |
| Enlargement or Kings Island Turning Basin | | | 10. SIZE AND TYPE OF BIT | | 1 3/8" ID Splitspoon | |
| 2. LOCATION (Coordinates or Station) | | N776665 E819180 | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) | | 4" Auger | |
| 3. DRILLING AGENCY | | Savannah District | 12. MANUFACTURER'S DESIGNATION OF DRILL | | MLW 7" Fisher | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-20 | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED 15 UNDISTURBED 0 | |
| 5. NAME OF DRILLER | | T. W. Scott | 14. TOTAL NUMBER CORE BOXES | | | |
| 6. DIRECTION OF HOLE | | <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | 15. ELEVATION GROUND WATER | | | |
| 7. THICKNESS OF OVERTBURDEN | | 70.5' | 16. DATE HOLE | | STARTED 24 Apr 78 COMPLETED 30 May 78 | |
| 8. DEPTH DRILLED INTO ROCK | | 0.0' | 17. ELEVATION TOP OF HOLE | | 13.5' MLW | |
| 9. TOTAL DEPTH OF HOLE | | 70.5' | 18. TOTAL CORE RECOVERY FOR BORING | | % | |
| | | | 19. SIGNATURE OF INSPECTOR | | C. GRIFFIN/D. HARLTAY | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0 | | | ML - Tan inorganic silt with traces of fine sand and mica | 1 | | BLOWS |
| 5 | | | Becomes more sandy | 2 | | W. T. 5.0' |
| 5 | | | SM - Dark gray and brown, fine to medium silty sand with soft silt layers | 3 | | Date 24 Apr 78 |
| 5 | | | Dark gray and green, fine grained, saturated, with no silt layers | | | Depth to water during drilling. |
| 10 | | | Dark green with gray layers | 4 | | W. T. 3.5' |
| 10 | | | Gray with some pieces of rotten wood, no clay | | | Water table reading 24 hrs. after hole completed. |
| 10 | | | Green, no wood | | | |
| 15 | | | MH - Dark brown, soft fat clayey silt with traces of fine mica | 5 | | |
| 20 | | | With tan sand layers | 6 | | |
| 20 | | | SM - Brown, fine to medium grained silty sand | | | |
| 20 | | | Tan and brown | | | |
| 25 | | | Gray, fine grained | | | |
| 30 | | | Continued on sheet 2 | | | |
| NOTE: Soils field classified in accordance with the Unified Soil Classification System. | | | | | | BLOWS PER FOOT: Number required to drive 1 3/8" ID Splitspoon w/140 lb. hammer falling 20" |

DRILLING LOG (Cont Sheet)

REV. A TOP OF MOLT

12.5' MLW

Hole No.

SH-22

PROJECT Enlargement of Kings Island
Turning Basin

INSTALLATION

SHEET 2
OF 2 SHEETS

| ELEVATION ft | DEPTH ft | LEGEND | CLASSIFICATION OF MATERIALS (Description) | | % CORE RECOV. ERY e | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | |
|-----------------|-------------|--------|---|---|------------------------------|--------------------------------|--|----|
| | | | d | e | | | f | g |
| 30 | | | SM - Light gray, fine grained silty sand, with mica flakes and occassional organic layers | | | | | 33 |
| 35 | | | | | | | | 20 |
| 40 | | | Gray, fine to medium grained | | | 8 | | 20 |
| 45 | | | With occassional layers of fine gravel | | | | | 29 |
| 50 | | | Fine grained, no gravel | | | | | 17 |
| 55' | | | Fine to medium grained | | | 9 | | 19 |
| 60 | | | | | | | | 17 |
| 65 | | | | | | | | 19 |
| 70 | | | MH - Green plastic silt with fine mica flakes | | | 10 | | 14 |
| | | | Bottom of Hole 67.5' | | | | | 23 |

Hole No. SH-22

| DRILLING LOG | | DIVISION South Atlantic | INSTALLATION Savannah River, Savannah, GA | SHEET 1 OF 2 SHEETS | | |
|--|-------|--|---|----------------------------|---|--|
| PROJECT Enlargement of Kings Island Turning Basin | | 10. SIZE AND TYPE OF BIT 1 3/8" ID Splitspoon | | | | |
| LOCATION (Coordinates or Station) N776200 E819310 | | 11. DATUM FOR ELEVATION SHOWN FROM - MLW 4" Auger MLW 7" Flight | | | | |
| DRILLING AGENCY Savannah District | | 12. MANUFACTURER'S DESIGNATION OF DRILL CME 75 | | | | |
| HOLE NO. (As shown on drawing title and file number) | | SH-22 | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | DISTURBED 12 UNDISTURBED 0 | | |
| NAME OF DRILLER T. W. Scott | | 14. TOTAL NUMBER CORE BOXES | | | | |
| DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER | | | | |
| THICKNESS OF OVERBURDEN 67.5' | | 16. DATE HOLE | STARTED 30 May 78 | COMPLETED 1 Jun. 78 | | |
| DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 12.5' MLW | | | | |
| TOTAL DEPTH OF HOLE 67.5' | | 18. TOTAL CORE RECOVERY FOR BORING % | | | | |
| 19. SIGNATURE OF INSPECTOR DAWN MARIE HARTLEY | | | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| * | 0 | c | SM - Brown, fine grained silty sand, moist, with mica flakes, with organic matter | 1 | | 12 BLOWS |
| | 5 | c | SC - Tan, fine grained clayey sand, damp, with mica flakes | 2 | | W. T. 6.0' 23 |
| | 5 | c | SM - Orange-tan, fine to medium grained silty sand, damp, with mica flakes | | | Date 30 May 78 25 |
| | 10 | c | Saturated | | | Depth to water during drilling. 6 |
| | 10 | c | MH - Dark brown, soft fat clayey silt, with fine mica flakes | 3 | | W. T. 4.3' Water table reading 24 hrs. after hole completed. 7 |
| | 15 | c | SM - Light gray, fine grained silty sand, with mica flakes | 4 | | 16 |
| | 15 | c | With occasional thin layers of organic matter | | | 9 |
| | 20 | c | No organic layers | 5 | | 15 |
| | 20 | c | | 6 | | 12 |
| | 25 | c | With occasional organic layers | | | 12 |
| | 25 | c | | 7 | | 12 |
| | 30 | c | Continued on sheet 2 | | | 14 |
| NOTE: Soils field classified in accordance with the Unified Soil Classification System. | | | | | BLOWS PER FOOT: Number required to drive 1 3/8" ID splitspoon w/140 lb. hammer falling 30". | |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | Hole No. SH-149 | |
|--|-------|----------------------------|---|---|---|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | SHEET 1 OF 2 SHEETS | | |
| 2. LOCATION (Coordinates or Station) $X = 817840$, $Y = 778530$ (GA EAST) | | | 10. SIZE AND TYPE OF BIT $1\frac{3}{8}$ " I.D. SPLIT SPOON, 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-149 | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | DISTURBED 15 UNDISTURBED 0 | |
| 5. NAME OF DRILLER D. JUSTISS | | | 14. TOTAL NUMBER CORE BOXES 0 | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | 15. ELEVATION GROUND WATER SEE REMARKS | | |
| 7. THICKNESS OF OVERTURDEN 60.0' | | | 16. DATE HOLE STARTED 18 Oct 91 COMPLETED 18 Oct 91 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | 17. ELEVATION TOP OF HOLE | | |
| 9. TOTAL DEPTH OF HOLE 60.0' | | | 18. TOTAL CORE RECOVERY FOR BORING N/A % | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOVERY BOX OR SAMPLE NO. JAN | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0 | b | c | d | 1 | CLEANED OUT HOLE WITH 4" SPIRAL AUGER FROM 1.5' TO 7' |
| 5 | | | (SM) BROWN, SILTY, FINE TO MEDIUM SAND, TRACE OF ROOTS, SLIGHTLY DAMP. (SP) LIGHT BROWN TO TAN, POORLY GRADED FINE TO MEDIUM SAND, TRACE OF SILT, SLIGHTLY DAMP. | 2 | 4.5' & 6.0' TO 9.0', JAN SAMPLE #2 TAKEN FROM AUGER |
| 10 | | | (SM) BROWN, SILTY, FINE TO MEDIUM SAND, DAMP. MEDIUM SAND, WET. / MEDIUM TO COARSE SAND, SOME FINE TO MEDIUM, SAND FROM 10.3' TO 10.5', WASH | 3 | FROM 1.5' TO 4.5', Began using 5½" FISHTAIL & ZEIGEL DRILLING MUD AT 10.5'. |
| 15 | | | (SC) GREENISH GRAY, CLAYEY, FINE TO MEDIUM SAND, SOME SILT, TRACE OF MICA, WET. | 4 | SPLIT SPOON DRIVES TAKEN AT 4.5' INTERVALS. |
| 20 | | | WASH | 5 | WATER LEVEL 6.5' DEPTH TO WATER DURING DRILLING. |
| 25 | | | (SM) TANNISH GRAY, SILTY, MEDIUM TO COARSE SAND, TRACE OF CLAY, WET. | 6 | WATER LEVEL NOT ENCOUNTERED 21 Oct 91. TAPEO HOLE TD 5.0'. |
| 30 | | | WASH | 7 | |
| | | | SAME AS 22.5' TO 24.0! | 8 | |
| | | | WASH | | |
| | | | CONTINUED ON SHEET #2 | | |
| | | | NOTE: SOILS VISUALLY FIELD CLASSIFIED IN ACCORDANCE WITH THE UNIFIED SOIL CLASSIFICATION SYSTEM. | | |
| | | | | | — — — — — |
| | | | | | BLows PER FOOT: |
| | | | | | NUMBER REQUIRED TO DRIVE $1\frac{3}{8}$ " I.D. SPLIT SPOON WITH 140 LB. HAMMER FALLING 30". |

DRILLING LOG (Cont. Sheet)

ELEVATION TOP OF HOLE

Hole No. SH-149

PROJECT
SAVANNAH HARBOR DEEPENINGINSTALLATION
SAVANNAH, GA.SHEET 2
OF 2 SHEETS


| ELEVATION a | DEPTH b | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY e | BOX OR SAMPLE NO. JAR f | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g | BLOWS h |
|----------------|------------|-------------|--|------------------------------|-------------------------------------|---|------------|
| | 30 | | Wash. | | | | |
| | | | (SM) Grey, fine to med. silty SAND. Trace of mica, wet. | | 9 | | 24 |
| | | | Wash. | | | | |
| 35 | | | (SP) Grey, med.to coarse, poorly graded SAND. Trace of silt & mica, wet. | | 10 | | 39 |
| | | | Wash. | | | | |
| 40 | | | Same as 36.0' to 37.5' but coarse sand, Trace of fine gravel. | | 11 | | 46 |
| | | | Wash. | | | | |
| 45 | | | Same as 40.5' to 42.0'. | | 12 | | 33 |
| | | | Wash. | | | | |
| 50 | | | (GP) Greenish-grey, fine, poorly graded GRAVEL. Trace of silt & coarse sand, wet. | | 13 | | 17 |
| | | | Wash. NOTE: Wash return contained some sand and clay. | | | | |
| 55 | | | (CL) Greyish-green, silty, lean CLAY. Trace of mica & fine sand, slightly damp. | | 14 | | 36 |
| | | | Wash | | | | |
| 60 | | | Same as 54.0' to 55.5' but dry. | | 15 | | 45 |
| | | | Bottom of Boring 60.0' | | | | |

| DRILLING LOG | | | VISION SOUTH ATLANTIC | | INSTALLATION | | Hole No. 377-100 | |
|--|-------|--------|--|--|--|--------------------------------|---|--|
| | | | | | SAVANNAH, GA. | | SHEET 1 OF 2 SHEETS | |
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " splitspoon, 4" spiral auger, 5 $\frac{1}{2}$ " fishtail | | | |
| 2. LOCATION (Coordinates or Station) X-817555 Y-779145 GA. EAST | | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | | SH-150 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED : 18 UNDISTURBED : 0 | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | | | 15. ELEVATION GROUND WATER SEE REMARKS | | | |
| 7. THICKNESS OF OVERTBURDEN 64.5' | | | | | 16. DATE HOLE STARTED 16 OCT 91 COMPLETED 17 OCT 91 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | | 17. ELEVATION TOP OF HOLE | | | |
| 9. TOTAL DEPTH OF HOLE 64.5' | | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | |
| | | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc. If significant) | |
| 0 | 0 | c | | | | | BLOWS | |
| | | | (SP) Tan, coarse, poorly graded SAND. Damp. | | | 1 | | |
| | | | (SC) Olive, fine clayey SAND. Some silt, damp. | | | 2 | Cleaned out hole with spiral auger to 4.5'. Jar #2 taken from auger from 1.5' to 4.5'. Splitspoon drive taken at each 4.5' interval to 55.5'. Began using 5 $\frac{1}{2}$ " fishtail & Zeogel drilling mud at 6.0'. | |
| | 5 | | Fine to med. sand, trace of fine gravel, wet. | | | 3 | Water level 2.0' depth to water during drilling. | |
| | | | Wash NOTE: Wash return contained large amount of clay. | | | 4 | | |
| | 10 | | Same as 4.5' to 6.0'. | | | 5 | Water level 1.7' depth to water on 21 Oct 91. Taped hole to 19.8' depth. | |
| | | | Wash | | | 6 | | |
| | 15 | | (SP) Olive grey, med., poorly graded SAND. Trace of silt, wet. | | | 7 | | |
| | | | Wash. | | | 8 | | |
| | 20 | | (SM) Olive-grey, med., silty SAND, wet. | | | | | |
| | | | Wash. Note: Traces of wood in wash. | | | | | |
| | 25 | | (SP) Light brown, med. to coarse, poorly graded SAND. Trace of silt, wet. | | | | | |
| | | | Wash. | | | | | |
| | 30 | | Some as 22.5' to 24.0', but with traces of fine gravel. | | | | | |
| | | | Wash. | | | | | |
| | | | Continued on sheet #2 | | | | | |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". | |

| DRILLING LOG (Cont.Sheet) | | | ELEVATION TOP OF HOLE | | Hole No. SH-150 | |
|--------------------------------------|-------|--------|---|-----------------|--------------------------|--|
| PROJECT SAVANNAH HARBOR DEEPENING | | | INSTALLATION SAVANNAH, GA. | | SHEET 2 OF 2 SHEETS | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOVERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc. if significant) |
| | 30 | | | | | |
| | 31.5 | | Wash. | | | |
| | 32.0 | | (SP) Light brown,fine to med poorly graded SAND. Trace of silt, wet. | | 9 | |
| | 33.0 | | | | | 33 |
| | 35 | | Wash. | | | |
| | 36.0 | | Same as 31.5' to 33.0' but med. to coarse sand. | | 10 | |
| | 37.5 | | | | | 30 |
| | 40 | | Wash. | | | |
| | 41.5 | | Same as 36.0' to 37.5' but with some wood. | | 11 | |
| | 43.0 | | | | | 26 |
| | 45 | | Wash. | | | |
| | 46.5 | | (SP) Greyish-brown,coarse,poorly graded SAND. Trace of fine gravel & silt, wet. | | 12 | |
| | 48.0 | | | | | 27 |
| | 49.5 | | Wash. | | | |
| | 50 | | (CL) Greyish-green,silty lean CLAY. Trace of Mica & fine sand, dry. | | 13 | |
| | 51.0 | | | | | 31 |
| | 52.5 | | Wash | | | |
| | 54.0 | | | | | |
| | 55 | | Same as 49.5' to 51.0' but greyish-green. | | 14 | |
| | 56.5 | | | | | 54 |
| | 58.5 | | Wash. | | | |
| | 60 | | | | | |
| | 61.5 | | (SM) Grey & greenish-grey,fine silty SAND. Trace of Mica,dry. | | 15 | |
| | 63.0 | | | | | 100/0.8 |
| | 64.5 | | (SC) Greyish-green,fine clayey SAND. Some silt, dry. | | 16 | |
| | 66.0 | | | | | 78 |
| | 67.5 | | | | | 42 |
| | 69.0 | | Bottom of Boring 64.5' | | 17 | |
| | 70.5 | | | | | 43 |

| DRILLING LOG | | | | VISION SOUTH ATLANTIC | | INSTALLATION | | Hole No. SH-15 / AVANNAH, GA. | | SHEET 1 OF 1 SHEETS | |
|--|------------|--------|--|--------------------------|--|--|-------------------------------|---|--|------------------------|--|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | | | 10. SIZE AND TYPE OF BIT 1 1/8" split spoon, 5 1/2" fishtail | | | | | |
| 2. LOCATION (Coordinates or Station) X-817067 Y-779191 GA. EAST | | | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | | | SH-157 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 15 | | DISTURBED 15 | | UNDISTURBED 0 | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | | | 14. TOTAL NUMBER CORE BOXES | | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | | | | 15. ELEVATION GROUND WATER N/A | | | | | |
| 7. THICKNESS OF OVERTBURDEN 59.6' (Water 38.6') | | | | | | 16. DATE HOLE STARTED 10 DEC 91 | | COMPLETED 10 DEC 91 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | | | 17. ELEVATION TOP OF HOLE 0.0' | | | | | |
| 9. TOTAL DEPTH OF HOLE 59.6' | | | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | | | |
| | | | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | | | |
| ELEVATION 0.0 | DEPTH 0 | LEGEND | CLASSIFICATION OF MATERIALS (Description) | | | % CORE RECOV- ERY | BOX OR SAMPLE NO JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | | | |
| | | | | | | | | | | | |
| | | | Water | | | | | Scalper change at 35.0'. Set 6" diameter casing by own weight to 43.0'. | | | |
| | | | 35 | | | | | | | | |
| | | | Bottom of Harbor 38.6' | | | | | | | | |
| -38.6' | 40 | | (SP) Tan, poorly graded, coarse SAND. | | | | 1 | Weight of rods drove split spoon to 40.1'. Had no recovery, redrove to 40.1' then cont'd. drive to 41.6'. Sample 1 from 38.6' to 41.6'. | | | |
| -41.6' | 41 | | Some fine gravel. | | | | | 0 | | | |
| -44.6' | 45 | | (CL) Grey, silty, lean CLAY. Some fine sand, trace of mica. | | | | 2 | 67 | | | |
| | 46 | | | | | | | 31 | | | |
| | 47 | | | | | | | 17 | | | |
| | 48 | | | | | | | 29 | | | |
| | 49 | | | | | | | 52 | | | |
| | 50 | | | | | | | 45 | | | |
| | 51 | | | | | | | 41 | | | |
| | 52 | | | | | | | 34 | | | |
| | 53 | | | | | | | 37 | | | |
| | 54 | | | | | | | 43 | | | |
| | 55 | | | | | | | 48 | | | |
| | 56 | | | | | | | 55 | | | |
| -58.1' | 57 | | (SC) Grey, fine clayey SAND. Some silt, trace of mica. | | | | 5 | 54 | | | |
| -59.6' | 58 | | Bottom of Boring 59.6' | | | | | | | | |
| | 59 | | | | | | | | | | |
| | 60 | | | | | | | | | | |
| NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | | | | BLOWS PER FOOT: Number required to drive 1 1/8" I.D. split spoon w/140 lb. hammer falling 30". | | | | | |

| | | | | |
|--|--|---|-------------------------------|------------------------|
| DRILLING LOG | | VISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 1 SHEETS |
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | 10. SIZE AND TYPE OF BIT 1 1/8" splitspoon, 5 1/2" fishtail | | |
| 2. LOCATION (Coordinates or Station) x-817368 Y-779194 GA. EAST | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-158 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN. DISTURBED 6 UNDISTURBED 0 | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | 14. TOTAL NUMBER CORE BOXES 0 | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | |
| 7. THICKNESS OF OVERBURDEN 60.0' (WATER 34.5') | | 16. DATE HOLE STARTED 6 DEC 91 COMPLETED 6 DEC 91 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | |
| 9. TOTAL DEPTH OF HOLE 60.0' | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | |
| | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | |



| DRILLING LOG | | VISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 1 SHEETS | | | |
|--|-------|--|--|-------------------------|--------------------------------|--|-------|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " Splitspoon, $5\frac{1}{2}$ " Fishtail | | | | | |
| 2. LOCATION (Coordinates or Station) X=817039 Y=778184 | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED UNDISTURBED 15 : 0 : 0 | | | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | 14. TOTAL NUMBER CORE BOXES 0 | | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | | | | |
| 7. THICKNESS OF OVERBURDEN 50.8' (Water 40.3') | | 16. DATE HOLE STARTED COMPLETED 14 JAN 91 14 JAN 91 | | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | | | | |
| 9. TOTAL DEPTH OF HOLE 50.8' | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | | | |
| | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | BLOWS |
| 0.0 | 0 | c | Water | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 43.4'. | 9 |
| -40.3' | 40 | | Bottom of Harbor 40.3' | | | | 0 |
| -40.3' | 40 | | (MH) Dark grey to black clayey SILT. | | 1 | Weight of rods drove splitspoon from 40.3' to 42.6'. Cont'd. drive to 43.3' with three hammer blows. Jar sample 2 from approx. 42.6' to 43.3'. | 3 |
| -42.6' | 42.6 | | (SC) Dark grey, fine to medium clayey SAND. | | 2 | | 45 |
| -43.3' | 43.3 | | (SM) Dark grey, fine silty SAND. Trace of clay. | | 3 | | 72 |
| -46.3' | 46.3 | | (SC) Grey, fine clayey SAND. Some silt. Trace of mica. | | 4 | | 38 |
| -50.8' | 50.8 | | Bottom of Boring 50.8' | | 5 | | 48 |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". | 36 |

| DRILLING LOG | | | VISION SOUTH ATLANTIC | | INSTALLATION* | | Hole No. 3M-101 |
|--|-------|--------|--|--|--|--|---|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | | AVANNAH, GA. | | SHEET 1 OF 1 SHEETS |
| 2. LOCATION (Coordinates or Station) X-818085 Y-778090 | | | GA. EAST | | 10. SIZE AND TYPE OF BIT 1½" Splitspoon, 5½" Fishtail | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or NSL) MLW | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | | SH-161 | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED 4 UNDISTURBED 0 |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | | | 14. TOTAL NUMBER CORE BOXES | | 0 |
| 7. THICKNESS OF OVERTBURDEN 50.9' (Water 38.9') | | | | | 15. ELEVATION GROUND WATER | | N/A |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | | 16. DATE HOLE STARTED 14 JAN 91 | | COMPLETED 14 JAN 91 |
| 9. TOTAL DEPTH OF HOLE 50.9' | | | | | 17. ELEVATION TOP OF HOLE 0.0' | | |
| | | | | | 18. TOTAL CORE RECOVERY FOR BORING | | N/A |
| | | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0.0 | 0.0 | c | Water | | | | 9 BLOWS |
| | | | 35 | | | | Scale change at 35.0'. Set 6" diameter casing by own weight to 44.9'. |
| | | | Bottom of Harbor 38.9' | | | | Weight of rods drove splitspoon from 38.9' to 44.9'. Jar sample 2 from approx. 44.0' to 44.9'. |
| | | | 40 (MH) Very dark grey clayey SILT. | | | 1 | |
| | | | 45 (SC) Dark grey, fine to medium clayey SAND. | | | 2 | |
| | | | Fine sand, some silt, trace of mica. | | | 3 | |
| | | | 50 Bottom of Boring 50.9' | | | 4 | |
| NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | | | | BLOWS PER FOOT: Number required to drive 1½" I.D. splitspoon w/140 lb. hammer falling 30". | |

Hole No. SH-1b2

| DRILLING LOG | | VISION SOUTH ATLANTIC | INSTALLATION | SAVANNAH, GA. | | SHEET 1 OF 1 SHEETS |
|--|-------|--|--|-------------------------|--------------------------------|---|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | 10. SIZE AND TYPE OF BIT 1 1/8" splitspoon, 5 1/2" fishtail | | | | |
| 2. LOCATION (Coordinates or Station) X-817143 Y-777680 GA. EAST | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-162 | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED 6 | UNDISTURBED 0 |
| 5. NAME OF DRILLER DAVID JUSTISS | | 14. TOTAL NUMBER CORE BOXES 0 | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | | | |
| 7. THICKNESS OF OVERTBURDEN 59.9' (Water 41.5') | | 16. DATE HOLE STARTED 26 JAN 92 COMPLETED 26 JAN 92 | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | | | |
| 9. TOTAL DEPTH OF HOLE 59.9' | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | | |
| | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0.0 | 0' | e | Water | | | BLOWS |
| | | | Bottom of Harbor 41.5' | | | Scale change at 41.5'. Set 6" diameter casing by own weight to 43.3'. |
| -41.5' | | | (MH) Very dark grey to black clayey SILT. Some fine to coarse sand. | | 1 | Weight of rods drove splitspoon from 41.5' to 43.4'. Jar sample 2 taken from approx. 43.0' to 43.4'. |
| -43.0' | | | (SC) Very grey, fine clayey SAND. Some silt. | | 2 | |
| -43.4' | | | Trace of mica. | | 3 | |
| -46.4' | | | Trace of silt. | | 4 | |
| | | | | | 5 | |
| | | | | | 6 | |
| -59.9' | 60' | | Bottom of Boring 59.9' | | | BLOWS PER FOOT: |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | Number required to drive 1 1/8" I.D. splitspoon w/140 lb. hammer falling 30". |

| DRILLING LOG | | | VISION SOUTH ATLANTIC | | INSTALLATION SAVANNAH, GA. | | Hole No. 37-103 |
|--|--------------|-------------|---|--|---|--------------------------------|---|
| | | | | | | | SHEET 1 OF 1 SHEETS |
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " split spoon, $5\frac{1}{4}$ " fishtail | | |
| 2. LOCATION (Coordinates or Station) X-817375 Y-777535 GA. EAST | | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Falling 314 | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | | SH-163 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 6 | | DISTURBED UNDISTURBED |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | | 14. TOTAL NUMBER CORE BOXES 0 | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED | | | DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | |
| 7. THICKNESS OF OVERTBURDEN | | | 59.8' (Water 41.8') | | 16. DATE HOLE STARTED 16 Nov 91 | | COMPLETED 16 NOV 91 |
| 8. DEPTH DRILLED INTO ROCK | | | 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | |
| 9. TOTAL DEPTH OF HOLE | | | 59.8' | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | |
| | | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | |
| ELEVATION 0.0 | DEPTH 0.0 | LEGEND c | CLASSIFICATION OF MATERIALS (Description) | | % CORE RECOV- ERY • | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) BLOWS |
| -41.8' | 40 | | Water | | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 45.8'. |
| -41.8' | 41.8' | | Bottom of Harbor 41.8' | | | | |
| -43.3' | 43.3' | | (MH) Dark grey, fat SILT. | | 1 | | |
| -44.8' | 44.8' | | (SC) Dark grey & grey, med. to coarse clayey SAND. | | 2 | | Weight of hammer drove split- spoon from 41.8' to 44.3', Cont'd. drive with five blows to 44.8'. 0 |
| -46.3' | 46.3' | | (SM) Grey, fine silty SAND. Some clay in layers up to 0.3' thick, trace of mica. | | 3 | | |
| | 47.8' | | (SC) Greenish grey, fine clayey SAND. Some silt, trace of mica. | | 4 | | Material from 41.8' to approx. 43.3' was very soft & wet. 48 |
| | 48.3' | | | | 5 | | |
| | 49.8' | | | | 6 | | |
| | 51.3' | | | | | | 36 |
| | 52.8' | | | | | | 53 |
| | 54.3' | | | | | | 51 |
| | 55.8' | | | | | | 35 |
| | 57.3' | | | | | | 45 |
| | 58.8' | | | | | | 53 |
| | 60.3' | | | | | | 68 |
| -59.8' | 60 | | Bottom of Boring 59.8' | | | | 61 |
| | 61.3' | | | | | | 62 |
| | | | | | | | BLOWS PER FOOT: |
| | | | | | | | Number required to drive $1\frac{1}{8}$ " I.D. split spoon w/140 lb. hammer falling 30". |
| | | | | | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. |

| DRILLING LOG | | VISION SOUTH ATLANTIC | | INSTALLATION SAVANNAH, GA. | | SHEET 1 OF 1 SHEETS | |
|--|--------------|--------------------------|--|---|--------------------------------|---|------------------------|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT 1 1/8"SPLITSPOON, 5 1/2" FISHTAIL | | | |
| 2. LOCATION (Coordinates or Station) X=818481 Y=777661 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Falling 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-164 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED 6 | UNDISTURBED 0 |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES | | 0 | |
| 6. DIRECTION OF HOLE | | | | 15. ELEVATION GROUND WATER N/A | | | |
| <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | | 16. DATE HOLE | | STARTED 16 NOV 91 | COMPLETED 16 NOV 91 |
| 7. THICKNESS OF OVERTBURDEN 60.5' (Water 38.6') | | | | 17. ELEVATION TOP OF HOLE | | 0.0' | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 18. TOTAL CORE RECOVERY FOR BORING | | N/A | |
| 9. TOTAL DEPTH OF HOLE 60.5' | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |
| ELEVATION 0.0 | DEPTH 0.0 | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY e | BOX OR SAMPLE NO. UAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g | |
| | | | | | | BLOWS | |
| | 35 | | Water | | | Scale change at 35.0'. Set 6" diameter casing by own weight to 43.6'. | |
| -38.6' | 40 | | Bottom of Harbor 38.6' | | | | |
| | 40 | | (MH) Dark grey, clayey SILT. Very wet & soft. | | 1 | Weight of hammer drove splitspoon from 38.6' to 44.0'. Jar 2 from 43.7' to 44.0'. 0 | |
| | 45 | | (SC) Greenish-grey, fine clayey SAND. Some silt, trace of mica. | | 2 | | |
| | 50 | | | | 3 | | |
| | 55 | | | | 4 | | |
| | 60 | | | | 5 | | |
| | 60 | | Bottom of Boring 60.5' | | 6 | 100/0.9 | |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | 62 | |
| | | | | | | BLOWS PER FOOT: | |
| | | | | | | Number required to drive 1 1/8" I.D. splitspoon w/140 lb. hammer falling 30". | |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | | INSTALLATION SAVANNAH, GA. | | Hole No. SH-103 | |
|--|------------|----------------------------|--|---|--------------------------------|--|------------------|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " split spoon, $5\frac{1}{2}$ " fishtail | | SHEET 1 OF 1 SHEETS | |
| 2. LOCATION (Coordinates or Station) X-817521 Y-777184 | | GA. EAST | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-165 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 6 | | DISTURBED 6 | UNDISTURBED 0 |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ | | DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERTBURDEN | | 50.8' (Water 38.8') | | 16. DATE HOLE STARTED 14 JAN 92 | | COMPLETED 14 JAN 92 | |
| 8. DEPTH DRILLED INTO ROCK | | 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE | | 50.8' | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | |
| ELEVATION 0.0 | DEPTH 0 | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) e | |
| | | | Water | | | Scale change at 35.0'. Set 6" diameter casing by own weight to 45.1'. | |
| | 35 | | | | | BLOWS | |
| | -38.8' | | Bottom of Harbor 41.5' 38.8' | | | | |
| | 40 | | (MH) Dark olive-grey, clayey SILT. | | 1 | | |
| | -42.8' | | | | 2 | | |
| | 45 | | (SC) Very dark grey to black, medium to coarse clayey SAND. Some silt. | | 3 | | |
| | -44.8' | | | | 4 | | |
| | 46.3' | | (SM) Grey, fine silty SAND. Trace of clay & mica. | | 5 | | |
| | 50 | | (SC) Grey, fine clayey SAND. Some silt, trace of mica. | | 6 | | |
| | -50.8' | | Bottom of Boring 50.8' | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. split spoon w/140 lb. hammer falling 30". | |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | | |

| DIVISION SOUTH ATLANTIC | | | | INSTALLATION SAVANNAH, GA. | | HOLE NO. 37-107 | |
|--|--------------|-------------|---|---|------------------------------|---|--|
| | | | | | | SHEET 1 OF 1 SHEETS | |
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " splitspoon, 5 $\frac{1}{2}$ " fishtail | | | |
| 2. LOCATION (Coordinates or Station) X-819096 Y-777170 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-167 | | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 5 UNDISTURBED 0 | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERTURDEN 59.7' (WATER 42.6') | | | | 16. DATE HOLE STARTED 24 JAN 92 COMPLETED 24 JAN 92 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 59.7' | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | |
| | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |
| ELEVATION 0.0 | DEPTH 0.0 | LEGEND e | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY JAR | BOX OR SAMPLE NO. f | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g | |
| | | | Water | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 45.1'. | |
| -42.6' | 40 | | | | | | |
| -42.6' | 42.6 | | Bottom of Harbor 34.5' | | | | |
| -44.7' | 44 | | | | 1 | Weight of rods drove splitspoon from 42.6' to 44.7'. 0 | |
| -44.7' | 45 | | (CH) Dark grey, fat CLAY. Some fine sand. | | 2 | | |
| -44.7' | 48 | | | | 3 | | |
| -44.7' | 50 | | (SC) Grey, fine clayey SAND. Some silt. | | 4 | | |
| -44.7' | 52 | | | | 5 | | |
| -59.7' | 55 | | | | | | |
| -59.7' | 58 | | | | | | |
| -59.7' | 60 | | Bottom of Boring 59.7' | | | | |
| NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". | | | |

| DRILLING LOG | | VISION SOUTH ATLANTIC | | INSTALLATION | SAVANNAH, GA. | | SHEET 1 OF 1 SHEETS |
|--|------------|--------------------------|--|--|--------------------------------|---|------------------------|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " splitspoon, 5 $\frac{1}{2}$ " fishtail | | | |
| 2. LOCATION (Coordinates or Station) X-817468 Y-776786 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-168 | | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 4 UNDISTURBED 0 | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERTBURDEN 53.5' (Water 40.7') | | | | 16. DATE HOLE STARTED 25 JAN 92 COMPLETED 25 JAN 92 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 53.5' | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | |
| | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |
| ELEVATION 0.0 | DEPTH 0 | LEGEND a | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc. If significant) | |
| | | | Water | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 44.5'. | |
| -40.7' | 40 | | Bottom of Harbor 40.7' (MH) Very dark grey, clayey SILT. Trace of fine to coarse sand. | | 1 | 0 | |
| -43.8' | 45 | | (CL) Dark grey, silty, lean CLAY. Some fine sand. Trace of mica. | | 2 | 37 | |
| -46.0' | 50 | | (SC) Grey, fine clayey SAND. Trace of silt, some mica. | | 3 | 45 | |
| -53.5' | 55 | | Bottom of Boring 53.5' NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | 4 | 77 70 93 76 | |
| | 60 | | | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". | |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | | INSTALLATION | SAVANNAH, GA. | | NOTE NO. SII 100A |
|--|--------------|----------------------------|--|---|--------------------------------|---|------------------------|
| | | | | | | | SHEET 1 OF 1 SHEETS |
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " splitspoon, $5\frac{1}{2}$ " fishtail | | | |
| 2. LOCATION (Coordinates or Station) X-817466 Y-776799 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-168A | | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 2 DISTURBED 0 UNDISTURBED 0 | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERTBURDEN 59.5' (Water 38.3') | | | | 16. DATE HOLE STARTED 25 JAN 92 COMPLETED 25 JAN 92 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 59.5' | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | |
| | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |
| ELEVATION 0.0 | DEPTH 0.0 | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY e | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g | |
| -38.3' | 35 | | Water | | | Scale change at 35.0'. Set 6" diameter casing by own weight to 44.5'. Hole SH-168A is a companion log to SH-168 which was completed to 53.5' before moving barge out of the shipping lane for traffic. | |
| -38.3' | 40 | | Bottom of Harbor 38.3' | | | Cleared out from 38.3' to 53.5' with $5\frac{1}{2}$ " fishtail. | |
| -53.5' | 45 | | | | | | |
| -53.5' | 50 | | | | | | |
| -53.5' | 55 | | (SC) Dark grey, fine clayey SAND. Trace of silt & mica. | | 1 | | |
| -59.5' | 55 | | | | | | |
| -59.5' | 60 | | Bottom of Boring 59.5' | | 2 | | |
| NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". | | | |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 1 SHEETS | |
|--|--------------|----------------------------|--|--|--------------------------------|---|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " SPLIT SPOON, $5\frac{1}{2}$ " FISHTAIL | | |
| 2. LOCATION (Coordinates or Station) X-818211 Y-776659 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-169 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED 5 UNDISTURBED 0 |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES 0 | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | | 15. ELEVATION GROUND WATER N/A | | |
| 7. THICKNESS OF OVERTBURDEN 60.3' (Water 40.8') | | | | 16. DATE HOLE STARTED 26 JAN 92 COMPLETED 26 JAN 92 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 17. ELEVATION TOP OF HOLE 0.0' | | |
| 9. TOTAL DEPTH OF HOLE 60.3' | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | |
| | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | |
| ELEVATION 0.0 | DEPTH 0.0 | LEGEND e | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. UAR | REMARKS (Drilling time, water loss, depth of weathering, etc. If significant) |
| | | | Water | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 41.1'. |
| -40.8' | 40 | | Bottom of Harbor 40.8' | | 1 | 22 |
| -43.8' | 45 | | (SC) Olive grey, fine clayey SAND. Some silt. Trace of mica. | | 2 | 38 |
| -48.3' | 48 | | Grey. | | 3 | 41 |
| -50 | 44 | | Trace of silt. | | 4 | 48 |
| -55 | 42 | | | | 5 | 52 |
| -60.3' | 54 | | | | | 54 |
| | 68 | | | | | 68 |
| | 66 | | | | | 66 |
| | 76 | | | | | 76 |
| | 82 | | | | | 82 |
| | 76 | | | | | 76 |
| | | | Bottom of Boring 60.3' | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. splitspoon w/140 lb. hammer falling 30". |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | |

| DRILLING LOG | | | VISION SOUTH ATLANTIC | | INSTALLATION SAVANNAH, GA. | | Hole No. SH-1/U |
|--|--------------|-------------|--|--|---|---|---|
| | | | | | | | SHEET 1 OF 1 SHEETS |
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " SPLIT SPOON, $5\frac{1}{2}$ " FISHTAIL | | |
| 2. LOCATION (Coordinates or Station) X-818643 Y-776483 GA. EAST | | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | | SH-170 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 5 | | DISTURBED UNDISTURBED 0 |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | | 14. TOTAL NUMBER CORE BOXES 0 | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED | | | DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | |
| 7. THICKNESS OF OVERTBURDEN | | | 59.8' (Water 41.8') | | 16. DATE HOLE STARTED 17 NOV 91 | | COMPLETED 17 NOV 91 |
| 8. DEPTH DRILLED INTO ROCK | | | 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | |
| 9. TOTAL DEPTH OF HOLE | | | 59.8' | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | % |
| ELEVATION 0.0 | DEPTH 0.0 | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | | % CORE RECOV- ERY • | BOX OR SAMPLE NO. UAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g |
| | | | Water | | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 42.6'. |
| -41.8' | 40 | | Bottom of Harbor 41.8' | | | | |
| -44.8' | 45 | | (CL) Greenish-grey, silty lean CLAY. Trace of mica & fine sand. | | 1 | | |
| -59.8' | 50 | | (SC) Greenish-grey, fine clayey SAND. Some silt, trace of mica. | | 2 | | |
| | 55 | | | | 3 | | |
| | 59.8' | | | | 4 | | |
| | 60 | | Bottom of Boring 59.8' | | 5 | | |
| | | | | | | BLOWS PER FOOT: | |
| | | | | | | Number required to drive $1\frac{1}{8}$ " I.D. split spoon w/140 lb. hammer falling 30". | |
| NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | | | | | |

| DRILLING LOG | | VISION SOUTH ATLANTIC | | INSTALLATION | SAVANNAH, GA. | | SHEET 1 OF 1 SHEETS |
|--|-------|--------------------------|--|--|-------------------------|---|------------------------|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " split spoon, $5\frac{1}{2}$ " fishtail | | | |
| 2. LOCATION (Coordinates or Station) X-817736 Y-776361 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL FAILING 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | SH-171 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 6 DISTURBED 0 UNDISTURBED | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERBURDEN 60.5' (WATER 39.5') | | | | 16. DATE HOLE STARTED 14 DEC 91 COMPLETED 14 DEC 91 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 60.5' | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A % | | | |
| | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY JAR | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | |
| 0.0 | 0 | c | | | | BLOWS | |
| | | | Water | | | Scale change at 35.0'. Set 6" diameter casing by own weight to 45.7'. | |
| 35 | | | | | | | |
| -39.5' | 40 | | Bottom of Harbor 39.5' | | | | |
| -44.5' | 45 | | (MH) Dark grey, clayey SILT. | 1 | | Weight of rods drove split spoon from 39.5' to 45.5'. | |
| -45.5' | 45 | | (SC) Dark grey, fine to medium clayey SAND. | 2 | | 0 | |
| -48.5' | 50 | | (CH) Grey, fat CLAY. Some silt & fine sand. | 3 | | 5 | |
| | 50 | | (SC) Grey, fine clayey SAND. | 4 | | 5 | |
| | 55 | | | 5 | | 38 | |
| | 55 | | | 6 | | 49 | |
| | 60 | | Bottom of Boring 60.5' | | | 49 | |
| | 60 | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | 56 | |
| | 60 | | | | | 42 | |
| | 60 | | | | | 48 | |
| | 60 | | | | | 41 | |
| | 60 | | | | | 44 | |
| | 60 | | | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. split spoon w/140 lb. hammer falling 30". | |

| DRILLING LOG | | | VISION SOUTH ATLANTIC | | INSTALLATION SAVANNAH, GA. | HOLE NO. 37-14 | SHEET 1 OF 1 SHEETS |
|--|--------------|-------------|--|--|---|--------------------------------|---|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | | 10. SIZE AND TYPE OF BIT 1½" SPLIT SPOON, 5½" FISHTAIL | | |
| 2. LOCATION (Coordinates or Station) X-818054 Y-775978 | | | GA. EAST | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Falling 314 | | |
| 4. HOLE NO. (As shown on drawing title and file number) | | | SH-172 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 4 UNDISTURBED 0 | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | | 14. TOTAL NUMBER CORE BOXES 0 | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | | | 15. ELEVATION GROUND WATER N/A | | |
| 7. THICKNESS OF OVERTBURDEN 59.9' (Water 43.4') | | | | | 16. DATE HOLE STARTED 25 JAN 92 COMPLETED 25 JAN 92 | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | | 17. ELEVATION TOP OF HOLE 0.0' | | |
| 9. TOTAL DEPTH OF HOLE 59.9' | | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | |
| | | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | |
| ELEVATION 0.0 | DEPTH 0.0 | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | | % CORE RECOV- ERY • | BOX OR SAMPLE NO. JAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g |
| | | | | | | | BLOWS |
| | | | Water | | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 44.3'. |
| | 40 | | | | | | 0 |
| | -43.4' | | Bottom of Harbor 43.4' | | | | 27 |
| | 45 | | (CL) Dark grey, silty lean CLAY. Some fine sand. | | | 1 | 99 |
| | -47.9' | | Dark (SC)-Olive-grey, fine clayey SAND. Some silt, trace of mica. | | | 2 | 32 |
| | 50 | | Olive-grey. | | | 3 | 31 |
| | 55 | | | | | | 90 |
| | 59.9' | | Bottom of Boring 59.9' NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | 4 | 89 |
| | 60 | | | | | | 100/0.6 |
| | | | | | | | 100/0.9 |
| | | | | | | | 90 |
| | | | | | | | 54 |
| | | | | | | | 39 |
| | | | | | | | BLOWS PER FOOT: |
| | | | | | | | Number required to drive 1½" I.D. split spoon w/140 lb. hammer falling 30". |

Hole NO. 37-173

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | | INSTALLATION SAVANNAH, GA. | | SHEET 1 OF 1 SHEETS | |
|--|-------|----------------------------|--|--|--------------------------------|--|--|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | | | 10. SIZE AND TYPE OF BIT $1\frac{1}{8}$ " SPLIT SPOON, $5\frac{1}{2}$ " FISHTAIL | | | |
| 2. LOCATION (Coordinates or Station) X-818264 Y-775913 GA. EAST | | | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-173 | | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN 15 DISTURBED 0 UNDISTURBED 0 | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | | | 14. TOTAL NUMBER CORE BOXES 0 | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | | 15. ELEVATION GROUND WATER N/A | | | |
| 7. THICKNESS OF OVERTBURDEN 59.8' (Water 44.4') | | | | 16. DATE HOLE STARTED 27 JAN 92 COMPLETED 27 JAN 92 | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | | | 17. ELEVATION TOP OF HOLE 0.0' | | | |
| 9. TOTAL DEPTH OF HOLE 59.8' | | | | 18. TOTAL CORE RECOVERY FOR BORING N/A % | | | |
| | | | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. UAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | |
| 0.0 | 0.0 | c | Water | * | | BLOWS | |
| | | | Bottom of Harbor 44.4' | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 48.2'. | |
| -44.4' | 45 | | (MH) Very dark grey to black clayey SILT. | 1 | | Weight of rods drove split spoon from 44.4' to 47.9'. Jar sample 2 taken from approx. 47.5' to 47.9'. | |
| -47.5' | 50 | | (SC) Dark grey, fine clayey SAND. Trace of silt. | 2 | | 0 | |
| | 55 | | | 3 | | 18 | |
| | 55 | | | 4 | | 49 | |
| | 55 | | | 5 | | 94 | |
| | 55 | | | | | 99 | |
| | 55 | | | | | 71 | |
| | 55 | | | | | 81 | |
| | 55 | | | | | 89 | |
| -59.8' | 60 | | Bottom of Boring 59.8' | | | 100/0.9 | |
| | 60 | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | BLOWS PER FOOT: Number required to drive $1\frac{1}{8}$ " I.D. split spoon w/140 lb. hammer falling 30". | |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | HOLE NO. 37-17 | | |
|--|--------------|---|---|------------------------------|--------------------------------|--|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | 10. SIZE AND TYPE OF BIT 1 1/8" SPLITSPOON, 5/2" FISHTAIL | | SHEET 1 OF 1 SHEETS | | |
| 2. LOCATION (Coordinates or Station) X-818856 Y-775859 GA. EAST | | 11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW | | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-174 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 6 UNDISTURBED 0 | | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | 14. TOTAL NUMBER CORE BOXES 0 | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | | | |
| 7. THICKNESS OF OVERTBURDEN 59.6' (Water 41.6') | | 16. DATE HOLE STARTED 27 JAN 92 COMPLETED 27 JAN 92 | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | | | |
| 9. TOTAL DEPTH OF HOLE 59.6' | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | | |
| | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | | |
| ELEVATION 0.0 | DEPTH 0.0 | LEGEND e | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY • | BOX OR SAMPLE NO. UAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g |
| | | | Water | | | Blows |
| | | | Bottom of Harbor 41.6' | | | |
| -41.6' | | | (SC) Dark grey, fine clayey SAND. Some silt, trace of mica. | | 1 | |
| -43.1' | | | (SM) Dark grey, fine silty SAND. Some clay & mica. | | 2 | |
| -45 | | | | | 3 | |
| -46.1' | | | (SC) Grey, fine clayey SAND. Trace of silt. | | 4 | |
| -49.1' | | | | | 5 | |
| -50 | | | | | 6 | |
| 55 | | | | | | |
| -59.6' | 60 | | Dark grey. | | | |
| | | | Bottom of Boring 59.6' | | | |
| NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | | | | BLOWS PER FOOT: Number required to drive 1 1/8" I.D. split spoon w/140 lb. hammer falling 30". |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | INSTALLATION SAVANNAH, GA. | SHEET 1 OF 1 SHEETS | | | |
|--|------------|---|--|------------------------------|--------------------------------|---|-------|
| 1. PROJECT SAVANNAH HARBOR DEEPENING | | 10. SIZE AND TYPE OF BIT 1 $\frac{1}{8}$ " SPLITSPOON, 5 $\frac{1}{2}$ " FISHTAIL | | | | | |
| 2. LOCATION (Coordinates or Station) X-818516 Y-775447 GA. EAST | | 11. DATUM FOR ELEVATION SHOWN (TBM or NSL) MLW | | | | | |
| 3. DRILLING AGENCY SAVANNAH DISTRICT | | 12. MANUFACTURER'S DESIGNATION OF DRILL Failing 314 | | | | | |
| 4. HOLE NO. (As shown on drawing title and file number) SH-175 | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN DISTURBED 5 UNDISTURBED 0 | | | | | |
| 5. NAME OF DRILLER DAVID JUSTISS | | 14. TOTAL NUMBER CORE BOXES 0 | | | | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 15. ELEVATION GROUND WATER N/A | | | | | |
| 7. THICKNESS OF OVERTBURDEN 60.1' (Water 43.6') | | 16. DATE HOLE STARTED 17 NOV 91 COMPLETED 17 NOV 91 | | | | | |
| 8. DEPTH DRILLED INTO ROCK 0.0' | | 17. ELEVATION TOP OF HOLE 0.0' | | | | | |
| 9. TOTAL DEPTH OF HOLE 60.1' | | 18. TOTAL CORE RECOVERY FOR BORING N/A | | | | | |
| | | 19. SIGNATURE OF INSPECTOR JAMES ARTHUR, P.G. | | | | | |
| ELEVATION 0.0 | DEPTH 0 | LEGEND c | CLASSIFICATION OF MATERIALS (Description) d | % CORE RECOV- ERY • | BOX OR SAMPLE NO. UAR | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | BLOWS |
| | | | Water | | | Scale change at 40.0'. Set 6" diameter casing by own weight to 44.1'. | |
| 40 | | | | | | | |
| -43.6' | | | Bottom of Harbor 43.6' | | | | |
| -45.1' | 45 | | (SC) Greenish-grey, fine clayey SAND. Some silt, trace of mica. | 1 | | | 24 |
| -46.6' | 46 | | Light olive to greenish-grey. | | | | 37 |
| | 50 | | Greenish-grey. | 2 | | | 42 |
| | 55 | | | | 3 | | 42 |
| | 57 | | | | 4 | | 49 |
| | 58 | | | | | | 74 |
| | 59 | | | | | | 50 |
| | 60 | | | | | | 57 |
| -60.1' | 60 | | Bottom of Boring 60.1' | | | | 77 |
| | | | NOTE: Soils visually field classified in accordance with the Unified Soil Classification System. | | | | 77 |
| | | | | | | | 90 |
| | | | | | | BLOWS PER FOOT: Number required to drive 1 $\frac{1}{8}$ " I.D. split spoon w/140 lb. hammer falling 30". | |

| DRILLING LOG | | DIVISION SOUTH ATLANTIC | | INSTALLATION BAVANNAH RIVER HARBOR | | Hole No. <i>CS-1</i> |
|--|-------|---|--|---|-------------------------|--|
| PROJECT <i>MAGS ISLAND TIKING ASS'N</i> | | 2. LOCATION (Coordinates or Station) <i>OF 1000 FT STA. 1001750</i> <i>1 1/2' NORTH EAST OF BLINN'S BAY IP</i> | | 10. SIZE AND TYPE OF BIT <i>1 1/2" IR SPLIT SPOON</i> | | SHEET 1 OF 2 SHEETS |
| 3. DRILLING AGENCY <i>SPARVNO DISTRICT</i> | | 4. HOLE NO. (As shown on drawing title and file number) <i>CS 1</i> | | 11. DATUM FOR ELEVATION SHOWN (TBM or MLW) <i>11 LIV</i> | | |
| 5. NAME OF DRILLER <i>J. Mc DONALD</i> | | | | 12. MANUFACTURER'S DESIGNATION OF DRILL <i>CPPD. OF F HENNAO</i> | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT. | | | | 13. TOTAL NO. OF OVER- BURDEN SAMPLES TAKEN | | DISTURBED <i>5</i> UNDISTURBED <i>0</i> |
| 7. THICKNESS OF OVERTURDEN | | | | 14. TOTAL NUMBER CORE BOXES | | |
| 8. DEPTH DRILLED INTO ROCK | | | | 15. ELEVATION GROUND WATER | | |
| 9. TOTAL DEPTH OF HOLE <i>45.1' BELOW MLW</i> | | | | 16. DATE HOLE STARTED <i>3 MARCH 1973</i> | | COMPLETED <i>3 MARCH 1973</i> |
| | | | | 17. ELEVATION TOP OF HOLE <i>0.0' MLW</i> | | |
| | | | | 18. TOTAL CORE RECOVERY FOR BORING | | |
| | | | | 19. SIGNATURE OF INSPECTOR <i>Chas. D. Griffin</i> | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV- ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| | | | | | | BLOWS |
| -5 | | | | | | |
| -10 | | | | | | |
| -13.6 | | | | | | |
| -15 | | | <i>- WATER</i> | | | |
| -20 | | | <i>SM. GRAY SILTY FINE & MEDIUM SAND</i> | | 1 | |
| -25 | | | <i>W/ GREEN</i> | | 2 | 88 |
| -30 | | | <i>OLIVE GREEN</i> | | 3 | 79 |
| | | | | | 4 | 81 |
| | | | | | | 68 |
| | | | | | | 76 |
| | | | | | | 84 |
| | | | | | | 93 |
| | | | | | | 100 |
| | | | | | | 89 |
| | | | | | | 63 |
| | | | | | | 74 |
| <i>CONTINUED ON SHEET NO 2</i> | | | | | | |

DRILLING LOG (Cont Sheet 2) ON TOP OF HOLE -13.6 BELOW MLW. Hole No. CS 1

PROJECT: KING ISLAND TIN MINE, EPMN | INSTALLATION: CIVILIAN DIVEE HIGHWAY | SHEET 2
OR 2 SHEETS

| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOV. ERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) | R BLOWS |
|-----------|-------|--------|--|-------------------------|-------------------------|--|---------|
| a | b | c | d | e | f | | |
| | | | SM - OLIVE GREEN SILTY FINE SAND | | | | 100 |
| 35 | | | | | | | 99 |
| | | | | | | | 88 |
| | | | | | | | 100 |
| | | | | | | | 94 |
| | | | | | | | 88 |
| 40 | | | | | 5 | | 93 |
| | | | | | | | 76 |
| | | | | | | | 94 |
| 45 | | | | | | | 98 |

NOTE: Soils field classified
in accordance with the Unified
Soil Classification System.

BLOWS PER FOOT:

Number required to drive
1 1/2" ID splitspoon w/140 lb.
hammer falling 30"

| DRILLING LOG | | DIVISION | INSTALLATION | | Hole No. | CS 2 | |
|---|-------|-----------------|---|--|-------------------|-------------------|---|
| PROJECT | | | | | SHEET / OF SHEETS | | |
| Kunlun Island Terminal Basalt | | | 10. SIZE AND TYPE OF BIT | | 10' 2" C 100 | | |
| 2. LOCATION (Coordinates or Site No.) 100' NE of ON 16 Perry, 350' E LINE PINE-LESS FOREST | | | 11. DAYUM FOR ELEVATION SHOWN (TBM = ASL) | | 11' 0" | | |
| 3. DRILLING AGENCY | | | 12. MANUFACTURER'S DESIGNATION OF DRILL | | SP-100 | | |
| S. T. M. Drilling | | CS-2 | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN | | DISTURBED | UNDISTURBED | |
| 4. HOLE NO. (As shown on drawing title and file number) | | | 14. TOTAL NUMBER CORE BOXES | | 0 | | |
| 5. NAME OF DRILLER | | CS-2 | 15. ELEVATION GROUND WATER | | In River | | |
| Mc Donell | | | 16. DATE HOLE | | STARTED | COMPLETED | |
| 6. DIRECTION OF HOLE | | | 17. ELEVATION TOP OF HOLE | | 5 April 1973 | 11' 0" | |
| <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED | | DEG. FROM VERT. | 18. TOTAL CORE RECOVERY FOR BORING | | 0.0' MLW | | |
| 7. THICKNESS OF OVERTBURDEN | | | 19. SIGNATURE OF INSPECTOR | | S. T. M. Drilling | | |
| 8. DEPTH DRILLED INTO ROCK | | | | | | | |
| 9. TOTAL DEPTH OF HOLE | | 45.0' | | | | | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | | % CORE RECOVERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0' | | | | | | | 30' 60' 40' 71' 65' 45' 25' 15' 10' 5' Water |
| 5' | | | | | | | |
| 10' | | | | | | | |
| 15' | | | | | | | |
| 20' | | | Water depth 17.6' at MLW SP-Tan poorly graded sand | | 100 | 1 | 30' 60' 40' 71' 65' 45' 25' 15' 10' 5' Water |
| 25' | | | ML - Green & Gray fine sandy silt micaceous slight plasticity | | 100 | 2 | 30' 60' 40' 71' 65' 45' 25' 15' 10' 5' Water |
| 30' | | | SM - Green & Gray silty fine sand micaceous slight plasticity | | 100 | 3 | 30' 60' 40' 71' 65' 45' 25' 15' 10' 5' Water |
| | | | | | 100 | 4 | 30' 60' 40' 71' 65' 45' 25' 15' 10' 5' Water |
| | | | | | 100 | 5 | 30' 60' 40' 71' 65' 45' 25' 15' 10' 5' Water |

Hole No. CS - 2

| | | | | | |
|--|----------|---|---|-------------------|---|
| DRILLING LOG | DIVISION | INSTALLATION | SHEET OF | | |
| 1. PROJECT <i>Kings Island</i> | | 14. SIZE AND TYPE OF BIT <i>1 1/2"</i> | | | |
| 2. LOCATION (Coordinates or Station) <i>5000 T 12 R.</i> | | 15. DATUM FOR ELEVATION (TBM or MSL.) <i>11.1</i> | | | |
| 3. DRILLING AGENCY <i>Soil Test Inc.</i> | | 16. MANUFACTURER'S DESIGNATION OF DRILL | | | |
| 4. HOLE NO. (As shown on drawing title and file number) | CS-2 | 17. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN | 5 DISTURBED UNDISTURBED | | |
| 5. NAME OF DRILLER <i>MS Davis!!</i> | | 18. TOTAL NUMBER CORE BOXES | 0 | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | 19. ELEVATION GROUND WATER | <i>11.1'</i> | | |
| 7. THICKNESS OF OVERTBURDEN | | 20. DATE HOLE | STARTED 5A.M. / 73 COMPLETED 11 A.M. / 73 | | |
| 8. DEPTH DRILLED INTO ROCK | | 21. ELEVATION TOP OF HOLE | <i>11.1' + 10.6' = 21.7'</i> | | |
| 9. TOTAL DEPTH OF HOLE CS.D' | | 22. TOTAL CORE RECOVERY FOR BORING | <i>50%</i> | | |
| 10. ELEVATION | DEPTH | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOVERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 30' | 30' | | 62 | 6 | |
| 35' | 35' | ML-Green & Gray fine sandy silt micaceous slight plasticity | 62 | 6 | |
| 40' | 40' | | 75 | | |
| 45' | 45' | | 62 | | |
| 50' | 50' | | 140 | | |
| 55' | 55' | | 5 | | |
| 60' | 60' | | 46 | | |
| 65' | 65' | | 44 | | |
| 70' | 70' | | 47 | | |
| 75' | 75' | | 50 | | |
| 80' | 80' | | 52 | | |
| 85' | 85' | | | | |
| 90' | 90' | | | | |
| 95' | 95' | | | | |
| 100' | 100' | | | | |
| 105' | 105' | | | | |
| 110' | 110' | | | | |
| 115' | 115' | | | | |
| 120' | 120' | | | | |
| 125' | 125' | | | | |
| 130' | 130' | | | | |
| 135' | 135' | | | | |
| 140' | 140' | | | | |
| 145' | 145' | | | | |
| 150' | 150' | | | | |
| 155' | 155' | | | | |
| 160' | 160' | | | | |
| 165' | 165' | | | | |
| 170' | 170' | | | | |
| 175' | 175' | | | | |
| 180' | 180' | | | | |
| 185' | 185' | | | | |
| 190' | 190' | | | | |
| 195' | 195' | | | | |
| 200' | 200' | | | | |
| 205' | 205' | | | | |
| 210' | 210' | | | | |
| 215' | 215' | | | | |
| 220' | 220' | | | | |
| 225' | 225' | | | | |
| 230' | 230' | | | | |
| 235' | 235' | | | | |
| 240' | 240' | | | | |
| 245' | 245' | | | | |
| 250' | 250' | | | | |
| 255' | 255' | | | | |
| 260' | 260' | | | | |
| 265' | 265' | | | | |
| 270' | 270' | | | | |
| 275' | 275' | | | | |
| 280' | 280' | | | | |
| 285' | 285' | | | | |
| 290' | 290' | | | | |
| 295' | 295' | | | | |
| 300' | 300' | | | | |
| 305' | 305' | | | | |
| 310' | 310' | | | | |
| 315' | 315' | | | | |
| 320' | 320' | | | | |
| 325' | 325' | | | | |
| 330' | 330' | | | | |
| 335' | 335' | | | | |
| 340' | 340' | | | | |
| 345' | 345' | | | | |
| 350' | 350' | | | | |
| 355' | 355' | | | | |
| 360' | 360' | | | | |
| 365' | 365' | | | | |
| 370' | 370' | | | | |
| 375' | 375' | | | | |
| 380' | 380' | | | | |
| 385' | 385' | | | | |
| 390' | 390' | | | | |
| 395' | 395' | | | | |
| 400' | 400' | | | | |
| 405' | 405' | | | | |
| 410' | 410' | | | | |
| 415' | 415' | | | | |
| 420' | 420' | | | | |
| 425' | 425' | | | | |
| 430' | 430' | | | | |
| 435' | 435' | | | | |
| 440' | 440' | | | | |
| 445' | 445' | | | | |
| 450' | 450' | | | | |
| 455' | 455' | | | | |
| 460' | 460' | | | | |
| 465' | 465' | | | | |
| 470' | 470' | | | | |
| 475' | 475' | | | | |
| 480' | 480' | | | | |
| 485' | 485' | | | | |
| 490' | 490' | | | | |
| 495' | 495' | | | | |
| 500' | 500' | | | | |
| 505' | 505' | | | | |
| 510' | 510' | | | | |
| 515' | 515' | | | | |
| 520' | 520' | | | | |
| 525' | 525' | | | | |
| 530' | 530' | | | | |
| 535' | 535' | | | | |
| 540' | 540' | | | | |
| 545' | 545' | | | | |
| 550' | 550' | | | | |
| 555' | 555' | | | | |
| 560' | 560' | | | | |
| 565' | 565' | | | | |
| 570' | 570' | | | | |
| 575' | 575' | | | | |
| 580' | 580' | | | | |
| 585' | 585' | | | | |
| 590' | 590' | | | | |
| 595' | 595' | | | | |
| 600' | 600' | | | | |
| 605' | 605' | | | | |
| 610' | 610' | | | | |
| 615' | 615' | | | | |
| 620' | 620' | | | | |
| 625' | 625' | | | | |
| 630' | 630' | | | | |
| 635' | 635' | | | | |
| 640' | 640' | | | | |
| 645' | 645' | | | | |
| 650' | 650' | | | | |
| 655' | 655' | | | | |
| 660' | 660' | | | | |
| 665' | 665' | | | | |
| 670' | 670' | | | | |
| 675' | 675' | | | | |
| 680' | 680' | | | | |
| 685' | 685' | | | | |
| 690' | 690' | | | | |
| 695' | 695' | | | | |
| 700' | 700' | | | | |
| 705' | 705' | | | | |
| 710' | 710' | | | | |
| 715' | 715' | | | | |
| 720' | 720' | | | | |
| 725' | 725' | | | | |
| 730' | 730' | | | | |
| 735' | 735' | | | | |
| 740' | 740' | | | | |
| 745' | 745' | | | | |
| 750' | 750' | | | | |
| 755' | 755' | | | | |
| 760' | 760' | | | | |
| 765' | 765' | | | | |
| 770' | 770' | | | | |
| 775' | 775' | | | | |
| 780' | 780' | | | | |
| 785' | 785' | | | | |
| 790' | 790' | | | | |
| 795' | 795' | | | | |
| 800' | 800' | | | | |
| 805' | 805' | | | | |
| 810' | 810' | | | | |
| 815' | 815' | | | | |
| 820' | 820' | | | | |
| 825' | 825' | | | | |
| 830' | 830' | | | | |
| 835' | 835' | | | | |
| 840' | 840' | | | | |
| 845' | 845' | | | | |
| 850' | 850' | | | | |
| 855' | 855' | | | | |
| 860' | 860' | | | | |
| 865' | 865' | | | | |
| 870' | 870' | | | | |
| 875' | 875' | | | | |
| 880' | 880' | | | | |
| 885' | 885' | | | | |
| 890' | 890' | | | | |
| 895' | 895' | | | | |
| 900' | 900' | | | | |
| 905' | 905' | | | | |
| 910' | 910' | | | | |
| 915' | 915' | | | | |
| 920' | 920' | | | | |
| 925' | 925' | | | | |
| 930' | 930' | | | | |
| 935' | 935' | | | | |
| 940' | 940' | | | | |
| 945' | 945' | | | | |
| 950' | 950' | | | | |
| 955' | 955' | | | | |
| 960' | 960' | | | | |
| 965' | 965' | | | | |
| 970' | 970' | | | | |
| 975' | 975' | | | | |
| 980' | 980' | | | | |
| 985' | 985' | | | | |
| 990' | 990' | | | | |
| 995' | 995' | | | | |
| 1000' | 1000' | | | | |

Soils field classified in accordance with the Unified Soil Classification System.

BLOWS PER FOOT:
Number required to drive 1 1/2" ID split spoon w/140 lb. hammer falling 30".

| DRILLING LOG | | | DIVISION South Atlantic | Hole No. CS-3 |
|--|-------|--------|---|---|
| 1. PROJECT Kings Island - Thomasville | | | INSTALLATION Savannah River | SHEET 1 OF 7 SHEETS |
| 2. LOCATION (Coordinates or Station) CYPRELLITE STA. 1001000 | | | IN SIZE AND TYPE OF BIT 11. DATUM FOR ELEVATION SHOWN (TBM OR MSL) 171.11 | |
| 1. APPROX. DEP. FROM WATER EDGE | | | 12. MANUFACTURER'S DESIGNATION OF DRILL Cutter 125, 111 | |
| 2. DRILLING AGENCY Savannah District | | | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN DISTURBED 6 UNDISTURBED | |
| 4. HOLE NO. (As shown on drawing title and file number) CS-3 | | | 14. TOTAL NUMBER CORE BOXES 0 | |
| 5. NAME OF DRILLER M.S. Driller | | | 15. ELEVATION GROUND WATER IN RIVER | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERT. | | | 16. DATE HOLE STARTED COMPLETED 17 Nov 1973 19 Dec 1973 | |
| 7. THICKNESS OF OVERTBURDEN | | | 17. ELEVATION TOP OF HOLE 0.0 3' MLW | |
| 8. DEPTH DRILLED INTO ROCK | | | 18. TOTAL CORE RECOVERY FOR BORING | |
| 9. TOTAL DEPTH OF HOLE 41.9' | | | 19. SIGNATURE OF INSPECTOR E. J. and M. B. and S. J. and S. J. | |
| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | Z CORE RECOV. REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
| 0' | 0' | | | |
| 5' | 5' | | Water | |
| 10' | 10' | | | |
| 15' | 15' | | | |
| 20' | 20' | | Water depth 11.9' MLW | |
| 25' | 25' | | SM - Gray & Green silt, fine sand micaceous, slight plasticity, when wet | 42 |
| 30' | 30' | | | 45 |
| | | | | 48 |
| | | | | 52 |
| | | | | 58 |
| | | | | 65 |
| | | | | 67 |
| | | | | 70 |
| | | | | 72 |
| | | | | |

Hole No. CS-3

| | | | |
|--|---|-------------------------------------|--|
| DRILLING LOG | DIVISION South ATLANTIC | INSTALLATION Savannah River | SHEET NO 1 OF 2 SH |
| 1. PROJECT <i>Kings Island Turning Basin</i> | M. SIZE AND TYPE OF BIT 11. DATUM FOR ELEVATION SHOWN (TMM = MSL) <i>191.41</i> | | |
| 2. LOCATION (Coordinates or Station) <i>58c P1/2</i> | 12. MANUFACTURER'S DESIGNATION OF DRILL <i>Spiral</i> | | |
| 3. DRILLING AGENCY <i>Geological Survey</i> | 13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN DISTURBED UNDISTURBED <i>6</i> | | |
| 4. HOLE NO. (As shown on drawing title and file number) | 14. TOTAL NUMBER CORE BOXES <i>0</i> | | |
| 5. NAME OF DRILLER <i>M.C. Donald</i> | 15. ELEVATION GROUND WATER IN FEET <i>In Tides</i> | | |
| 6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED | DEG. FROM VERT. | 16. DATE HOLE <i>19 Nov. 173</i> | STARTED COMPLETED <i>19 Nov. 173</i> |
| 7. THICKNESS OF OVERTURDEN | 17. ELEVATION TOP OF HOLE D.O. of 191.41 W | | |
| 8. DEPTH DRILLED INTO ROCK | 18. TOTAL CORE RECOVERY FOR BORING | | |
| 9. TOTAL DEPTH OF HOLE <i>146.91</i> | 19. SIGNATURE OF INSPECTOR <i>S. J. McDonald</i> | | |

| ELEVATION | DEPTH | LEGEND | CLASSIFICATION OF MATERIALS (Description) | % CORE RECOVERY | BOX OR SAMPLE NO. | REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) |
|-----------|-------|--------|---|-----------------|-------------------|---|
| 130' | 130' | | | | 1 | 13 |
| 57' | 73' | | | | | 57 |
| 60' | 80' | | | | | 60 |
| 73' | 90' | | SM - Gray & Green silty fine sand micaceous slight plasticity when wet | | | 73 |
| 70' | 95' | | Cut out to steep with fish tail | | 5 | 70 |
| 65' | 100' | | SM - Gray & Green silty fine sand micaceous | 6 | | 65 |
| 61' | 100' | | Soils field classified in accordance with the Unified Soil Classification System. | | | 61 |
| | | | | | | BLOWS PER FOOT: Number required to drive 1 1/2" ID splitspoon w/140 lb hammer falling 30". |